

CABLE-FCN40/4X14/.../IM/MEL

System cable



Data sheet
105346_en_01

© PHOENIX CONTACT 2012-08-13

1 Description

Assembled round cable for connecting 4 x 8 channels of the PLCs listed below. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK socket strips. It is available in various lengths of 0.5 m ... 10 m.

Scope of use

You can connect the following I/O cards:

PLC	I/O card
Mitsubishi Melsec L	LX41C4 and LX42C4 (common plus terminal B01, B02) LY41NT1P, LY42NT1P, LY41PT1P, LY42PT1P
Mitsubishi Melsec Q	QX41, QX41-S1, QX42, QX42-S1 QY41P (24 V), QY42P (24 V), QH42P (24 V)
Honeywell ML 200	2MLQ-TR4A, 2MLQ-TR8A, 2MLQ-TR4B (24 V), 2MLQ-TR8B (24 V)



Make sure you always use the latest documentation.
It can be downloaded at www.phoenixcontact.net/catalog.



This data sheet is valid for all products listed on the following page:

2 Ordering data

Description	Type	Order No.	Pcs. / Pkt.
Assembled round cable for connecting 4 x 8 channels in the Mitsubishi Melsec L and Melsec Q PLC. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK socket strips, length: 0.5 m.	CABLE-FCN40/4X14/ 0,5M/IM/MEL	2903502	1
Assembled round cable for connecting 4 x 8 channels in the Mitsubishi Melsec L and Melsec Q PLC. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK socket strips, length: 1 m	CABLE-FCN40/4X14/ 1,0M/IM/MEL	2903503	1
Assembled round cable for connecting 4 x 8 channels in the Mitsubishi Melsec L and Melsec Q PLC. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK socket strips, length: 2 m	CABLE-FCN40/4X14/ 2,0M/IM/MEL	2903504	1
Assembled round cable for connecting 4 x 8 channels in the Mitsubishi Melsec L and Melsec Q PLC. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK socket strips, length: 3 m	CABLE-FCN40/4X14/ 3,0M/IM/MEL	2903505	1
Assembled round cable for connecting 4 x 8 channels in the Mitsubishi Melsec L and Melsec Q PLC. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK socket strips, length: 4 m	CABLE-FCN40/4X14/ 4,0M/IM/MEL	2903506	1
Assembled round cable for connecting 4 x 8 channels in the Mitsubishi Melsec L and Melsec Q PLC. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK socket strips, length: 6 m	CABLE-FCN40/4X14/ 6,0M/IM/MEL	2903507	1
Assembled round cable for connecting 4 x 8 channels in the Mitsubishi Melsec L and Melsec Q PLC. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK socket strips, length: 8 m	CABLE-FCN40/4X14/ 8,0M/IM/MEL	2903508	1
Assembled round cable for connecting 4 x 8 channels in the Mitsubishi Melsec L and Melsec Q PLC. The system cable has one 40-pos. Fujitsu strip and four 14-pos. FLK socket strips, length: 10 m	CABLE-FCN40/4X14/10,0M/IM/MEL	2903509	1

3 Technical data

Supply	
Nominal voltage	< 50 V AC / 60 V DC
Max. current per branch	1 A
Max. total current	2 A
General data	
Ambient temperature (operation)	-20 °C ... 50 °C
Standards/regulations	DIN EN 60352-4 DIN EN 60603-1
Max. conductor resistance	0.16 Ω / m
Connection data	
Connection	4 x 14-pos. IDC/FLK socket strip (2.54 mm) (module side) 40-pos. Fujitsu plug connector (controller side)
Conductor cross section solid / stranded / AWG	10 x 0.14 mm ² / 10 x 0.14 mm ² / 26

4 Connections

Socket strip (X1)	Bridges	Conductor color	FLK 14 (X2) Byte 0	FLK 14 (X3) Byte 1	FLK 14 (X4) Byte 2	FLK 14 (X5) Byte 3	
PIN B20		black	PIN 1				
PIN B19		brown	PIN 2				
PIN B18		red	PIN 3				
PIN B17		orange	PIN 4				
PIN B16		yellow	PIN 5				
PIN B15		green	PIN 6				
PIN B14		blue	PIN 7				
PIN B13		violet	PIN 8				
PIN B01		grey	PIN 9				
PIN A01		white	PIN10				
PIN B12		black			PIN 1		
PIN B11		brown			PIN 2		
PIN B10		red			PIN 3		
PIN B09		orange			PIN 4		
PIN B08		yellow			PIN 5		
PIN B07		green			PIN 6		
PIN B06		blue			PIN 7		
PIN B05		violet			PIN 8		
		grey			PIN 9		
		white			PIN10		
PIN A20	black				PIN 1		
PIN A19	brown				PIN 2		
PIN A18	red				PIN 3		
PIN A17	orange				PIN 4		
PIN A16	yellow				PIN 5		
PIN A15	green				PIN 6		
PIN A14	blue				PIN 7		
PIN A13	violet				PIN 8		
PIN B02	grey				PIN 9		
PIN A02	white				PIN10		
PIN A12	black					PIN 1	
PIN A11	brown					PIN 2	
PIN A10	red					PIN 3	
PIN A09	orange					PIN 4	
PIN A08	yellow					PIN 5	
PIN A07	green					PIN 6	
PIN A06	blue					PIN 7	
PIN A05	violet					PIN 8	
	grey					PIN 9	
	white					PIN10	