

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY -

ALL RIGHTS RESERVED.

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	A	INITIAL	25MAR2015	DW	CW
	B	ECR-15-018270	07DEC2015	DW	CW

NOTES:

- TECHNICAL CHARACTERISTICS:
INSULATION MATERIAL: PC
RATED VOLTAGE: 400V
RATED CURRENT: 16A
INSULATION RESISTANCE: $\geq 400M\Omega$
RATED IMPULSE VOLTAGE: 6KV
POLLUTION DEGREE: 3
FLAMMABILITY: UL94V-0
MATING CYCLES: 500 CYCLES
OPERATION TEMPERATURE: $-40\sim+125^{\circ}C$
WIRE RANGE: $0.14\sim 4\text{ mm}^2$ (26~12 AWG)
CONTACT TYPE: CRIMP CONTACT
- CONTACT NEED TO BE ORDERED SEPARATELY.
(ORDER No. REFER TO DRAWING: T20300X20XX000)

注释:

- 技术参数:
绝缘材料: PC
额定电压: 400V
额定电流: 16A
绝缘电阻: $\geq 400M\Omega$
额定脉冲电压: 6KV
污染等级: 3
阻燃等级: UL94V-0
插拔次数: 500次
工作温度: $-40\sim+125^{\circ}C$
接线范围: $0.14\sim 4\text{ mm}^2$ (26~12 AWG)
接线类型: 冷压接
- 端子需要单独订购.
(订货号参考图面: T20300X20XX000)

HMN-008-F	T2111082201-000
DESCRIPTION	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	25MAR2015		TE Connectivity
		CHK	25MAR2015		
		APVD	25MAR2015		
		NAME	Xiang Xu		
DIMENSIONS: mm		PRODUCT SPEC	108-137061	NAME HMN-008-F	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APPLICATION SPEC	114-137061	SIZE	CAGE CODE
0 PLC	±-	WEIGHT	-	DRAWING NO	RESTRICTED TO
1 PLC	±-	A300779 © T2111082201000			
2 PLC	±-	SCALE 3:2 SHEET 1 OF 1 REV B			
3 PLC	±-				
4 PLC	±-				
ANGLES	±-				
MATERIAL	FINISH	Customer Drawing			
-	-				
-	-				

1470-19 (3/13)