



**TERMINATION:**

P1	COLOR
1	BLACK
2	RED
3	GREEN
4	YELLOW

Extended Length ("L2")	Typical Retracted Length ("L1")
60.0 Inches - 69.0 Inches	13.0 Inches
1,524.0MM-1,752.6MM	330.2MM

- Material:**
- Plug Housing: Polycarbonate, clear
  - Plug Terminal: 0.36" [0.14MM] Thick Phosphor Bronze
  - Connector: 50µ" of Selective Gold Contact Plating
    - Area, Gold flash over the remainder
    - Over 2.54µm [0.000100] thick nickel underplate
  - Conductor(X4C): 26AWG (0.12X12) Bare Copper
  - Insulation(X4C): PP6331 ID 0.95-1.0
  - Jacke: PVC No UL 80 P
  - Package: Individual PE Bag



Scale	1:1				Name	Item No.				
TOLERANCE					Drawn	11.02.11 Chappell				
X.X	±0.40				Approved					
X.XX	±0.25									
X.XXX	±0.15									
Angle	±3°									
<p><b>ASSMANN</b> W+S components</p>						<b>AT-C-26-4/4/W-5-OE</b>				
						<p><b>Title</b> NON-UL 26 AWG (0.12X12)*4C, O.D.: 2.4*4.8MM, Reverse Plug, 50µ" of contact plating, WHITE</p>				
						<p>Drawing No.</p>				
Modification				Date	Name	rev00				
					Replace	Sheet				