



JKL LAMP NUMBER	VOLTS RATED	AMPS ±10%	MSCP ±25%	LUMENS ±25%	AVERAGE LIFE HRS.	FILAMENT TYPE
6832	5.0	.060	.050	0.63	100,000	C-2R
6152	5.0	.060	.150	1.89	5,000	C-2R
7132	5.0	.075	.090	1.13	25,000	C-2R
7152	5.0	.115	.150	1.89	40,000	C-2R

NOTES:

- GLASS ENVELOPE TO BE OF TIPLESS AND SEAMLESS CONSTRUCTION TO PROVIDE UNDISTORTED END VIEWING.
- WIRE TERMINALS TO BE TINNED DUMENT TYPE WIRE. OPTIONAL PLATING MATERIALS ARE AVAILABLE.
- ALL LAMPS TO BE 100% AGED FOR AN EQUIVALENT OF TEN HOURS OF THE RATED VOLTAGES.
- FINAL INSPECTION ON ALL LAMPS TO BE MIL. STD. 105-E. ELECTRICAL CHARACTERISTICS TO AN AQL OF 2.5 OR BETTER, LEVEL II. MECHANICAL TO AN AQL OF 4.0, LEVEL S-1. (NOTE: AS15 TYPE LAMPS WILL BE 100% INSPECTED FOR AMPERAGE AND MSCP RATINGS.)
- ALL DIMENSIONS PROVIDED HEREIN, NOT LISTING TOLERANCES, ARE CONSIDERED REFERENCE DIMENSIONS ONLY.

				METRIC DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION											
C DIM. CHNG. 0.8±0.13 TO 0.8 REF.		5/21/01				TITLE T-1 SHORTY WIRE TERMINAL LAMP											
B LEAD DIA. 0.25 TO 0.25 REF.		02/08/00		DRAWN BY L. WENGSTROM		APP'VD BY DATE QC 5/21/01		SIZE A		FSCM NO. 55335		DRAWING NO. WIRE TERMINAL SHORTY T-1					
A DRAWING TO CAD - LAMPS 2022, 6802 DELETED		01/14/00															
RELEASED		07/07/97															
REV. NO.		DESCRIPTION/ECO NUMBER		APP'VD DATE		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 07/07/97		REVISION DATE 5/21/01		REV. NO. C		SHEET 1 OF 1	