

BLADE TERMINALS DIN 46 244-A6,3-0,8 CuZn TIN PLATED
 CUT EDGES WITHOUT TIN PLATING ALLOWED
 DEGREE OF PROTECTION ACC. TO IEC529 = DIN 40 050 Teil 9

TERMINALS IP20
 HOUSING IP34
 IN CONNECTION WITH A CONNECTOR HOUSING
 MOUNTING POSITION: TERMINALS SHALL POINT DOWNWARDS
 FOR ALL OTHER POSITIONS PROTECTION GROUP IP 20 IS VALID

PART	MATERIAL	COLOUR
HOUSING	PA 66 GF 30± 10 [%]	BLACK
BASE PLATE	PA 66 GF 30± 10 [%]	BLACK

OBSOLETE BOSCH P/N	TE P/N	REV	PART NUMBER	CUSTOMER P/N	CODE NO
0 332 209 150	0-1904022-2		V23234-A1001-X036		
	1-1904022-2				
	2-1904022-2				
	3-1904022-2				
	4-1904022-2				
	5-1904022-2				
6-1904022-2					

PROPRIETARY THE REPRODUCTION, TRANSMISSION OR USE OF THIS DOCUMENT OR IT'S CONTENTS IS NOT PERMITTED WITHOUT EXPRESSED WRITTEN AUTHORITY. OFFENDERS WILL BE LIABLE FOR ALL DAMAGES. ALL RIGHTS, INCLUDING RIGHTS CREATED BY REGISTERED PATENT(S) GRANTED FOR A UTILITY MODEL OR DESIGN, ARE RESERVED.		CHANGES TO THIS DRAWING MUST BE DONE ONLY IN CAD	PAPER SIZE A3
APPLICABLE SPEC.:		FINISH	
TOLERANCE UNLESS SPECIFIED OTHERWISE		DIMENSIONS APPLY	PLATING
DIMENSIONS IN MM		SCALE 1:1	WEIGHT Ca.34g
MATERIAL		PART NAME MINI RELAY B CHANGEOVER 12V 20/30A	
DATE NAME B1 ECO-14-008934 12JUN2014 LSand DWN. 2006-06-06 P.Tomas B ECO-12-015770 30AUG2012 A.P. APP. A5 INITIAL VERSION 2007-10-18 PTom REV.		PART NO. V23234-A1001-X036	
LOCATION PE EVORA		SHT. 1	
REV. CHANGE ORDER DATE APP.		CUSTOMER DRAWING OF 2	




Nominal voltage (load and excitation circuit)	
Permissible operating voltage	8...16V
Permissible ambient temperature	-40... 100 ° C
Response voltage (at 20 ° C)	≤ 8 V
Release voltage (at 20 ° C)	1,2...5.5 V
Response time	≤ 10 ms
Release time	≤ 10 ms
Contact material	Silver based
Equivalent coil resistance at terminal 85-86	85± 5Ω

Voltage drop at blade terminals at a measuring current of 10± 0.5A	
Normally Open Contact, Terminal 30-87 in new condition	Typically ≤ 50mV, Max. 300mV
After life test	Typically ≤ 80mV, Max. 300mV
Normally Closed Contact, Terminal 30-87a in new condition	Typically ≤ 70mV, Max. 300mV
After life test	Typically ≤ 120mV, Max. 300mV

ELECTRICAL ENDURANCE

Resistive Load 30A on NO	- ≥ 250.000 cycles
Resistive Load 10A on NO	- ≥ 250.000 cycles
Resistive Load 20A on NC	- ≥ 250.000 cycles



PROPRIETARY THE REPRODUCTION, TRANSMISSION OR USE OF THIS DOCUMENT OR IT'S CONTENTS IS NOT PERMITTED WITHOUT EXPRESSED WRITTEN AUTHORITY. OFFENDERS WILL BE LIABLE FOR ALL DAMAGES. ALL RIGHTS, INCLUDING RIGHTS CREATED BY REGISTERED PATENT(S) GRANTED FOR A UTILITY MODEL OR DESIGN, ARE RESERVED.				CHANGES TO THIS DRAWING MUST BE DONE ONLY IN CAD		PAPER SIZE A3		
APPLICABLE SPEC. #				FINISH				
				DIMENSIONS APPLY		PLATING		
				TOLERANCE UNLESS SPECIFIED OTHERWISE		SCALE		
				DIMENSIONS IN MM		WEIGHT Ca. 34g		
				DATE		NAME		
B1	ECO-14-008934	12JUN2014	LSand	DWN.	2006-06-06	PART NAME MINI RELAY B		
B	ECO-12-015770	30AUG2012	A.P.	APP.		CHANGEOVER 12V 20/30A		
A4	INITIAL VERSION	2007-10-18	PTom	REV.				
A3	---	2007-03-01	--	LOCATION	PE EVORA			
A2	---	2007-01-31	--			PART NO.		
A1	---	2006-11-13	--			V23234-A1001-X036		SHT. 2
A1	---	2006-10-30	--			CUSTOMER DRAWING		OF 2
REV.	CHANGE ORDER	DATE	APP.					