



CRYSTEK
MICROWAVE
 A DIVISION OF CRYSTEK CORPORATION

18GHZ PRECISION RF COAX CABLE ASSEMBLIES WITH STAINLESS STEEL CONNECTORS



SS402 50 Ohm 18GHz Precision Coaxial Cables

Features:

- Strain Relief:** Heavy duty adhesive strain relief.
- Center Conductor:** SPCCS (Silver-plated copper clad steel)
- Inner Shielding:** SS(Spiral strip of silver plated copper)
- Outer Braid:** SPC (Silver-plated copper braid)
- Insulation:** PTFE (Polytetrafluoroethylene) dielectric
- Jacket:** ETFE
- Cable Outer Dia.** 0.163 (4.14mm)
- Connectors:** SST, corrosion-resistant, per ASTM-A582 (Passivated finish per SAE-AMS-2700)
- Center Pin:** GPBC(Gold-plated beryllium copper)
- Jacket Color:** Blue
- Operating Temperature:** -45°C to +85°C (Also available in -55°C to +125°C)
- Minimum Bend Radius:** 0.8" (20.32mm)

Custom Lengths Available

Available Connector Terminations:

- SMA Male
- SMA Male Right Angle
- Type N Male
- Type N Bulkhead Female
- Type N Male Right Angle
- TNC Male
- TNC Bulkhead Female
- TNC Male Right Angle

SMA / SMA [Straight/Straight]

Part Number	Description	Length
CCSMA-MM-SS402-6	SS402 Precision Coax Cable, SMA Male/Male, Straight/Straight	6"
CCSMA-MM-SS402-12	SS402 Precision Coax Cable, SMA Male/Male, Straight/Straight	12"
CCSMA-MM-SS402-24	SS402 Precision Coax Cable, SMA Male/Male, Straight/Straight	24"
CCSMA-MM-SS402-36	SS402 Precision Coax Cable, SMA Male/Male, Straight/Straight	36"
CCSMA-MM-SS402-48	SS402 Precision Coax Cable, SMA Male/Male, Straight/Straight	48"
CCSMA-MM-SS402-60	SS402 Precision Coax Cable, SMA Male/Male, Straight/Straight	60"
CCSMA-MM-SS402-72	SS402 Precision Coax Cable, SMA Male/Male, Straight/Straight	72"
CCSMA-MM-SS402-120	SS402 Precision Coax Cable, SMA Male/Male, Straight/Straight	120"

Electrical Specifications:

- Impedance:** 50 Ohms
- Frequency:** 18 GHz
- Insertion Loss:** 0.66 dB/ft Typ. at 18GHz
- VSWR:** <1.3, DC to 18GHz
- Nominal Capacitance:** 29 pF/ft
- Velocity of Propagation:** 70%
- RF Shielding:** < -110 dB
- Attenuation (dB/ft):** 0.08 Typ. at 500MHz
 *connector loss not included 0.11 Typ. at 1GHz
 0.21 Typ. at 3GHz
 0.32 Typ. at 6GHz
 0.50 Typ at 12GHz
 0.66 Typ at 18GHz



- Avg. Power in (Watts):** 920 @ 500MHz
 *as specified at 25°C 620 @ 1GHz
 360 @ 3GHz
 220 @ 6GHz
 150 @ 12GHz
 120 @ 18GHz

Mechanical Specifications:

- Connector Corrosion (salt spray):** MIL-STD-202, method 101, test cond. B 5% salt solution.
- Connector Durability:** 500 connections Min.



CRYSTEK
 CORPORATION

12730 COMMONWEALTH DRIVE • FORT MYERS, FL 33913
 PHONE: 239-561-3311 • 800-237-3061 Rev.: G
 FAX: 239-561-1025 • WWW.CRYSTEK.COM Date: 04-27-11