

Shield connection terminal block - SK 8-D - 3026861

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Shield connection clamp, for direct shield on conductive mounting plates, metal thickness 1 ... 2 mm

Why buy this product

- ✓ Easy handling
- ✓ Spring-loaded, large-surface pressure plate
- ✓ Suitable for direct and busbar mounting
- ✓ Knurled screw
- ✓ Spring-loaded, large-surface pressure plate
- ✓ Knurled screw

Key Commercial Data

Packing unit	10 STK
GTIN	 4 017918 820251
GTIN	4017918820251

Technical data

General

Number of levels	1
Number of connections	1
Cable diameter	3 mm ... 8 mm
Color	silver
Open side panel	No

Dimensions

Length	19.5 mm
Width	12 mm
Height	47.2 mm

Connection data

Shield connection terminal block - SK 8-D - 3026861

Technical data

Connection data


Connection method	Spring-cage connection
Screw thread	M4
Tightening torque max	0.6 Nm

Environmental Product Compliance


China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Drawings

Dimensional drawing



Dimensional drawing



Punching template

Drilling diagram

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		7500651.22.01.00246
-----	--	---------------------