

**Industrial Ethernet  
IE-PS-V04P-2LC-MM**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



PushPull plug-in connector set according to IEC  
61076-3-106 ver.4 (IEC24702), plastic with LC insert

**General ordering data**

Type	IE-PS-V04P-2LC-MM
Order No.	<a href="#">1963320000</a>
Version	FO connector, Variant 4, LC-Duplex multi-mode, IP 67
GTIN (EAN)	4032248651795
Qty.	10 pc(s).

**Data sheet****Industrial Ethernet  
IE-PS-V04P-2LC-MM**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight	35.3 g
------------	--------

**Temperatures**

Operating temperature	-40 °C...70 °C	Storage temperature	
Installation temperature			

**Downloads**

GOST Approval	POCC DE.ME25.B01411.pdf
---------------	----------------------------

**General data**

Colour		Miscellaneous		Connection 1		LC	
Connection 2		LC		Description of article		Variant 4, LC-Duplex multi-mode	
Fibre type		Multimode		Housing main material		PA UL 94 V0	
Insertion loss		0.5 dB singlemode, 0.4 dB multimode		Plugging cycles		500	
Protection degree		IP 67		Return loss (attenuation)		40 dB singlemode; 30 dB multimode	
Sheath diameter, max.		10 mm		Sheath diameter, min.		5 mm	

**Standards**

Connector standard	IEC 61076-3-106 Var. 4, IEC 61754-20
--------------------	---

**Classifications**

ETIM 3.0	EC001121	ETIM 4.0	EC002641
ETIM 5.0	EC002641	ETIM 6.0	EC002641
UNSPSC	30-21-18-10	eClass 5.1	27-26-07-08
eClass 6.2	27-26-07-08	eClass 7.1	27-25-05-04

**Approvals**

Approvals



ROHS	Conform
------	---------

**Industrial Ethernet  
IE-PS-V04P-2LC-MM**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmüller.com

**Drawings**

**Dimensioned drawing**

