

SHELLY-T-6X1-WAS

Asymmetric oval beam for wall washing


TECHNICAL SPECIFICATIONS:

Dimensions	119.8 + 19.6 mm
Height	7.6 mm
Fastening	pin, screw
Colour	clear
Box size	476 x 273 x 292 mm
Box weight	6.4 kg
Quantity in Box	588 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
SHELLY-T-6X1-WAS	Lens	PMMA	clear




INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	C14274	SHELLY-T-6X1-WAS	PMMA	

LEDiL	Ledil Oy Salorankatu 10 FIN 24240 SALO Finland	
DRAWING TITLE C14274_SHELLY-T-6X1-WAS		
SIZE	PART NUMBER	
A3	C14274	
SCALE	WEIGHT	SHEET
1:1	- g	1/1


PHOTOMETRIC DATA (MEASURED):




LED XQ-E
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 1.400 cd/lm
 Required components:




LED LUXEON Rebel ES
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 1.000 cd/lm
 Required components:



LED LUXEON T
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.960 cd/lm
 Required components:




LED LUXEON TX
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.980 cd/lm
 Required components:





PHOTOMETRIC DATA (MEASURED):





LED LUXEON Z ES
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 1.400 cd/lm
 Required components:





LED NCSxx19A
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 1.100 cd/lm
 Required components:



LED NCSxx19B
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.820 cd/lm
 Required components:





LED NF2x757A
 FWHM Asymmetric
 Efficiency 94 %
 Peak intensity 0.960 cd/lm
 Required components:





PHOTOMETRIC DATA (MEASURED):





LED NVSxx19A
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.940 cd/lm
Required components:



LED NVSxx19B/NVSxx19C
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.890 cd/lm
Required components:




LED Duris S5 (2 chip)
FWHM Asymmetric
Efficiency 94 %
Peak intensity 0.970 cd/lm
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED XD16
FWHM Asymmetric
Efficiency 94 %
Peak intensity 1.110 cd/lm
Required components:



LED XQ-E HI
FWHM Asymmetric
Efficiency 93 %
Peak intensity 1.500 cd/lm
Required components:



LED NF2x757G
FWHM Asymmetric
Efficiency 94 %
Peak intensity 1.100 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)