


PANEL THICKNESS	X
0.030~0.049 [0.75~1.25]	0.917 [23.3]
0.049~0.079 [1.25~2.00]	0.929 [23.6]
0.079~0.118 [2.00~3.00]	0.941 [23.9]



**SCHEMATIC**

**SPECIFICATIONS**

**FUNCTION:**  
1P1T OFF-ON

**RATINGS:**  
ANSI/UL 1054 and CAN/CSA C22.2 No. 55 (E194579):  
16A 125VAC [UR, CLR]  
10A 250VAC [UR, CLR]  
1/3HP 125/250VAC [UR, CLR]

EN 61058-1:2002:  
6(2)A 250V~ μ 1E4 T125/55 [ENEC14, SEMKO]

**CONTACT RESISTANCE:**  
Initial: 50mΩ Max. at 50VAC

**INSULATION RESISTANCE:**  
100MΩ Min. at 500VDC

**DIELECTRIC STRENGTH:**  
1,500VAC for 1 minute

**ELECTRICAL LIFE:**  
6,000 Cycles [UR, CLR]  
10,000 Cycles [ENEC14, SEMKO: 10(2)A 250V~]  
50,000 Cycles [ENEC14, SEMKO: 10(2)A 250V~]

**TEMPERATURE:**  
Operating: -20°C to 105°C [UR, CLR]  
Operating: -20°C to 125°C [ENEC14, SEMKO: 10(2)A 250V~]  
Operating: -20°C to 85°C [ENEC14, SEMKO: 10(2)A 250V~]

**APPROVALS:**



**COLORS AND MARKINGS**

**BODY:**  
Black

**ACTUATOR:**  
Black

**MARKINGS:**  
I/O Vertical (1)

**MARKING COLOR:**  
White

**MATERIALS**

**BODY:**  
Polyamide 6/6 (PA66), UL94 V-2

**ACTUATOR:**  
Polyamide 6/6 (PA66), UL94 V-2

**SPRING:**  
Steel

**SPRING COVER:**  
Steel

**CONTACTS:**  
Silver Alloy Plated Copper

**TERMINALS:**  
Silver Plated Copper  
Silver Plated Brass


**SUGGESTED PANEL CUTOUT**

ACTUATOR	A	90/08/11	CAB
BODY	A	90/08/11	CAB
COLORS	A	90/08/11	CAB
MATERIALS	A	90/08/11	CAB
SPECIFICATIONS	A	90/08/11	CAB
REFERENCE	REV.	DATE	BY

CHANGE RATING	B
INITIAL RELEASE DESCRIPTION <td>A</td>	A
FOR	REV.

POST1494	5/25/14	EBP
POST0051	90/08/11	CAB
FOR	DATE	DRAWN BY

INCHES [MILLIMETERS]
GENERAL TOLERANCES ±0.008 [±0.2] / ±1'
SCALE DRAWING NOT TO SCALE
PROJECTION



REVISION	DATE
RE1111C1121	AUGUST 11, 2009
REVISION B	