



NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: x.x= ± 0.4  
x.xx= ± 0.25
3. TERM. NOS. FOR REF ONLY
4. RATING: 50 MILLI-AMPS @12VDC
5. TRAVEL: 0.25 +0.2/-0.1MM
6. CONTACT RESISTANCE: 100 mΩ MAX (B)
- ▲7. OPERATING FORCE: 500 ± 100 GF
8. PACKAGING: TAPE AND REEL, 1500 PIECES PER REEL
- 9.▲DENOTES CRITICAL PARAMETER
10. 2002/95/EC (ROHS) COMPLIANT
11. LIFE CYCLES: 100,000 ACTUATIONS (B)
12. OPERATING TEMPERATURE: -20°C TO 70°C (B)
- ▲13. CONTACT MATERIAL: SILVER (B)

C	21086	12.0 MIN WAS 12.0, 7.0 MAX WAS 5.8	3/27/13	EBP
B	21024	WAS 100Ω, ADD TEMP, LIFE, SILVER	2/12/13	EBP
A	17215	RELEASED FOR PRODUCTION	4/25/07	TN
REV	PCR NO	DESCRIPTION	DATE	BY

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED



TITLE TL3304NF500QG

SCALE	DATE	DR	DWG	REV
4:1	4/25/2007	TN	P010645	C