


Sleeve housing for cable plug-in connector - RC-0000000Z200 - 1593040

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

Sleeve housing for cable plug-in connector, angled, Screw locking, M23, Shielded: No, Cable cross section: 8 mm...12 mm



Key commercial data

Packing unit	1 PCE
GTIN	 4 046356 193962
Custom tariff number	85366990
Country of origin	GERMANY

Technical data

Technical data

Note	Order information Order contact inserts and cable clamping separately
Ambient temperature	-20 °C ... 125 °C
Type of locking	Screw locking
Degree of protection	IP65
Contact connection method	Crimp connection
Type of contacts	Socket
Conductor entry	8 mm ... 12 mm

Material data

Housing material	Turned parts: copper zinc alloy (CuZn), die-cast parts: zinc (GD-Zn)
Gasket and O-ring material	FPM

Specifications according to DIN EN 61984:2001

Installation height max.	2000 m
--------------------------	--------

Sleeve housing for cable plug-in connector - RC-0000000Z200 - 1593040

Classifications

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC


UNSPSC 11	43172015
UNSPSC 12.01	43201404
UNSPSC 13.2	43201404
UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404

eCl@ss


eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260708
eCl@ss 7.0	27440312

Drawings

Diagram



Diagram



Sleeve housing for cable plug-in connector - RC-0000000Z200 - 1593040

Dimensioned drawing

