

Features

Regulated Converters

- Compact AC-DC Power Supply
- 20 Watt PCB Mount Package
- Universal Input Voltage Range
- 3000VAC Isolation
- Low Output Ripple and Noise
- Short Circuit Protected
- Low Temperature Operation
- Anti-Vibration Mechanical Fixing
- CE Marked

Description

Compact switching AC/DC power module for PCB, screw-terminal connection or DIN-rail mounting. The converter is pin compatible with the RAC05-SB and RAC10-SB models. A threaded insert is provided for additional mechanical fixing.

Selection Guide

Part Number	Input Range (VAC)	Output Voltage (VDC)	Output Current (mA)	Typical Efficiency (%)	Maximum Power (W)	Max. Capacitive Load
RAC20-3.3SB	90-264	3.3	3600	74	11.9W	4500µF
RAC20-05SB	90-264	5	3600	78	18W	3500µF
RAC20-12SB	90-264	12	1660	82	20W	1800µF
RAC20-15SB	90-264	15	1330	83	20W	1500µF
RAC20-24SB	90-264	24	833	83	20W	1200µF

*add suffix "-ST" for screw terminal module e.g. RAC20-05SB-ST

Specifications (typical at 25°C and after warm up time unless otherwise specified)

Input Voltage Range	90-264VAC or 120-370VDC	
Rated Power	20 Watts max.	
Input Frequency Range (for AC Input)	47-440Hz	
Input Current (full load)	115VAC/230VAC	385mA / 250mA max.
No Load Power Consumption	115VAC/230VAC	470mW max.
Inrush Current (<2ms)	115VAC	20A max.
	230VAC	40A max.
Leakage Current	0.75mA max.	
Output Voltage Accuracy (Full load)	±2%	
Line Voltage Regulation (low line, high line at full load)	±0.5% typ.	
Load Voltage Regulation (5% to 100% full load)	±1% typ.	
Output Ripple and Noise ⁽²⁾	Ripple (3.3V, 5V)	75mVp-p max.
	Noise (3.3V, 5V)	120mVp-p max.
	Others (Ripple and Noise)	1% Vout
Operating Frequency	100 - 130kHz typ.	
Minimum Load	0%	
Isolation Voltage (input to output)	3000VAC min.	
Temperature Coefficient	±0.02%/°C typ.	
Isolation Resistance	100 MΩ min.	
Short Circuit Protection	Continuous, Automatic Restart	
Over Voltage Category	OVC II	
Operating Temp. Range (Natural Convection, with derating)	-40°C to +70°C	
	3.3V, 5V (no derating)	-40°C to +40°C
	Others (no derating)	-40°C to +45°C
Storage Temperature Range	-40°C to +85°C	
Humidity	95% RH max.	
Case Material	Epoxy with Fibreglass (UL94V-0)	
Package Weight	59g	
Packing Quantity	5 pcs (-ST Version: 1 pc)	
EMC	designed to meet EN 55022 Class B / EN 55024	
MTBF (+25°C)	using MIL-HDBK-217F	>250 x 10 ³ hours

continued on next page


POWERLINE

AC/DC-Converter

with 3 year Warranty

RECOM


20 Watt Single Output



CE Marked

RAC20-B

Derating-Graph (Ambient Temperature)



Refer to Application Notes

POWERLINE

AC/DC-Converter

RAC20-SB Series


Specifications (typical at 25°C and after warm up time unless otherwise specified)

Notes:

Note 1: Ripple & Noise measured with 20MHz BW probe and 0.47µF capacitor in parallel across the outputs.

Note 2: Suggested input fuse rating 2A Slow Blow

Screw Terminal Module Option (suffix -ST)




Pin Connections

Pin #	Single Out
1	NC
2	VAC in (L)
3	VAC in (N)
4	NC
5	+VDC out
6	-VDC out
7	NC
8	NC

NC = No Connection

RAC20-B

Standard Package Style and Pinning




Pin Connections

Pin #	Single Out
1	VAC in (L)
2	VAC in (N)
3	+VDC out
4	-VDC out

XX.X ± 0.5 mm
XX.XX ± 0.25 mm

Recommended Footprint Details



The product information and specifications are subject to change without prior notice. RECOM products are not authorized for use in safety-critical applications (such as life support) without RECOM's explicit written consent. A safety-critical application is defined as an application where a failure of a RECOM product may reasonably be expected to endanger or cause loss of life, inflict bodily harm or damage property. The buyer shall indemnify and hold harmless RECOM, its affiliated companies and its representatives against any damage claims in connection with the unauthorized use of RECOM products in such safety-critical applications.