



Technical specification :

Rated voltage: IEC 61076-2-104	30 V
Current rating: IEC 61076-2-104	3 A at 40°C
Insulation resistance: IEC 60512	>=100 MΩ
Pollution degree: IEC 60664-1	3/2
Degree of protection: IEC 60529	IP 67, in mated condition
Temperature range: IEC 60664-1	-30°C ... +80°C
Mating cycles: IEC 60512-9a	>=100

Materials:

Contact:	CuZn
Contact plating:	Nickel, gold plated
Contact carrier:	TPU GF, UL 94
Sealing:	FPM
Coupling nut/ screw:	GD-Zn, nickel plated
Moulding body:	TPU, UL 94, grey

Installation specification:

Recommended torque:	0,4 Nm
Conec installation tool:	Torque wrench: 36-000200 Insert across flats 9: 36-000210

Contact assignment:

- 1) brown
- 2) white
- 3) blue
- 4) black

Part no:	Description:	Length L:	Cable:
42-10169	SAL - 8 - RKW4 - RS4 - 0,3 / K1	0,3m	TPU, UL 20549, black, 4x0,25mm ² Cable: 781-K12400
42-10170	SAL - 8 - RKW4 - RS4 - 0,6 / K1	0,6m	
42-10171	SAL - 8 - RKW4 - RS4 - 1,5 / K1	1,5m	
42-10172	SAL - 8 - RKW4 - RS4 - 3 / K1	3,0m	
42-xxxxx	SAL - 8 - RKW4 - RS4 - ... / K1	x	

D see data sheet cable

DO NOT ALTER CAD DRAWING BY HAND Directive 2002/95/EC RoHS compliant	Index: a 17.03.11 VF Ä3945 Coupling nut/ screw modified, spanner flats added, data sheet modified	dim. in mm	title: Connecting cable M8x1, female connector angled - male connector axial									
	tolerance of cable: L ≤ 4m: L + 40mm L > 4m: L + 1%			<table border="1"> <tr> <td></td> <td>date</td> <td>name</td> </tr> <tr> <td>drawn</td> <td>13.12.07</td> <td>Franz</td> </tr> <tr> <td>appd.</td> <td>13.12.07</td> <td>Mankopf</td> </tr> </table>		date	name	drawn	13.12.07	Franz	appd.	13.12.07
		date		name								
	drawn	13.12.07		Franz								
appd.	13.12.07	Mankopf										
THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH		dwg no: 42K1A042										
		part no: see table										