



General ordering data

Order No.	1720820000
Part designation	ZDL 2.5/NT/L/PE
Version	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
EAN	4008190958954
Qty.	50 pc(s).

Product notes

Note, technical data	2.5 mm ² flexible conductors with wire end ferrules are crimped with the Weidmüller PZ 6/5 crimping tool.
Product description	Electrical distribution with plug-in cross-connection

Additional technical data

Colour of insulating material	dark beige
Connection direction	Inclined / angled
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 35
Insulating material	Wemid
Levels cross-connected internally	No
No. of levels	3
No. of terminal strips per level	2
Open sides	right
Operating temperature range	- 50 °C, + 120 °C
Product family	Z-series
Type of connection	Tension clamp connection
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	V-0
Version	3-conductor installation terminal

CSA rating data

Voltage (CSA)	300 V
CSA current	10 A

CSA rating data

Min. cross-section (CSA)	AWG 26
Max. cross-section (CSA)	AWG 12

Conductors for clamping (additional connection)

Flexible with ferrule, min. (DIN 46228 pt 1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228 pt 1)	2.5 mm ²

Conductors for clamping (rated connection)

Clamping range, min.	0.13 mm ²
Clamping range, max.	4 mm ²
Type of connection	Tension clamp connection
Connection direction	Inclined / angled
No. of connections	5
Stripping length	8 mm
Blade size	0.6 x 3.5 mm
Gauge to IEC 60947-1	A2
Solid, min.	0.5 mm ²
Solid, max.	4 mm ²
Flexible, min.	0.5 mm ²
Flexible, max.	4 mm ²
Flexible with ferrule, min. (DIN 46228/1)	0.5 mm ²
Flexible with ferrule, max. (DIN 46228/1)	2.5 mm ²
Flexible, min., ferrule with plastic collar (DIN 46228 pt 4)	0.5 mm ²
Flexible, max., ferrule with plastic collar (DIN 46228 pt 4)	2.5 mm ²
AWG conductor size, min.	AWG 26
AWG conductor size, max.	AWG 12

Dimensions

Width	5.1 mm
Height of lowest version	48.5 mm
Length	95 mm
TS 35 offset	49 mm

Distribution terminals

N-function	Yes
No. of potentials	2
PE function	Yes
Rated impulse withstand voltage to N/PE	4 kV
Rated voltage to N/PE	250 V

N-conductor disconnect terminal

For N-busbar	3 x 10 mm
--------------	-----------

Rating data

Rated cross-section	2.5 mm ²
Rated voltage	400 V
Rated impulse voltage	4 kV
Rated current	20 A

Rating data

Standards	IEC 60947-7-1 (-7-2)
Current with max. conductor	20 A
Pollution severity	3

UL rating data

Voltage (UL)	300 V
Current (UL)	10 A
Min. cross-section (UL)	AWG 26
Max. cross-section (UL)	AWG 12

Approvals

Approvals institutes



Classifications

ETIM 2.0	EC001329
ETIM 3.0	EC001329
eClass 4.1	27-14-11-25
eClass 5.0	27-14-11-25
eClass 5.1	27-14-11-25

Similar products

Order No.	Part designation	Version
1720850000	ZDL 2.5/L	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
1720830000	ZDL 2.5/L/L	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
1720880000	ZDL 2.5/L/L/PE	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
1720840000	ZDL 2.5/N	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35
1720860000	ZDL 2.5/N/L	Storey installation terminal, 2.5 mm ² , Tension clamp connection, Wemid, dark beige, TS 35