

1	2	3	4	5	6	7																														
<p>TEST CONDITION:</p> <ol style="list-style-type: none"> 100% OPEN & SHORT TESTING VOLTAGE: 300V DC INSULATION RESISTANCE: 10M ohm CONTACT RESISTANCE: 3 ohm (1M~3M) 5 ohm (5M~10M) 8 ohm (15M) 																																				
<p>PIN OUT</p> <table border="1"> <thead> <tr> <th>P1</th> <th>COLOR</th> <th>P2</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>white/orange</td> <td>1</td> </tr> <tr> <td>2</td> <td>orange</td> <td>2</td> </tr> <tr> <td>3</td> <td>white/green</td> <td>3</td> </tr> <tr> <td>4</td> <td>green</td> <td>6</td> </tr> <tr> <td>5</td> <td>blue</td> <td>4</td> </tr> <tr> <td>6</td> <td>white/blue</td> <td>5</td> </tr> <tr> <td>7</td> <td>white/brown</td> <td>7</td> </tr> <tr> <td>8</td> <td>brown</td> <td>8</td> </tr> <tr> <td colspan="2">SHELL</td> <td>SHELL</td> </tr> </tbody> </table>							P1	COLOR	P2	1	white/orange	1	2	orange	2	3	white/green	3	4	green	6	5	blue	4	6	white/blue	5	7	white/brown	7	8	brown	8	SHELL		SHELL
P1	COLOR	P2																																		
1	white/orange	1																																		
2	orange	2																																		
3	white/green	3																																		
4	green	6																																		
5	blue	4																																		
6	white/blue	5																																		
7	white/brown	7																																		
8	brown	8																																		
SHELL		SHELL																																		
<table border="1"> <thead> <tr> <th>NO.</th> <th>NAME</th> <th>DESCRIPTION</th> <th>QTY</th> <th>UNIT</th> </tr> </thead> <tbody> <tr> <td>④</td> <td>AL-FOIL</td> <td>Conductive AL-FOIL:W=8mm L=28mm</td> <td>2</td> <td>PCS</td> </tr> <tr> <td>③</td> <td>OVERMOLD</td> <td>75A PVC Color: see order code</td> <td>N/A</td> <td>G</td> </tr> <tr> <td>②</td> <td>CONNECT</td> <td>CAT 6 RJ45 8P8C PLUG Brass 3u" gold. Shell: Nickel plated</td> <td>2</td> <td>PCS</td> </tr> <tr> <td>①</td> <td>CABLE</td> <td>LAN CAT5e FTP 24AWG*4P+Mylar+AL+Drain, OD:5.5±0.3mm JACKET COLOR:see order code</td> <td>1</td> <td>PCS</td> </tr> </tbody> </table>							NO.	NAME	DESCRIPTION	QTY	UNIT	④	AL-FOIL	Conductive AL-FOIL:W=8mm L=28mm	2	PCS	③	OVERMOLD	75A PVC Color: see order code	N/A	G	②	CONNECT	CAT 6 RJ45 8P8C PLUG Brass 3u" gold. Shell: Nickel plated	2	PCS	①	CABLE	LAN CAT5e FTP 24AWG*4P+Mylar+AL+Drain, OD:5.5±0.3mm JACKET COLOR:see order code	1	PCS					
NO.	NAME	DESCRIPTION	QTY	UNIT																																
④	AL-FOIL	Conductive AL-FOIL:W=8mm L=28mm	2	PCS																																
③	OVERMOLD	75A PVC Color: see order code	N/A	G																																
②	CONNECT	CAT 6 RJ45 8P8C PLUG Brass 3u" gold. Shell: Nickel plated	2	PCS																																
①	CABLE	LAN CAT5e FTP 24AWG*4P+Mylar+AL+Drain, OD:5.5±0.3mm JACKET COLOR:see order code	1	PCS																																
<p>WSW order code AMJG0808-xxxx-xxB-24</p> <p>Cable length: 0.3±0.015M BK: Black 0050: 0.5±0.02M RD: Red 0100: 1.0±0.03M YE: Yellow 0150: 1.5±0.03M GN: Green 0200: 2.0±0.05M GY: Grey 0300: 3.0±0.08M BU: Blue 0500: 5.0±0.15M WH: White 0700: 7.0±0.25M BN: Brown 1000: 10±0.30M 1500: 15±0.50M</p>																																				
<p>Customer-No.</p> <p>ASSMANN WSW-No. AMJG0808-xxxx-xxB-24</p> <p>ASSMANN logo</p>																																				
<p>Scale Free</p> <p>TOLERANCE</p> <p>DIM TOL</p> <p>Angle TOL</p>																																				
<p>RoHS compliant</p> <p>Unit: mm</p>																																				
<p>1 2 3 4 5 6 7</p>																																				