



**Notes:**

1. Electrical:
  - Meets EIA/TIA-568-B.2-10 Cat. 6A Channel Specification
  - Connector Operating Temperature: -40° C to +85° C
2. Materials and Finish:
  - Coupling Ring: Brass, Nickel Plated
  - ⓑ - Plug Housing: Zinc Die-Cast, Nickel Plated
    - Interfacial Seal: Silicon, Color: White
    - Cable Gland: Brass, Nickel Plated
    - Cable Gland Seal: NBR, Color: Black
    - Cat.6A RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
    - Cat.6A RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-2
    - Cat.6A RJ45 Plug Contacts: Phosphor Bronze, Finish: 50 u" Gold min. over Nickel
    - Cable: Cat.6A SSTP, 4 Pairs, AWG26, Stranded, Jacket Color: Black

**RoHS Compliant**

Ⓒ Patch Cord Length <b>L</b>	Part Number
1m ± 0.02m	17-180504
2m ± 0.03m	17-150724
3m ± 0.03m	17-180514
4m ± 0.04m	17-150734
5m ± 0.05m	17-150744
10m ± 0.10m	17-180524
20m ± 0.20m	17-180534

\*Note: Special cable length and blue cable up to 20m are available please contact factory  
Cable length > 20m cannot guarantee to meet TIA/EIA-568-C.2 Cat. 6A Specification.

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION  DOT NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale: NTS	Dim. in meter
	Name	Title	Approval Date	0 PLC ±0.50	1 PLC ±0.38		Autodesk Inventor  Material: See Notes  Cat. 6A RJ45 Ethernet Patch Cords IP67 Industrial to IP67 Industrial M28 Thread Metal Version	DIN A3 Sheet 1/1
				2 PLC ±0.25	3 PLC ±0.10			
				ANGES	±3°			
	c	1 x c	Apr./15/2015	Vincent Ke	2011	Date	Name	Drawing No.: 17K1A278
b	1 x b	Jun/23/2014	Vincent Ke	Draw.	Sept. 28	Vincent Ke	Part No.: SEE PART NUMBER TABLE	
a	original			Appd.	Sept. 28	J. Chaudry		
Rev.	Changes	Date	Name	Norm				

