



NOTES:

- 1-Material:Phosphor bronze,thickness 0.20
- 2-Finish on contact area:see table  
finish on termination:bright tin lead over nickel
- 3-Wire range:20 to 24 AWG
- 4-Max outer dia of wire insulator:1.73 mm
- 5-Current carrying capacity per contact:  
5.Amps max when crimped to #20 AWG  
5 Amps max when crimped to #22 AWG  
3 Amps max when crimped to #24 AWG
- 6-After 5 insertions into connector,  
contact retention must be 5 pounds axial load min
- 7-When contact is crimped to 20 AWG,the insulation  
support crimped height must be 1.78 mm max to ensure  
a proper insertion into housing
- 6-Packaging:Box of 500 contacts

NOTE : ROHS INFORMATIONS

The LF products meet European union directives and other country regulations as described in GS-22-008  
Terminations plating spec : 2um Nickel min + 2um Sn min  
Packaging Spec : see GS-14-920

Core range	-
<b>8656352064LF</b>	Flash Au
<b>8656352064</b>	Flash Au
PART NUMBER	Plating

www.fciconnect.com		surface -	tolerance std	projection	mm
		ISO 1302	ISO 406 ISO 1101		
		TOLERANCES UNLESS OTHERWISE SPECIFIED			
Dr	C JARRY	28/01/97	ANGULAR	size A3	Scale 10:1
Eng			LINEAR		
Chr			0° ±2°	ECN	LS08-0127
Appr			0.X ±0.3	Spec ref	
			0.XX ±0.1		
			0.XXX ±0.05		
			Product family		
		title CRIMP PIN		Rev. no	E
		#wire 20-24 in box 500 cts		C01-8656-1523	
		catalog no		CUSTOMER	sheet 1 of 1

rev	ecn no	dr	date
D	LS06-196	MPE	27/11/2006
E	LS08-0127	MPE	2008/05/13
-	-	-	-
-	-	-	-
-	-	-	-
-	-	-	-



Copyright FCI.