


## Transceiver Gateway Module TCM 310 / TCM 310U

TCM 310 enables the realization of gateways for the EnOcean 868 and 902 MHz radio systems. It provides a bi-directional radio interface at one end and a bi-directional serial interface at the other end. Radio messages are sent transparently through the serial interface in both directions from and to an externally connected host processor or host PC. In addition control commands can be sent from the host, e.g. to configure the repeater functionality or to manage the Smart Ack functions. TCM 310 can act as postmaster for up to 15 bi-directional sensors using Smart Ack technology.

### Feature

- Smart Ack controller functionality
- Transparent radio channel
- Programmable repeater functionality (1 / 2 Level)
- EnOcean Serial Protocol V3 (ESP3)



### Product variants

- TCM 310: SMD transceiver module 868MHz
- TCM310U: SMD transceiver module 902MHz

#### Type

TCM 310  
TCM 310U

#### Ordering Code

S3003-K310  
S3053-K310

### Features overview

<b>Antenna</b>	External whip or 50Ω antenna mountable
<b>Frequency</b>	TCM 310: 868.300MHz TCM 310U: 902.875MHz
<b>Data rate</b>	125 kbps
<b>Modulation type</b>	TCM 310: ASK 868 MHz <sup>1)</sup> TCM 310U: FSK 902MHz
<b>Receiver Sensitivity (at 25°C)<sup>2)</sup></b>	TCM 310: typ. -96 dBm (868MHz) TCM 310U: typ. -98 dBm (902MHz)
<b>Conducted Output Power</b>	TCM 310: typ. 3 dBm (868MHz) TCM 310U: typ. 1 dBm (902MHz)
<b>Power Supply</b>	2.6...4.5V
<b>Serial Interface</b>	UART (ESP3)
<b>Current Consumption</b>	Receive mode: 33 mA Transmit mode: 24 mA
<b>Dimensions of PCB</b>	22x19x3 mm
<b>Operating temperature</b>	-25° to +85°C
<b>Radio Regulations</b>	TCM 310: R&TTE / EN 300 220 TCM 310U: IC/FCC / CFR-47 Part 15

1) According to ISO/IEC 14543-3-10

2) 0.1% telegram error rate (based on the combination of 3 received sub-telegrams)