


Material: UL94 V-2 Nylon 6/6

Color: Natural

Part No.	A	
	mm	in
CBDSL505A	3.2	.126
CBDSL510A	5	.197
CBDSL515A	6.4	.252
CBDSL520A	7	.276
CBDSL525A	8	.315
CBDSL530A	9.5	.374
CBDSL535A	11.2	.441
CBDSL540A	12	.472
CBDSL545A	15	.591
CBDSL550A	16	.630
CBDSL555A	17	.669
CBDSL560A	20	.787
CBDSL565A	22	.866
CBDSL570A	25.4	1.000

TO SNAP LOCK IN A 3 (.118) Ø HOLE, IN A  
1.2 - 2 (.047 - .078) PANEL THICKNESS



TO SNAP LOCK IN A 3 (.118) Ø HOLE, IN A  
1.2 - 2 (.047 - .078) PANEL THICKNESS

TOLERANCES  
UNLESS NOTED  
≤ 5 mm ±0.2  
5 - 20 mm ±0.3  
20 - 40 mm ±0.4  
40 - 60 mm ±0.5  
60 - 100 mm ±0.8  
≥ 100 mm ±1.0

TITLE:

DUAL LOCKING CIRCUIT BOARD SUPPORT

FILE: CBDSL55XX

DWN: CLC

SHEET: 1 OF 1

SHEET SIZE: A

DT: 01/08/15

RE:



PART #

SEE TABLE

PRINT TYPE

CA



DWG IN  
MM (IN)