

LV-PECL/ 3.3V/ 7.0x5.0mm



RoHS Compliant

Features

- Miniature ceramic package
- Highly reliable with seam welding
- LV-PECL output
- Supply voltage $V_{CC}=3.3V$
- $\pm 25 \times 10^{-6}$ available

Table 1

Freq. Tol. Code	Tol. $\times 10^{-6}$	Operating Temperature Range (°C)	Note
0	± 50	0 to +70	Standard specifications
S	± 30		With only certain frequencies
U	± 25		
F	± 100		
G	± 50	-40 to +85	

How to Order

KC7050P 125.000 P 3 0 E 00
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Type (7.0x5.0mm SMD)
- ② Output Frequency
- ③ Output Type (LV-PECL)
- ④ Supply Voltage (3.3V)
- ⑤ Frequency Tolerance (See Table 1)
- ⑥ Symmetry/ INH Function (45/ 55%, Stand-by)
- ⑦ Customer Special Model Suffix (STD Specification is "00")

Packaging (Tape & Reel 1000 pcs./ reel)

Specifications

Item	Symbol	Conditions	Min.	Max.	Units	
Output Frequency Range ^{Note1}	f_o		50	190	MHz	
Frequency Tolerance	f_{tol}	Initial tolerance, Operating temperature range, Rated power supply voltage change, Load change, Aging (1 year @25°C), Shock and vibration	Op. Temp.: -40 to +85°C	-100	+100	$\times 10^{-6}$
			Op. Temp.: 0 to +70°C/ -40 to +85°C	-50	+50	
			Op. Temp.: 0 to +70°C	-30	+30	
			Op. Temp.: 0 to +70°C	-25	+25	
Storage Temperature Range	T_{stg}		-55	+125	°C	
Operating Temperature Range	T_{use}	Standard Specifications Extend (Option)	0 -40	+70 +85	°C	
Max. Supply Voltage	—		-0.5	+5.0	V	
Supply Voltage	V_{CC}	Freq. Tol.Code: 0, S, F Freq. Tol.Code: U, G	+2.97 +3.14	+3.63 +3.46	V	
Current Consumption	I_{CC}		—	90	mA	
Stand-by Current	I_{std}		—	30	μA	
Symmetry	SYM	50ohm @crossing point	45	55	%	
Rise/ Fall Time (20% to 80% Output Level)	tr/ tf	50ohm	—	0.6	ns	
Low Level Output Voltage ^{Note2}	V_{OL}	Op. Temp.: 0 to +85°C/ Typ. 1.600V	$V_{CC}-1.810$	$V_{CC}-1.620$	V	
		Op. Temp.: -40 to 0°C/ Typ. 1.605V	$V_{CC}-1.830$	$V_{CC}-1.555$		
High Level Output Voltage ^{Note2}	V_{OH}	Op. Temp.: 0 to +85°C/ Typ. 2.350V	$V_{CC}-1.025$	$V_{CC}-0.880$	V	
		Op. Temp.: -40 to 0°C/ Typ. 2.295V	$V_{CC}-1.085$	$V_{CC}-0.900$		
Output Load	RL	LV-PECL Output	50		ohm	
Input Voltage Range	V_{IN}		0	V_{CC}	V	
Low Level Input Voltage	V_{IL}		—	30% V_{CC}	V	
High Level Input Voltage	V_{IH}		70% V_{CC}	—	V	
Disable Time	t_{dis}		—	150	ns	
Enable Time	t_{ena}		—	10	ms	
Start-up Time	t_{str}	@Minimum operating voltage to be 0 sec.	—	10	ms	
Deterministic Jitter (DJ)	DJ	Measured with Wavecrest SIA-3000	—	2	ps	
1 Sigma Jitter	JSigma		—	4	ps	
Peak to Peak Jitter	JPK-PK		—	30	ps	


Note : All electrical characteristics are defined at the maximum load and operating temperature range.

Note1: Please contact us for inquiry about operating temperature range, available frequencies and other conditions.

Note2: DC characteristic

Dimensions

(Unit: mm)



Recommended Land Pattern

(Unit: mm)

