



N= NUMBER OF CONCATS

Material

- 1.Terminal body
(metal housing): Brass(CuZn)
- 2.Terminal screw:Steel Zinc plating"-slot type
- 3.Contacts: Brass
- 4.Surface of solder tail: Tin plated
- 5.Insulator (housing): Thermoplastic (UL94V-0),Green

Electrical UL / VDE

- 1.Voltage rating: 300VAC/250VAC
- 2.Current rating: 10A/10A
- 3.Wire range: 0.5-1.5mm²
- 4.Solid wire(AWG): 16-26
- 5.Stranded wire(AWG): 16-26
- 6.Torque: 3.5Lb-In/0.4N.m
- 7.Screw:M2.5
- 8.Wire strip length:5-6mm
- 9.Withstanding Voltage: 1.6KV/2KV
- 10.Operating temperature: -30°C to +105°C
- 11.Soldering temperature: 250°C±10°C/5 Sec
- 12.Safety Approval:

RoHS compliant

Scale	1:1						Date	Name	Customer-No.
TOLERANCE						Drawn	10.09.2008	N.Schulz	
X.	±0.50					Approved	27.05.2009	Hellwig	ASSMANN WSW-No. A-TB500-TOxx
X.X	±0.30								Drawing-No.
X.XX	±0.10								ASS 2783 CO
DIM	TOL	②	Update	27.05.2009	Dean				rev02
X.°	±1°	①	Drawn	10.09.2008	N.Schulz			Replace	Sheet
X.X°	±X°								
Angle	TOL	Id.	Modification	Date	Name				