



- NOTES**
- 1 MATERIAL:
-HOUSING: THERMOPLASTIC POLYESTER, COLOR GREY.
-CONTACTS: BRASS.
 - 2 PLATING CONTACT: 1,25 µm Au OVER 1,25 µm Ni IN CONTACT AREA.
Sn/Pb over 1,25 µm Ni ON SOLDER POST.
 - 3 PLATING CONTACT: 0,8 µm Au OVER 1,25 µm Ni IN CONTACT AREA.
Sn/Pb over 1,25 µm Ni ON SOLDER POST.
 - 4 PLATING CONTACT: 2,0 µm Au OVER 1,25 µm Ni IN CONTACT AREA.
Sn/Pb over 1,25 µm Ni ON SOLDER POST.
 - 5 PLATING CONTACT: 0,4 µm Au OVER 1,25 µm Ni IN CONTACT AREA.
Sn/Pb over 1,25 µm Ni ON SOLDER POST.
 - 6 SOLDER POSTS SUITABLE FOR P.C.B. HOLES
0,8±0,05 OR 1,0±0,1 DIA.
 - 7 8 HOLES SUITABLE FOR KEYING PIN PN. 215916-1.
 - 8 KEYING HOLES TO BE DRILLED BY CUSTOMER.

DO NOT SCALE METRIC DIMENSIONS IN mm THIRD ANGLE PROJECTION

2--8 OBSOLETE	SEE NOTE 5		2-167495-8
2--7 OBSOLETE	SEE NOTE 4	SEE NOTE 1	2-167495-7
	SEE NOTE 3		2-167495-4
2--1 OBSOLETE	SEE NOTE 2		2-167495-1
FINISH		MATERIAL	PARTNUMBER
CUSTOMER DRAWING			FOR REFERENCE ONLY WILL NOT BE UPDATED
© COPYRIGHT 19- BY AMP-HOLLAND B.V. ALL INTERNATIONAL RIGHTS RESERVED. AMP PRODUCTS MAY BE COVERED BY U.S. AND FOREIGN AND/OR PATENTS PENDING. THIS DRAWING IS UNPUBLISHED RELEASED FOR PUBLICATION ,19			
AMP		AMP-HOLLAND B.V. 's-Hertogenbosch, The Netherlands.	
G	EH-0467-96	J.G. J.G. 27-05-97	NAME
F	H-9853	R.v.L J.v.v. 31.03.93	48 POS. DIN 41612 F MALE 90° SOLDER CONNECTOR
LTR.	REVISION RECORD	DR. CHK. DATE	
DR.:	R.v.Lokven	CHK. J. STIBBELS	APP.:
DATE:	31.03.93	DATE: 27-5-97	DATE:
DWG.No. C-167495		REV.LTR. G	SHEET 1 OF 1 A3