

UNR511xG Series

Silicon PNP epitaxial planar type

For digital circuits

■ Features

- Costs can be reduced through downsizing of the equipment and reduction of the number of parts
- S-Mini type package, allowing automatic insertion through the tape/magazine packing


■ Resistance by Part Number

	Marking symbol	(R ₁)	(R ₂)
• UNR5110G	6L	47 kΩ	—
• UNR5111G	6A	10 kΩ	10 kΩ
• UNR5112G	6B	22 kΩ	22 kΩ
• UNR5113G	6C	47 kΩ	47 kΩ
• UNR5114G	6D	10 kΩ	47 kΩ
• UNR5115G	6E	10 kΩ	—
• UNR5116G	6F	4.7 kΩ	—
• UNR5117G	6H	22 kΩ	—
• UNR5118G	6I	0.51 kΩ	5.1 kΩ
• UNR5119G	6K	1 kΩ	10 kΩ
• UNR511DG	6M	47 kΩ	10 kΩ
• UNR511EG	6N	47 kΩ	22 kΩ
• UNR511FG	6O	4.7 kΩ	10 kΩ
• UNR511HG	6P	2.2 kΩ	10 kΩ
• UNR511LG	6Q	4.7 kΩ	4.7 kΩ
• UNR511MG	EI	2.2 kΩ	47 kΩ
• UNR511NG	EW	4.7 kΩ	47 kΩ
• UNR511TG	EY	22 kΩ	47 kΩ
• UNR511VG	FC	2.2 kΩ	2.2 kΩ
• UNR511ZG	FE	4.7 kΩ	22 kΩ

■ Package

- Code
SMini3-F2
- Pin Name
1: Base
2: Emitter
3: Collector

■ Internal Connection



■ Absolute Maximum Ratings T_a = 25°C

Parameter	Symbol	Rating	Unit
Collector-base voltage (Emitter open)	V _{CBO}	-50	V
Collector-emitter voltage (Base open)	V _{CEO}	-50	V
Collector current	I _C	-100	mA
Total power dissipation	P _T	150	mW
Junction temperature	T _j	150	°C
Storage temperature	T _{stg}	-55 to +150	°C

■ Electrical Characteristics $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$

Parameter		Symbol	Conditions	Min	Typ	Max	Unit		
Collector-base voltage (Emitter open)		V_{CBO}	$I_C = -10 \mu\text{A}, I_E = 0$	-50			V		
Collector-emitter voltage (Base open)		V_{CEO}	$I_C = -2 \text{ mA}, I_B = 0$	-50			V		
Collector-base cutoff current (Emitter open)		I_{CBO}	$V_{CB} = -50 \text{ V}, I_E = 0$			-0.1	μA		
Collector-emitter cutoff current (Base open)		I_{CEO}	$V_{CE} = -50 \text{ V}, I_B = 0$			-0.5	μA		
Emitter-base cutoff current (Collector open)	UNR5110G/5115G/5116G/5117G	I_{EBO}	$V_{EB} = -6 \text{ V}, I_C = 0$			-0.01	mA		
	UNR5113G					-0.1			
	UNR5112G/5114G/511DG/511EG/511MG/511NG/511TG					-0.2			
	UNR511ZG					-0.4			
	UNR5111G					-0.5			
	UNR511FG/511HG					-1.0			
	UNR5119G					-1.5			
	UNR5118G/511LG/511VG					-2.0			
Forward current transfer ratio	UNR511VG	h_{FE}	$V_{CE} = -10 \text{ V}, I_C = -5 \text{ mA}$	6		20	—		
	UNR5118G/511LG			20					
	UNR5119G/511DG/511FG/511HG			30					
	UNR5111G			35					
	UNR5112/511EG			60					
	UNR511ZG			60	200				
	UNR5113/5114/511MG			80					
	UNR511N/511TG			80	400				
Collector-emitter saturation voltage	UNR511VG	$V_{CE(sat)}$	$I_C = -10 \text{ mA}, I_B = -0.3 \text{ mA}$			-0.25	V		
			$I_C = -10 \text{ mA}, I_B = -1.5 \text{ mA}$						
Output voltage high-level		V_{OH}	$V_{CC} = -5 \text{ V}, V_B = -0.5 \text{ V}, R_L = 1 \text{ k}\Omega$	-4.9			V		
Output voltage low-level		V_{OL}	$V_{CC} = -5 \text{ V}, V_B = -2.5 \text{ V}, R_L = 1 \text{ k}\Omega$			-0.2	V		
			$V_{CC} = -5 \text{ V}, V_B = -3.5 \text{ V}, R_L = 1 \text{ k}\Omega$						
			$V_{CC} = -5 \text{ V}, V_B = -10 \text{ V}, R_L = 1 \text{ k}\Omega$						
			$V_{CC} = -5 \text{ V}, V_B = -6 \text{ V}, R_L = 1 \text{ k}\Omega$						
Transition frequency		f_T	$V_{CB} = -10 \text{ V}, I_E = 1 \text{ mA}, f = 200 \text{ MHz}$		80		MHz		
Input resistance	UNR5118G	R_1		-30%	0.51	+30%	k Ω		
	UNR5119G				1.0				
	UNR511HG/511MG/511VG				2.2				
	UNR5116G/511FG/511LG/511NG/511ZG				4.7				
	UNR5111G/5114G/5115G				10				
	UNR5112G/5117G/511TG				22				
	UNR5110G/5113G/511DG/511EG				47				
Resistance ratio	UNR511MG	R_1/R_2			0.047		—		
	UNR511NG				0.1				
	UNR5118G/5119G				0.08			0.10	0.12
	UNR511ZG				0.21				

■ Electrical Characteristics (continued) $T_a = 25^\circ\text{C} \pm 3^\circ\text{C}$


Parameter		Symbol	Conditions	Min	Typ	Max	Unit
Resistance ratio	UNR5114G			0.17	0.21	0.25	
	UNR511HG			0.17	0.22	0.27	
	UNR511TG				0.47		
	UNR511FG			0.37	0.47	0.57	
	UNR511VG				1.0		
	UNR511G/5112G/5113G/511LG			0.8	1.0	1.2	
	UNR511EG			1.70	2.14	2.60	
	UNR511DG			3.7	4.7	5.7	

Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7030 measuring methods for transistors.




2. *: Rank classification




Rank	Q	R	S	No-rank
h_{FE}	160 to 260	210 to 340	290 to 460	160 to 460

Common characteristics chart









Characteristics charts of UNR5110G














Characteristics charts of UNR5111G






Characteristics charts of UNR5112G









Characteristics charts of UNR5113G














Characteristics charts of UNR5114G






Characteristics charts of UNR5115G









Characteristics charts of UNR5116G














Characteristics charts of UNR5117G






Characteristics charts of UNR5118G









Characteristics charts of UNR5119G














Characteristics charts of UNR511DG






Characteristics charts of UNR511EG








Characteristics charts of UNR511FG













Characteristics charts of UNR511HG






Characteristics charts of UNR511LG









Characteristics charts of UNR511MG













Characteristics charts of UNR511NG





Characteristics charts of UNR511TG









Characteristics charts of UNR511VG







Characteristics charts of UNR511ZG



SMini3-F2

Unit: mm



Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products, and no license is granted under any intellectual property right or other right owned by our company or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.
- (3) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
 - Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
 - Any applications other than the standard applications intended.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
 - Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.