

**Products**

- Products Overview
- Product Search**
- Evaluate
  - FAQ's
- Design a Solution
  - Part Drawings
  - PDF-PVC Heat Shr
- How to Buy
  - Bill of Material
  - Favorite Products List
  - Locate Distributor

Home > Products Overview > Product Search >

Current refinements (click  to remove) Search Tips 

Part Number > HSTTP75-QY

Your search criteria matched only one product, shown below

**HSTTP75-QY**



**PVC DRY-SHRINK™ Heat Shrink Tubing in Reels**

- For dry locations
- Flexible, highly flame retardant tubing
- Good resistance to most fuels and oils
- Good cut through and solder resistance
- Material Type: Polyvinyl Chloride Cross-Linked
- Shrink Ratio: 2:1
- Temperature Range: -4°F to 221°F (-20°C to 105°C)
- Voltage: 600V
- UL VW-1 Recognized, CSA Certified
- For dry locations
- Flexible, highly flame retardant tubing
- Good resistance to most fuels and oils
- Good cut through and solder resistance

|  |   |
|--|---|
| Part Number                            | HSTTP75-QY  |
| RoHS Compliancy Status                 | Compliant   |
| Note                                   | HSTTP75-QY replaces HSTTP75-Q   |
| Part Description                       | Flexible, Flame Retardant PVC material offers good cut through and solder resistance. |
| Material                               | Polyvinyl Chloride Cross-Linked   |
| Color                                  | Black   |
| CSA Certified                          | Yes   |
| UL Recognized                          | E122770   |
| CE Compliant                           | No  |
| Flammability Rating                    | UL224 VW-1  |
| Length Per Reel (ft.)                  | 25  |
| Length Per Reel (m)                    | 7.6   |
| Max. Recovered I.D. (In.)              | 0.375   |
| Max. Recovered I.D. (mm)               | 9.5   |
| Min. Expanded I.D. (In.)               | 0.750   |
| Min. Expanded I.D. (mm)                | 19.0  |
| Nominal Diameter (In.)                 | 0.750   |
| Nominal Diameter (mm)                  | 19.0  |
| Nominal Recovered Wall Thickness (In.) | 0.035   |
| Nominal Recovered Wall Thickness (mm)  | 0.9   |
| Pricing Description                    | Heat Shrink Thin PVC, .75"(19.0mm) Dia Black  |
| Shrink Ratio                           | 2:1   |
| Temperature Range                      | -4°F – 221°F (-20°C – 105°C)  |
| Min. Order UOM                         | RL  |
| Min. Order Qty.                        | 1   |
| BOM Qty. (# of Pkgs.)                  | <input type="text" value="0"/>  |
| Add to Favorite Product List           | <input type="checkbox"/>  |

Please [register](#) to utilize the 'Bill of Materials', 'Submit Quotes' and 'Favorite Product List' features.