



- 注) NOTES:
1. 材質 MATERIAL  
黄銅 (板厚: 0.3)  
BRASS (THICKNESS : 0.3)
  2. メッキ仕様 TERMINAL PLATING  
接点部 : 金メッキ 0.1μmMIN.  
CONTACT AREA : GOLD 0.1 MICROMETER MINIMUM.  
 : パラジウムニッケルメッキ 0.6μmMIN.  
 : PD-NI 0.6 MICROMETER MINIMUM.  
圧着部 : 錫メッキ 1.0 μm MIN.  
CRIMP AREA : TIN 1.0 MICROMETER MINIMUM.  
下地メッキ : ニッケルメッキ 1.5 μm MIN.  
UNDER PLATE : NICKEL 1.5 MICROMETER MINIMUM.
  3. 適用電線範囲: UL 1015 , UL 1865 , AWG #16~14  
APPLICABLE WIRE RANGE : UL 1015 , UL 1865 , AWG #16~14
  4. 被覆外径 : φ3.8MAX.  
INSULATION EXTERNAL DIA : φ3.8MAX.
  5. 50638-9028 は 50638-9049 の鉛フリー品である。  
50638-9128 は 50638-9149 の鉛フリー品である。  
50638-9028 IS LEAD FREE OF 50638-9049.  
50638-9128 IS LEAD FREE OF 50638-9149.

バラ状 LOOSE	50638-9128
連鎖状 CHAIN	50638-9028
端子形状 TERMINAL CONFIGURATION	MATERIAL NO.

DO NOT SCALE DRAWING

64NO. DRWN: CH'K: APPR: 63NO. DRWN: CH'K: APPR: 62NO. DRWN: CH'K: APPR: 61NO. DRWN: CH'K: APPR:	新規作成 RELEASED 60NO. J2004-4129 DRWN: M.NAGATA '04/05/10 CH'K: K.TOJO '04/05/10 APPR: M.SASAO '04/05/10
--	--

MATERIAL 材料	#
FINISH 仕上げ	#
WIRE RANGE 適用電線範囲	#
INS. RANGE 被覆外径	#

GENERAL TOLERANCES: (UNLESS SPECIFIED) 一般公差	10 UNDER 未満 ±0.2	30 UNDER 未満 ±0.25	30 OVER 以上 ±0.3
ANGLE 角度	±3°		

MODEL NO. 50638-****	DIMENSIONS: <input type="checkbox"/> mm <input type="checkbox"/> INCH <input checked="" type="checkbox"/> mm ONLY		SHT	REV	
SCALE 5:1	DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH	TITLE: 2mm PITCH AC/DC CONN. PLUG CRIMP TERM. (MII DRAWER CONNECTOR) -LEAD FREE-			
DRAWN BY & DATE M.NAGATA '04/05/10		MOLEX INCORPORATED			
CHECKED BY & DATE K.TOJO '04/05/10					
APPROVED BY & DATE M.SASAO '04/05/10		CAD FILENAME SD-50638-001.S01	MATERIAL NO. SEE CHART	DRAWING NO. SD-50638-001	SHEET NO. 1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.					
				SIZE B	