

AJ8 switch standard actuator



AJ8 switch Wide actuator



Compliance with RoHS Directive

FEATURES

1. Power rocker switches for safety requirements.

- All versions comply with Class II EN61058-1 insulation grade. Insulation distance: 8mm Min. Contact gap: 3mm Min.

• International Standard-approved status

| | | |
|------------|------------------------|-------------------|
| | | Already approved |
| AJ8 switch | Standard actuator type | UL/C-UL, ENEC/VDE |
| | Wide actuator type | UL/C-UL, ENEC/VDE |


2. High inrush current resistance is ideal for office automation equipment.

| Type | Inrush | Contact rating | Expected life |
|------|--------|----------------|----------------------|
| AJ8 | 160A | 16A 250V AC | Min. 10 ⁴ |

3. Operation that only requires a light touch

The best operation characteristics were sought by analyzing touch data gathered by monitoring 1,500 people.

- Power Rocker Switch touch curve



4. A broad product line

The AJ8 switches are available with five different types of terminals: quick-connect terminals, soldering terminals, PC board terminals, right angle terminals and left angle terminals.

5. Eight standard actuator colors

White, black, red, dark gray, light gray, blue, green, yellow

6. Cadmium-free contact compatibility.

7. TV-8 rating type added to lineup


PRECAUTIONS WHEN USING CADMIUM-FREE CONTACT TYPE

Models with cadmium-free contacts have been introduced in order to reduce environmentally harmful substances. ("F" is affixed to the end of the part number.)

We ask customers who are currently using products with cadmium-containing contacts (no "F" at the end of the part number) to please make the switch to models with cadmium-free contacts.

When switching, operating life may differ depending on the load. Please be sure to verify this by conducting an evaluation using actual equipment.

CONSTRUCTION



Contact gap (more than 3mm)

The EN60950 (intended for office automation equipment) conforms with a 3mm gap. When directly opening or closing the primary power supply side, a contact gap of at least 3mm is required in order to ensure safety.

AJ8 (J8)

ORDERING INFORMATION

| | | | | | | | | | |
|-----------|----------|--|--|--|--|--|--|--|----------|
| AJ | 8 | | | | | | | | F |
|-----------|----------|--|--|--|--|--|--|--|----------|

8: AJ8 switch

Nil: Standard actuator
W: Wide actuator

Number of poles and Operation
1: 1-pole, single throw (ON-OFF)
2: 2-pole, single throw (ON-OFF)

Terminal shape
0: .250 Quick-connect terminal
1: Soldering terminal
2: PC board terminal
3: PC board right angle terminal (for standard actuator only)
4: PC board left angle terminal (for standard actuator only)

Actuator indication
0: No indication
1: indication
2: indication

Actuator color
W: White B: Black R: Red Z: Dark gray H: Light gray L: Blue G: Green Y: Yellow

Flange color
Nil: Black (standard color)
(Custom ordered color: W: White, R: Red, Z: Dark gray, H: Light gray, L: Blue, G: Green, Y: Yellow) Remark 1)

Insulation guard
Nil: Short guard type
T: Long guard type (.250 Quick-connect terminal and soldering terminal of standard actuator only)

F: Cadmium-free product

Remarks: 1. Please consult us for details concerning different flange colors.
2. "I O" is engraved on all flanges.
3. The color of indication on the actuator:
• White actuator: black
• Others: white
4. They come with a stamp indicating international standards without your request.

TV rating type

| | | | | | | | |
|-----------|----------|----------|--|--|----------|-----------|----------|
| AJ | 8 | 2 | | | B | TV | F |
|-----------|----------|----------|--|--|----------|-----------|----------|

8: AJ8 switch

Number of poles and Operation
2: 2-pole, single throw (ON-OFF)

Terminal shape
0: .187 Quick-connect terminal
1: Soldering terminal

Actuator indication
0: No indication
2: indication

Actuator color
B: Black

Rating
TV: TV rating

F: Cadmium-free product

PRODUCT TYPES

1. Standard actuator type

(1) Without indication on actuators

| Terminal shape | Poles | Operating types | Part No. | |
|-------------------------------|--------|-----------------|--------------------|--|
| | | | Without indication | |
| .250 Quick-connect terminal | 1-pole | ON-OFF | AJ8100*F | |
| | 2-pole | | AJ8200*F | |
| Soldering terminal | 1-pole | | AJ8110*F | |
| | 2-pole | | AJ8210*F | |
| PC board terminal | 1-pole | | AJ8120*F | |
| | 2-pole | | AJ8220*F | |
| PC board right angle terminal | 1-pole | | AJ8130*F | |
| | 2-pole | | AJ8230*F | |
| PC board left angle terminal | 1-pole | | AJ8140*F | |
| | 2-pole | | AJ8240*F | |

- Remarks: 1. A letter indicating the actuator color is entered in place of asterisk. (W: White, B: Black, R: Red, Z: Dark gray, H: Light gray, L: Blue, G: Green, and Y: Yellow). Standard flange color is black. For other colors type, they are custom ordered. For requests of other flange color, please enter the following letter before the "F" in the part number. (W: White, R: Red, Z: Dark gray, H: Light gray, L: Blue, G: Green and Y: Yellow)
2. Long guard type is available for .250 Quick-connect terminal and soldering terminal type. When ordering, please add a "T" before the "F" at the end of the part number.
3. The color of indication on the actuator:
- For white actuator: black
 - For others: white
4. They come with a stamp indicating international standards without your request.
5. Note that the position of the I mark on the flange is used as a reference for left angle and right angle terminals as shown in the diagram below.



Right angle terminal



Left angle terminal


(2) With indication on actuators

| Terminal shape | Poles | Operating types | Part No. | |
|-------------------------------|--------|-----------------|---------------------|---------------------|
| | | | With I ○ indication | With — ○ indication |
| .250 Quick-connect terminal | 1-pole | ON-OFF | AJ8101*F | AJ8102*F |
| | 2-pole | | AJ8201*F | AJ8202*F |
| Soldering terminal | 1-pole | | AJ8111*F | AJ8112*F |
| | 2-pole | | AJ8211*F | AJ8212*F |
| PC board terminal | 1-pole | | AJ8121*F | AJ8122*F |
| | 2-pole | | AJ8221*F | AJ8222*F |
| PC board right angle terminal | 1-pole | | AJ8131*F | AJ8132*F |
| | 2-pole | | AJ8231*F | AJ8232*F |
| PC board left angle terminal | 1-pole | | AJ8141*F | AJ8142*F |
| | 2-pole | | AJ8241*F | AJ8242*F |

- Remarks: 1. A letter indicating the actuator color is entered in place of asterisk. (W: White, B: Black, R: Red, Z: Dark gray, H: Light gray, L: Blue, G: Green, and Y: Yellow). Standard flange color is black. For other colors type, they are custom ordered. For requests of other flange color, please enter the following letter before the "F" in the part number. (W: White, R: Red, Z: Dark gray, H: Light gray, L: Blue, G: Green and Y: Yellow)
2. Long guard type is available for .250 Quick-connect terminal and soldering terminal type. When ordering, please add a "T" before the "F" at the end of the part number.
3. The color of indication on the actuator:
- For white actuator: black
 - For others: white
4. They come with a stamp indicating international standards without your request.
5. Note that the position of the I mark on the flange is used as a reference for left angle and right angle terminals as shown in the diagram below.



Right angle terminal



Left angle terminal

AJ8 (J8)

2. Wide actuator type

(1) Without indication on actuators

| Terminal shape | Poles | Operating types | Part No. | |
|-----------------------------|--------|-----------------|--------------------|--|
| | | | Without indication | |
| .250 Quick-connect terminal | 1-pole | ON-OFF | AJ8W100*F | |
| | 2-pole | | AJ8W200*F | |
| Soldering terminal | 1-pole | | AJ8W110*F | |
| | 2-pole | | AJ8W210*F | |
| PC board terminal | 1-pole | | AJ8W120*F | |
| | 2-pole | | AJ8W220*F | |

(2) With indication on actuators

| Terminal shape | Poles | Operating types | Part No. | |
|-----------------------------|--------|-----------------|---------------------|---------------------|
| | | | With ○ indication | With — ○ indication |
| .250 Quick-connect terminal | 1-pole | ON-OFF | AJ8W101*F | AJ8W102*F |
| | 2-pole | | AJ8W201*F | AJ8W202*F |
| Soldering terminal | 1-pole | | AJ8W111*F | AJ8W112*F |
| | 2-pole | | AJ8W211*F | AJ8W212*F |
| PC board terminal | 1-pole | | AJ8W121*F | AJ8W122*F |
| | 2-pole | | AJ8W221*F | AJ8W222*F |

- Remarks: 1. A letter indicating the actuator color is entered in place of asterisk. (W: White, B: Black, R: Red, Z: Dark gray, H: Light gray, L: Blue, G: Green, and Y: Yellow).
Standard flange color is black. For other colors type, they are custom ordered. For requests of other flange color, please enter the following letter before the "F" in the part number. (W: White, R: Red, Z: Dark gray, H: Light gray, L: Blue, G: Green and Y: Yellow)
2. The color of indication on the actuator:
 - For white actuator: black
 - For others: white
3. They come with a stamp indicating international standards without your request.

3. TV rating type

| Terminal shape | Poles | Operating types | Part No. | |
|-----------------------------|--------|-----------------|--------------------|---------------------|
| | | | Without indication | With — ○ indication |
| .187 Quick-connect terminal | 2-pole | ON-OFF | AJ8200BTVF | — |
| | | | — | AJ8202BTVF |
| AJ8210BTVF | | | — | |
| — | | | AJ8212BTVF | |

SPECIFICATIONS

1. Contact rating

| Voltage | Resistive load ($\cos \phi \approx 1.0$) | Motor load (EN61058-1) ($\cos \phi \approx 0.6$) | Inrush load |
|---------|-----------------------------------------------|----------------------------------------------------------|--------------|
| 250V AC | 16A | 4A | 100A (8.3ms) |

Remark: The motor load is in accordance with EN61058-1. Inrush current can be switched up to the value of 6 times the indicated rating.

2. TV rating

| Voltage | Resistive load | Motor load (EN6105801) | Capacitor load (EN61058-1) | Lamp load (UL1054) | Expected electrical life |
|---------|-----------------------------|-----------------------------|----------------------------|--------------------|--------------------------|
| | ($\cos \phi \approx 1.0$) | ($\cos \phi \approx 0.6$) | (Inrush load) | (TV-8) | (at 7 cpm) |
| 120V AC | — | — | — | 8/117A | Min. 2.5×10^4 |
| 250V AC | 16A | 4A | 160A (8.3ms) | — | Min. 10^4 |

3. Characteristics

| | | |
|----------------------------------------------------------------|-------------------------------------|-----------------------------------------------------------------|
| Expected life (Min. operations) | Mechanical | Min. 5×10^4 (at 20 cpm.) |
| | Electrical* | Min. 10^4 (at 7 cpm., at rated load) |
| Initial insulation resistance (Between terminals) | | Min. 100 MΩ (at 500V DC measured by insulation resistive meter) |
| Initial breakdown voltage (Between terminals) | | 2,000 Vrms detection current: 10 mA |
| Initial contact resistance (By voltage drop at 1A, 2 to 4V DC) | | Max. 100mΩ |
| Temperature rise | at 6×10^3 ope. or less | Max. 30°C (UL1054) |
| | from 6×10^3 ope. to 10^4 | Max. 55°C (EN61058-1) |
| Vibration resistance | | 10 to 55 Hz at double amplitude of 1.5mm |
| Shock resistance | | Min. 490m/s ² {50 G} |
| Actuator strength | | 40 N {4.08kgf} for 1 minute (operating direction) |
| Terminal strength (.250 Quick-connect terminal) | | 100 N {10.2kgf} for 1 minute or more (Pull & push direction) |
| Ambient temperature | | -25°C to +85°C (Not freezing below 0°C) |
| Flame retardancy | | UL94V-0 |
| Tracking resistance | | Min. 175 |
| Operating force (reference characteristics) | 1-pole | $2.45 \pm 1.47\text{N}$ {0.25 ±0.15kgf} |
| | 2-pole | $4.5 \pm 2.5\text{N}$ {0.46 ±0.25kgf} |
| Contact material | | AgSnO ₂ alloy |


Remark: Test conditions are in accordance with EN61058-1, UL1054 and JIS C 6571.

* Except TV rating type

DIMENSIONS

mm General tolerance: ±0.5

1. .250 Quick-connect terminal/Short guard type



Long guard type
.250 Quick-connect terminal






Diagram of recommended
locations for panel
mounting holes



| Panel thickness | X |
|-----------------|--------------------|
| 0.75 to 1.25 | $28.2^{+0}_{-0.1}$ |
| 1.25 to 2 | $28.4^{+0}_{-0.1}$ |
| 2 to 3 | $28.8^{+0}_{-0.1}$ |

2. Soldering terminal



Long guard type
Soldering terminal





Diagram of recommended
locations for panel
mounting holes



| Panel thickness | X |
|-----------------|--------------------|
| 0.75 to 1.25 | $28.2^{+0}_{-0.1}$ |
| 1.25 to 2 | $28.4^{+0}_{-0.1}$ |
| 2 to 3 | $28.8^{+0}_{-0.1}$ |

AJ8 (J8)

3. PC board terminal

mm General tolerance: ± 0.5





Diagram of recommended locations for panel mounting holes



| Panel thickness | X |
|-----------------|-----------------------|
| 0.75 to 1.25 | 28.2 $^{+0.0}_{-0.1}$ |
| 1.25 to 2 | 28.4 $^{+0.0}_{-0.1}$ |
| 2 to 3 | 28.8 $^{+0.0}_{-0.1}$ |

4. PC board right angle terminal





Diagram of recommended locations for panel mounting holes



| Panel thickness | X |
|-----------------|-----------------------|
| 0.75 to 1.25 | 28.2 $^{+0.0}_{-0.1}$ |
| 1.25 to 2 | 28.4 $^{+0.0}_{-0.1}$ |
| 2 to 3 | 28.8 $^{+0.0}_{-0.1}$ |

Remark: Left angle terminal type is also available.

5. Wide actuator type





Diagram of recommended locations for panel mounting holes



| Panel thickness | X |
|--------------------|-----------------------|
| 1 to less than 1.8 | 30.0 $^{+0.0}_{-0.1}$ |
| 1.8 to 2.3 | 30.7 $^{+0.0}_{-0.1}$ |

Remark: Dimensions for the terminals of soldering terminal type and PC board terminal type are the same as those of standard actuator type.

NOTES

1. Switch mounting


Mount the switch with the hole cutting dimensions shown in the dimensions. Contact us if you are considering using a panel of other than the recommended size and shape.

2. Regarding fastening lead wires to terminals

1) When connecting the tab terminals, use a .250 Quick-connect and insert the terminals straight in. If they are skewed, the terminals will require excessive insertion force. In addition, there is some variation in the insertion force required for different receptacles from different manufacturers, so confirm how much force is needed under actual conditions. Do not solder wires onto tab terminals.

2) With manual soldering: Complete the soldering connection work within 3 seconds with the tip of the soldering iron (60W soldering iron) at a temperature of 420°C or lower, and take care not to apply any force to the terminal area.

Avoid touching the switch with soldering iron.



Refer to the diagram above, "soldering position," for details on the position where a wire should be soldered to a terminal. When soldering PC board terminals, keep soldering time to within 5 s at 270°C soldering bath or within 3 s at 350°C soldering bath.

3) The terminals should be connected in such a way that they are not under constant stress from the connecting wires.

4) Terminal material is copper alloy which may discolor due to finger's oil or after a long time. But that discoloration does not effect actual performance.

3. Resistance to chemicals

To clean the switch unit, use a neutral detergent diluted with water. Do not use acidic or alkaline solvents as they may damage the switch. Furthermore, be careful not to get any of the detergent solution inside of the switch while cleaning it.

4. Environment

Avoid using and storing these switches in a location where they will be exposed to corrosive gases, silicon, or high dust levels, all of which can have an adverse effect on the contacts.

5. Take care not to drop the product as it may impair performance.

REFERENCE

1. Outline of UL1054 test

Overload test AJ8: 20A 250V AC
(Power factor 0.75 to 0.8)

50 operation


Endurance test AJ8: 16A 250V AC
(Power factor 0.75 to 0.8)

6×10³ operation

After testing, temperature rise of terminals should be less than 30°C and no abnormality should be observed in characteristics.

2. Outline of EN61058-1 test

After switching 5 × 10³ times on the above load condition at both 85±5°C and 25±10°C, temperature rise of terminals should be less than 55°C and no abnormality should be observed in characteristics.



INTRODUCTION TO 4P CONNECTORS FOR THE AJ8 SWITCH (produced by Nippon Tanshi co.,Ltd)



Notes) This AJ8 switch connector is not available from Matsushita Electric Works. Contact us for further details on this connector.

Suitable switches: AJ8 switch, .250 Quick-connect terminal

(Note: Terminal guard long type switches are not suitable for this connector.)

Housing

Product number: N1620-4204

Receptacle

Product number: 17168-2 (post-plated product for fine wires)
17168-M2 (material plated product for fine wires)
172131-M2 (for thick wires)