


NOTES:
 TEST ALL (100%) CONNECTORS FOR INSERTION LOSS (I.L.) AND RETURN LOSS (R.L.)
 I.L. TO BE 0.35dB OR BETTER MEASURE WITH A 1550 NM SOURCE
 R.L. TO BE -55dB OR BETTER MEASURED WITH A 1550 NM SOURCE

PART NUMBER	LENGTH (M)
FA1SMLCLC	1
FA2SMLCLC	2
FA3SMLCLC	3

I N V E N T O R S	HellermannTyton®		R E V I S I O N	D level 	D I M E N S I O N S	.xxxx = ±.013		number SEE CHART phase Production	format AH CAD SW 2009 scale 1:2	
	ALL PROPRIETARY RIGHTS IN THE SUBJECT MATTER SHOWN ON THIS DRAWING ARE EXCLUSIVE PROPERTY OF HELLERMANNTYTON			by AAC		.xxx = ±.13				name SINGLEMODE SIMPLEX LC TO LC FIBER OPTIC CABLE ASSEMBLY
	name _____ date _____ city, state _____			date 11/10/2010		.xx = ±.3		material ASSEMBLED		drawn AAC checked KAC approved _____
				ECN # 011681		.X = ±.8				type Customer sheet 1 of 1
		part level -	∠ = ±0.5°				number MI3026054CST			
			unless otherwise specified							
			units millimeters							