


Weidmüller terminal - SAK-series- are proved in millions of applications for more than 50 years.

Available for the two rail systems TS32 and TS35, the SAK terminals are useable for every application and for all cross-sections. SAK terminals fulfill the requirements of EN 60 947-7-1.




Thermosetting plastic or Thermoplastic


Terminal of thermosetting plastic are normally used in applications where high continuous service temperature and high flammability level are necessary. The Weidmüller thermosetting plastic KRG is very resistant against infection through mould and micro-organisms.

The thermoplastic material Polyamide 66 has very good electrical and mechanical properties upto 100°C. PA66 is flexible and unsusceptible to fracture, even with low temperatures.

Polyamid 66 has improved fire resistance and is self-extinguishing with flammability level V2 according to UL 94.



Thermosetting plastic




Cross-connection systems

40% of all terminals are cross-connected for potential branching.

Weidmüller distinguishes between the following cross-connection units for SAK-series:

- type Q pre-assembled cross-connections
- type QL permanent cross-connections
- type VL removeable cross-connection straps
- type QS removeable cross-connection plugs

Cross-connection systems from the SAK and AKZ series, type Q, QL or VL or other freely accessible live components, must be protected with appropriate covers ADP 1 or 4 or TSK 31.5 as long as they are to be inserted safe from contact.



Approvals

The following approvals apply to SAK terminals:

- UL-USA
- CSA-Canada
- GOST-Russia
- SEV-Switzerland
- KEMA-Netherlands
- Lloyds Register of Shipping
- Germanischer Lloyd
- Det Norske Veritas

SAK portfolio

- Feed-through terminals
- Protective conductor terminals
- Fuse terminals
- Disconnect-test terminals
- Feed-through terminals with tab, solder, WireWrap and Termi Point connections
- Initiator terminals, Actuator terminals
- Stud terminals

Accessories



An extensive assortment of accessories is available for Weidmüller SAK terminals:

- Partitions
- Cover plates
- Small partitions
- Test plugs
- Test adapters
- Marking material
- Cross-connections and
- Covers

Positioning of end plates or partitions between cross-connections

Operating voltage	Terminal width (in mm)					
	≤ 6	≤ 8	10	12	18	22
125 V ~	AP	-	-	-	-	-
250 V ~	AP	-	-	-	-	-
380 V ~	AP	AP	-	-	-	-
440 V ~	TW	AP	AP	AP	AP	-
500 V ~	TW	TW	AP	AP	AP	-
660 V ~	TW	TW	TW	TW	TW	AP
750 V ~	TW	TW	TW	TW	TW	AP

In PA terminals small partitions (TSch) have to be used up to 380 V.

Feed-through terminals

SAKD 2.5 N SAKD 2.5/10/35



UL LR

Dimensions/approvals	
Width/length/height (mm)	with TS 32 5/32.5/43.5
Width/length/height (mm)	with TS 35 x 7.5 5/44/38
Insulation stripping length/clamping screw/screwdriver blade	10/M 2.5/3.5 x 0.6
Rated data according to IEC 60 947-7-1	
Rated voltage/current/cross-section	500 V/24 A/2.5 mm ²
Rated impulse voltage/pollution severity	6 kV/3
Further technical data	
Tightening torque range	Nm 0.4...0.6
Torque setting with electric screwdriver type DMS 2	1

SAK 2.5/35 SAK 2.5/10/35



UL LR

Dimensions/approvals	
Width/length/height (mm)	6/45/40
Insulation stripping length/clamping screw/screwdriver blade	10/M 2.5/3.5 x 0.6
Rated data according to IEC 60 947-7-1	
Rated voltage/current/cross-section	800 V/24 A/2.5 mm ²
Rated impulse voltage/pollution severity	8 kV/3
Further technical data	
Tightening torque range	Nm 0.4...0.6
Torque setting with electric screwdriver type DMS 2	1

SAK 2.5 SAK 2.5/10



UL LR DNV

Dimensions/approvals	
Width/length/height (mm)	6/36.5/46.5
Insulation stripping length/clamping screw/screwdriver blade	10/M 2.5/3.5 x 0.6
Rated data according to IEC 60 947-7-1	
Rated voltage/current/cross-section	800 V/24 A/2.5 mm ² ³⁾
Rated impulse voltage/pollution severity	8 kV/3
Further technical data	
Tightening torque range	Nm 0.4...0.6
Torque setting with electric screwdriver type DMS 2	1

SAK 4/35 SAK 4/10/35



UL

Dimensions/approvals	
Width/length/height (mm)	6.5/40/51.5
Insulation stripping length/clamping screw/screwdriver blade	12/M 3/3.5 x 0.6
Rated data according to IEC 60 947-7-1	
Rated voltage/current/cross-section	800 V/32 A/4 mm ²
Rated impulse voltage/pollution severity	8 kV/3
Further technical data	
Tightening torque range	Nm 0.5...1.0
Torque setting with electric screwdriver type DMS 2	2

Clampable conductor

Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	0.5...2.5
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...2.5
Plug gauge according to 60 947-7-1	Size	A 2
Continuous current of terminal for conductor size		30 A/4 mm ²
Continuous current rating of cross-connection 2...5-pole	A	24
Continuous current rating of cross-connection 6...10-pole	A	24

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/20 A/28...12 AWG
Voltage/current/conductor size	CSA	300 V/20 A/22...12 AWG

Ordering data

Version	Qty.	Qty.
KrG		
Blue KrG		
KrS		
PA		
Blue PA		
Orange PA		
Terminal block with marking PA		
Terminal block without marking PA		

Cat. No.	Qty.
0215560000 ¹⁾⁰⁰	0268860000 ¹⁾⁰⁰
0215580000 ¹⁾⁰⁰	0268880000 ¹⁾⁰⁰
0401060000 ¹⁾⁰⁰	0523160000 ¹⁾⁰⁰
0401160000 ¹⁾⁰⁰	

Cat. No.	Qty.
0380420000 ¹⁾¹⁰⁰	0380470000 ¹⁾¹⁰⁰
0380460000 ¹⁾¹⁰⁰	0380480000 ¹⁾¹⁰⁰
0499460000 ¹⁾¹⁰	0499560000 ¹⁾¹⁰

Cat. No.	Qty.
0279620000 ¹⁾¹⁰⁰	0279670000 ¹⁾¹⁰⁰
0279660000 ¹⁾²⁾¹⁰⁰	0279680000 ¹⁾²⁾¹⁰⁰
1326360000 ¹⁾²⁾¹⁰⁰	0322560000 ¹⁾²⁾¹⁰
0322860000 ¹⁾²⁾¹⁰	

Cat. No.	Qty.
0443620000 ¹⁾¹⁰⁰	0443670000 ¹⁾¹⁰⁰
0443660000 ¹⁾¹⁾¹⁰⁰	0443680000 ¹⁾¹⁾¹⁰⁰
1323660000 ¹⁾¹⁾¹⁰⁰	0530460000 ¹⁾¹⁾¹⁰
0530360000 ¹⁾¹⁾¹⁰	

End plate (thickness mm)

Type	Cat. No.	Qty.
KrG		
Blue KrG		
KrS		
PA	AP (1.5) 0150960000	20
Blue PA	AP (1.5) 0150980000	20
PA		
Blue PA		

Partition (thickness mm)

Type	Cat. No.	Qty.
KrG		
Blue KrG		
KrS		
PA	TW (1.5) 0191860000	20
Blue PA	TW (1.5) 0191880000	20
HP	TW (1.5) 0307500000	20

Small partition

Type	Cat. No.	Qty.
TSch 1		
TSch 3	0366860000	100

Cross-connection

Type	Cat. No.	Qty.
Q 4		
2-pole	Q 2 0367800000	50
3-pole	Q 3 0367900000	50
4-pole	Q 4 0368000000	50
10-pole	Q 10 0368100000	20

Cover plates

Type	Cat. No.	Qty.
AD 4	0303400000	50
BSKM3x22	0128900000	100

Switchable cross-connection link

Type	Cat. No.	Qty.
VL 2		
BS		
VH		
VL 2	0197000000	100
VH	0285100000	50
BS	0292500000	100

Marking tags

Type	Cat. No.	Qty.
DEK		
Standard		
DEK 5	see "Accessories"	
DEK 6	see "Accessories"	
DEK 6	see "Accessories"	
DEK 6.5	see "Accessories"	


Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ Contact-proof with ADP 4 cover profile (see section "Accessories")
²⁾ Not suitable for SST 3 safety pin

³⁾ Cat. No. **0279660000**, **0279680000**, **0380460000** and **0380480000**, 41 A for 6 mm²

Feed-through terminals


SAK 4 SAK 4/10



DK 4 Q* DKB4 Q*/10*



DK 4 DK4/35



Dimensions/approvals

Width/length/height (mm)	with TS 32	
Width/length/height (mm)	with TS 35 x 7.5	
Insulation stripping length/clamping screw/screwdriver blade		

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	800 V/32 A/4 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data

Tightening torque range	Nm	0.5...1.0
Torque setting with electric screwdriver type DMS 2		2

Clampable conductor

Solid H07V-U	mm ²	0.5...6
Stranded H07V-R	mm ²	0.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	
With/without plastic insulating collar	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 4
Continuous current of terminal for conductor size		41 A/6 mm ²
Continuous current rating of cross-connection 2...5-pole	A	36
Continuous current rating of cross-connection 6...10-pole	A	

Technical data

Voltage/current/conductor size	UL	600 V/20 A/22...12 AWG
Voltage/current/conductor size	CSA	600 V/36 A/26...10 AWG

Ordering data

Version	Cat. No.	Qty.
KrG	0128320000	100
Blue KrG	0128370000	100
KrS	0128330000	100
PA	0128360000 ¹⁾²⁾	100
Blue PA	0128380000 ¹⁾²⁾	100
Orange PA	0105060000 ¹⁾²⁾	100
Terminal block with marking PA	0322660000 ¹⁾²⁾	10
Terminal block without marking PA	0308860000 ¹⁾²⁾	10

End plate (thickness mm)

Type	Cat. No.	Qty.
KrG	AP (1.5) 0117920000	20
Blue KrG	AP (1.5) 0117970000	20
KrS	AP (1.5) 0117930000	20
PA	AP (1.5) 0117960000	20
Blue PA	AP (1.5) 0117980000	20
PA		
Blue PA		

Partition (thickness mm)

Type	Cat. No.	Qty.
KrG	TW (2.5) 0130120000	20
Blue KrG	TW (2.5) 0103170000	20
KrS	TW (2.5) 0130130000	20
PA	TW (1.5) 0130160000	20
Blue PA	TW (1.5) 0130180000	20
HP	TW (1.0) 0197100000	20

Small partition

TSch 6	TSch 1	0319160000	100
--------	--------	-------------------	-----

Cross-connection

Type	Cat. No.	Qty.
Q 2	0336700000	50
Q 3	0336800000	50
Q 4	0336900000	50
Q 10	0368800000	20
QB 2	0482700000 **	100
QB 3	0482800000 **	50
QB 4	0482900000 **	50

Switchable cross-connection link

VL 2	VL 2	0197000000	100
BS	VH	0285100000	50
	BS	0292500000	100

Marking tags

DEK	Standard	DEK6.5	see "Accessories"
-----	----------	--------	-------------------

Mounting rails, end brackets, further marking material see "Accessories"

* Accepts LS 2.8 shield lugs Cat. No. **1056400000**

** 2.5 mm² conductor connection when using QB

SAK 4

UL	LR	DNV
----	----	-----

6.5/40/51.5

--

--

800 V/32 A/4 mm ²

8 kV/3

--

0.5...1.0

2

--

0.5...6

0.5...4

0.5...4

0.5...4

A 4

41 A/6 mm ²

36

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

DK 4 Q*

UL	
----	--

6/54/60

6/54/60.5

9/M 3/3.5 x 0.6

500 V/2 x 32 A/4 mm ²

6 kV/3

--

0.5...1.0

2

--

0.5...4

0.5...4

0.5...4

A 3

32 A/4 mm ²

32

32

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

--

DK 4

UL	
----	--

6/54/60

6/54/60.5

9/M 3/3.5 x 0.6

500 V/2 x 32 A/4 mm ²


6 kV/3

--

0.5...1.0

Feed-through terminals

DK4 QV* DK4 QV/35*



UL

Dimensions/approvals	
Width/length/height (mm)	with TS 32 6/54/60
Width/length/height (mm)	with TS 35 x 7.5 6/54/60.5
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	500 V/32 A/4 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data

Tightening torque range	Nm 0.5...1.0
Torque setting with electric screwdriver type DMS 2	2

Clampable conductor

Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	0.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	
With/without plastic insulating collar	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 3
Continuous current of terminal for conductor size		32 A/4 mm ²
Continuous current rating of cross-connection 2...5-pole	A	32
Continuous current rating of cross-connection 6...10-pole	A	32

Rated data according to UL/CSA

Voltage/current/conductor size	UL 300 V/27 A/22...12 AWG
Voltage/current/conductor size	CSA 300 V/10 A/26...12 AWG

Ordering data

Version	Qty.	Qty.
KrG		
Blue KrG		
KrS		
PA	0590260000 ¹⁾ 100 0363660000 ¹⁾ 100	
Blue PA	0590280000 ¹⁾ 100 0363680000 ¹⁾ 100	
Orange PA		
Terminal block with marking		
Terminal block without marking		

Width/length/height (mm)	8/40/51.5
Width/length/height (mm)	8/45/44
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 3.5/4.0 x 0.8

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	800 V/41 A/6 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data

Tightening torque range	Nm 0.8...1.6
Torque setting with electric screwdriver type DMS 2	3

Clampable conductor

Solid H07V-U	mm ²	0.5...10
Stranded H07V-R	mm ²	0.5...6
Flexible H07V-K	mm ²	0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	
With/without plastic insulating collar	mm ²	0.5...6
Plug gauge according to 60 947-7-1	Size	A 5
Continuous current of terminal for conductor size		41
Continuous current rating of cross-connection 2...5-pole	A	41
Continuous current rating of cross-connection 6...10-pole	A	32

Rated data according to UL/CSA

Voltage/current/conductor size	UL 600 V/40 A/22...8 AWG
Voltage/current/conductor size	CSA 600 V/47 A/20...8 AWG

Ordering data

Version	Qty.	Qty.
KrG		
Blue KrG		
KrS		
PA	0193260000 ¹⁾ 100 0380560000 ¹⁾ 100	
Blue PA	0193280000 ¹⁾ 100 0380580000 ¹⁾ 100	
Orange PA		
Terminal block with marking		
Terminal block without marking		

SAK 6 N SAK 6/10/35



UL

Width/length/height (mm)	10/40/51.5
Width/length/height (mm)	10/45/44
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 4/5.5 x 1.0

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	800 V/57 A/10 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data

Tightening torque range	Nm 1.2...2.0 ²⁾
Torque setting with electric screwdriver type DMS 2	4

Clampable conductor

Solid H07V-U	mm ²	1.5...10
Stranded H07V-R	mm ²	2.5...16
Flexible H07V-K	mm ²	1.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	
With/without plastic insulating collar	mm ²	1.5...10
Plug gauge according to 60 947-7-1	Size	B 6
Continuous current of terminal for conductor size		76 A/16 mm ²
Continuous current rating of cross-connection 2...5-pole	A	57
Continuous current rating of cross-connection 6...10-pole	A	76

Rated data according to UL/CSA

Voltage/current/conductor size	UL 600 V/60 A/14...6 AWG ³⁾
Voltage/current/conductor size	CSA 600 V/65 A/14...6 AWG ³⁾

Ordering data

Version	Qty.	Qty.
KrG		
Blue KrG		
KrS		
PA	0110020000 ¹⁾ 100 0443720000 ¹⁾ 100	
Blue PA	0110070000 ¹⁾ 100 0443770000 ¹⁾ 100	
Orange PA		
Terminal block with marking		
Terminal block without marking		

SAK 10 SAK 10/10/35



UL

Width/length/height (mm)	12/50/57.5
Width/length/height (mm)	12/50/50
Insulation stripping length/clamping screw/screwdriver blade	15 mm/M 4/5.5 x 1.0

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	1000 V/76 A/16 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data

Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4

Clampable conductor

Solid H07V-U	mm ²	2.5...10
Stranded H07V-R	mm ²	4...16 ²⁾
Flexible H07V-K	mm ²	4...16
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	
With/without plastic insulating collar	mm ²	4...16
Plug gauge according to 60 947-7-1	Size	B 6
Continuous current of terminal for conductor size		76
Continuous current rating of cross-connection 2...5-pole	A	76
Continuous current rating of cross-connection 6...10-pole	A	76

Rated data according to UL/CSA

Voltage/current/conductor size	UL 600 V/80 A/12...4 AWG
Voltage/current/conductor size	CSA 600 V/87 A/10...4 AWG

Ordering data

Version	Qty.	Qty.
KrG		
Blue KrG		
KrS		
PA	0271020000 ¹⁾ 50 0380620000 ¹⁾ 50	
Blue PA	0271080000 ¹⁾ 50 0380680000 ¹⁾ 50	
Orange PA		
Terminal block with marking		
Terminal block without marking		

SAK 16 SAK 16/35



UL

Width/length/height (mm)	12/50/57.5
Width/length/height (mm)	12/50/50
Insulation stripping length/clamping screw/screwdriver blade	15 mm/M 4/5.5 x 1.0

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	1000 V/76 A/16 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data

Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4

Clampable conductor

Solid H07V-U	mm ²	2.5...10
Stranded H07V-R	mm ²	4...16 ²⁾
Flexible H07V-K	mm ²	4...16
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	
With/without plastic insulating collar	mm ²	4...16
Plug gauge according to 60 947-7-1	Size	B 6
Continuous current of terminal for conductor size		76
Continuous current rating of cross-connection 2...5-pole	A	76
Continuous current rating of cross-connection 6...10-pole	A	76

Rated data according to UL/CSA

Voltage/current/conductor size	UL 600 V/80 A/12...4 AWG
Voltage/current/conductor size	CSA 600 V/87 A/10...4 AWG

Ordering data

Version	Qty.	Qty.
KrG		
Blue KrG		
KrS		
PA	0271030000 ¹⁾ 50	
Blue PA	0271060000 ¹⁾ 50 0380660000 ¹⁾ 50	
Orange PA	0271080000 ¹⁾ 50 0380680000 ¹⁾ 50	
Terminal block with marking		
Terminal block without marking		

End plate (thickness mm)

Type	Cat. No.	Qty.
AP		
KrG		
Blue KrG		
KrS		
PA	AP (1.5) 1397160000	20
Blue PA	AP (1.5) 1397180000	20

Partition (thickness mm)

Type	Cat. No.	Qty.
TW		
WTW		
Small partition		
KrG		
Blue KrG		
KrS		
PA	WTW (Ex) 1058800000	20
Blue PA		
TSch 6	TW (2.0) 0607000000	20
	TSch 6 0190260000	100

Cross-connection

Type	Cat. No.	Qty.
Q 4		
QB 4		
2-pole	Q 2 0336400000	50
3-pole	Q 3 0336500000	50
4-pole	Q 4 0336600000	50
10-pole	Q 10 0368600000	20
	QB 2 0482700000 **	100
	QB 3 0482800000 **	50
	QB 4 0482900000 **	50

Cover

Type	Cat. No.	Qty.
AD 4	0303400000	50
BSK M 2.5 x18	0303300000	100

Switchable cross-connection link

Type	Cat. No.	Qty.
VL 2	0446700000	50
VH	1056500000	100
BS	0343100000	100

Marking tags

Print	DEK	Standard
	DEK 6	see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* Accepts LS 2.8 shield lugs Cat. No. **1056400000**
 ** 2.5 mm² conductor connection when using QB

¹⁾ Contact-proof with ADP 4 cover profile (see section "Accessories")

²⁾ Tightening torque for 16 mm² stranded: 2 Nm

³⁾ Tightening torque for 16 mm² and AWG6: 2 Nm

Feed-through terminals

SAK 35 N SAK 35 N/35



UL CE LR DNV

Width/length/height (mm) with TS 32	16/58/67.5
Width/length/height (mm) with TS 35 x 7.5	16/63/60
Insulation stripping length/clamping screw/screwdriver blade	18 mm/M 6/6.5 x 1.2

Rated data according to IEC 60 947-7-1	
Rated voltage/current/cross-section	1000 V/125 A/35 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data	
Tightening torque range	Nm 4.0...5.0/4.0...6.0***
Torque setting with electric screwdriver type DMS 2	

Clampable conductor	
Solid H07V-U	mm ² 2.5...16
Stranded H07V-R	mm ² 2.5...50
Flexible H07V-K	mm ² 2.5...35
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 2.5...35
Plug gauge according to 60 947-7-1	Size B 8
Continuous current of terminal for conductor size	125 A/35 mm ²
Continuous current rating of cross-connection 2...5-pole	A 65
Continuous current rating of cross-connection 6...10-pole	A 65

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 600 V/100 A/12...2 AWG
Voltage/current/conductor size	CSA 600 V/120 A/12...2 AWG

Ordering data	Version	Qty.	Qty.
	KrG	0550620000	20 0608220000
	Hexagon socket KrG	0555720000	20 0608320000
	Hexagon socket Blue KrG		0608370000
	KrS	0550630000	20
	Hexagon socket KrS	0555730000	20
	PA	0550660000	20 0608260000
	Hexagon socket PA	0555760000	20 0608360000
	Blue PA		

SAK 35 SAK 35/35



UL CE KEF LR DNV

Width/length/height (mm)	18/58/67.5
Width/length/height (mm)	18/58/60
Insulation stripping length/clamping screw/screwdriver blade	20 mm/M 6/6.5 x 1.2

Rated data according to IEC 60 947-7-1	
Rated voltage/current/cross-section	800 V/125 A/35 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data	
Tightening torque range	Nm 4.0...5.0/4.0...6.0***
Torque setting with electric screwdriver type DMS 2	

Clampable conductor	
Solid H07V-U	mm ² 6...16
Stranded H07V-R	mm ² 16...50
Flexible H07V-K	mm ² 10...35
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 10...35
Plug gauge according to 60 947-7-1	Size B 9
Continuous current of terminal for conductor size	125 A/35 mm ²
Continuous current rating of cross-connection 2...5-pole	A 99
Continuous current rating of cross-connection 6...10-pole	A 99

Rated data according to UL/CSA	
Voltage/current/conductor size	600 V/100 A/6...2 AWG
Voltage/current/conductor size	600 V/145 A/6...2 AWG

Ordering data	Version	Qty.	Qty.
	KrG	0303520000	20
	Hexagon socket KrG	0476520000	20
	KrS	0303530000	20
	Hexagon socket KrS	0303560000	20 0380760000
	PA	0476560000	20 0582460000
	Hexagon socket PA	0303580000	20 0380780000
	Blue PA		

SAK 70 SAK 70/35



UL CE LR DNV

Width/length/height (mm)	22/75/79.5
Width/length/height (mm)	22/75/87
Insulation stripping length/clamping screw/screwdriver blade	24 mm/M 8/S 6 D911

Rated data according to IEC 60 947-7-1	
Rated voltage/current/cross-section	1000 V/192 A/70 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data	
Tightening torque range	Nm 6.0...12.0
Torque setting with electric screwdriver type DMS 2	

Clampable conductor	
Solid H07V-U	mm ² 16
Stranded H07V-R	mm ² 16...70 1) 3x9x0.8
Flexible H07V-K	mm ² 16...70 1) 6x9x0.8
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 16...70 1) 6x13x0.5
Plug gauge according to 60 947-7-1	Size B 11
Continuous current of terminal for conductor size	192 A/70 mm ²
Continuous current rating of cross-connection 2...5-pole	A 180
Continuous current rating of cross-connection 6...10-pole	A 180

Rated data according to UL/CSA	
Voltage/current/conductor size	600 V/145 A/4...2/0 AWG
Voltage/current/conductor size	600 V/150 A/4...2/0 AWG

Ordering data	Version	Qty.	Qty.
	KrG	0340820000	10
	Hexagon socket KrG	0340870000	10
	KrS	0340830000	10
	Hexagon socket KrS		
	PA		
	Hexagon socket PA	0139160000	10
	Blue PA		

SAK 95 SAK 95/35



UL CE DNV

Width/length/height (mm)	28/83.5/100.5
Width/length/height (mm)	28/83.5/96.5
Insulation stripping length/clamping screw/screwdriver blade	30 mm/M 10/S 8 D6911

Rated data according to IEC 60 947-7-1	
Rated voltage/current/cross-section	1000 V/232 A/95 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data	
Tightening torque range	Nm 10.0...20.0
Torque setting with electric screwdriver type DMS 2	

Clampable conductor	
Solid H07V-U	mm ² 10...16
Stranded H07V-R	mm ² 10...120 2) 3x9x0.8
Flexible H07V-K	mm ² 10...95 2) 6x9x0.8
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 10...95 2) 6x13x0.5
Plug gauge according to 60 947-7-1	Size B 12
Continuous current of terminal for conductor size	232 A/95 mm ²
Continuous current rating of cross-connection 2...5-pole	A 180
Continuous current rating of cross-connection 6...10-pole	A 180

Rated data according to UL/CSA	
Voltage/current/conductor size	600 V/190 A/6...3/0 AWG
Voltage/current/conductor size	600 V/260 A/6...3/0 AWG

Ordering data	Version	Qty.	Qty.
	KrG	0550520000	10 0662220000
	Hexagon socket KrG		
	KrS		
	Hexagon socket KrS		
	PA		
	Hexagon socket PA		
	Blue PA		

Dimensions/approvals

Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Rated data according to IEC 60 947-7-1	
Rated voltage/current/cross-section	
Rated impulse voltage/pollution severity	

Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

Clampable conductor	
Solid H07V-U	mm ²
Stranded H07V-R	mm ²
Flexible H07V-K	mm ²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
Plug gauge according to 60 947-7-1	Size
Continuous current of terminal for conductor size	
Continuous current rating of cross-connection 2...5-pole	A
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL
Voltage/current/conductor size	CSA

Ordering data	Version	Qty.	Qty.
	KrG	0550620000	20 0608220000
	Hexagon socket KrG	0555720000	20 0608320000
	Hexagon socket Blue KrG		0608370000
	KrS	0550630000	20
	Hexagon socket KrS	0555730000	20
	PA	0550660000	20 0608260000
	Hexagon socket PA	0555760000	20 0608360000
	Blue PA		

End plate (thickness mm)



Type	Cat. No.	Qty.
KrG	AP (3.0) 0303620000	10
Blue KrG	AP (3.0) 0303670000	10
KrS	AP (3.0) 0303630000	10
PA	AP (1.5) 0303660000	10
Blue PA	AP (3.0) 0303680000	10
Orange PA		

Type	Cat. No.	Qty.
KrG	AP (3.0) 0303620000	10
Blue KrG	AP (3.0) 0303670000	10
KrS	AP (3.0) 0303630000	10
PA	AP (1.5) 0303660000	10
Blue PA	AP (3.0) 0303680000	10

Type	Cat. No.	Qty.
KrG	AP (4.0) 0340920000	10
Blue KrG	AP (4.0) 0340930000	10
KrS	AP (2.0) 0340960000	10

Type	Cat. No.	Qty.
KrG	AP (3.0) 0550920000	10
Blue KrG	AP (3.0) 0550970000	10

Partition (thickness mm)



Type	Cat. No.	Qty.
KrG	TW (3.0) 0304320000	10
Blue KrG	TW (3.0) 0304330000	10
KrS	TW (3.0) 0304330000	10
PA	TW (1.5) 0304360000	10
Blue PA	TW (1.5) 0304360000	10

Type	Cat. No.	Qty.
KrG	TW (3.0) 0304320000	10
Blue KrG	TW (3.0) 0304330000	10
KrS	TW (3.0) 0304330000	10
PA	TW (1.5) 0304360000	10
Blue PA	TW (1.5) 0304360000	10

Cross-connection




QL 3	VH	BS	SS	2-pole	QL 2	0564900000	50
				3-pole	QL 3	0565000000	50
				4-pole	QL 4	0565100000	50
				10-pole	QL 10	0565200000	20
					VH 17	0267000000	50
					BS M 4x30	0267100000	50
					SS M 4	0136400000	100

QL 2				2-pole	QL 2	0123600000	20
QL 3				3-pole	QL 3	0123700000	20
QL 4				4-pole	QL 4	0123800000	20
QL 10				10-pole	QL 10	0338600000	20
VH 17					VH 17	0267000000	50
BS M 4x30					BS M 4x30	0267100000	50
SS M 4					SS M 4	0136400000	100

QL 2				2-pole	QL 2	0345300000	20
QL 3				3-pole	QL 3	0167000000	20
VH 30.5					VH 30.5	0345500000	20
BS M 5x45					BS M 5x45	0345600000	20
SS M 5					SS M 5	0346100000	100

QL 2				2-pole	QL 2	0551200000	10
QL 3				3-pole	QL 3	0407600000	10
QL 4				4-pole	QL 4	0407700000	10
VH 35					VH 35	0551100000	10
BS M 5x50					BS M 5x50	0630200000	20

Switchable cross-connection link



VL 2	BS	VH	

VL 2			
VH 24.5			
BS M 4x35			

VL 2			
VH 24.5			
BS M 4x35			

VL 2			
VH 24.5			
BS M 4x35			

Cover / test plug



AD 4	0576700000	50
BSKM 4x32	0129100000	50
PS 4	0299600000	20

AD 4	0178700000	20
BSKM 4x32	0129100000	50
PS 4	0299600000	20

AD 3	0344300000	10
BSKM 5x45	0344400000	50
PS 4	02	

Feed-through terminals

Terminals/Accessories

SAKG 28 I


SAKG 28 II




The Weidmüller SAKG range offers the following connection variants:

- clamping yoke/flat lug as a combination, Version I.
- flat lug, Version II.
Two types of threading are provided here.
a) screw set with lock nut
b) with thread in busbar
- clamping yoke connection, Version III.
The stripped conductor can be connected without further preparation.

Versions




Version I



Version II
without thread



Version II G
with thread




Version III

Cables with cable lugs are connected to SAKG terminals of Version I and to SS stud terminals.

Fitting instructions for SAKG terminals

When tightening the clamping screw, it is recommended that the conductor be held against the direction of tightening to prevent deformation of the mounting rail and so as not to place the terminal foot under undue torsional forces.



Cover

To ensure shock protection following connections of **conductors**, AH covers can be clipped onto the terminal.

Dimensions/approvals

Width/length/height (mm)	with TS 32	
Width/length/height (mm)	with TS 35	
Insulation stripping length/clamping screw/screwdriver blade		

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	1000 V*/125 A/35 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data

Tightening torque range	Nm	3...6
Torque setting with electric screwdriver type DMS 2		

Clampable conductor

Solid H07V-U	mm ²	6...35
Stranded H07V-R	mm ²	6...35
Flexible H07V-K	mm ²	10...35
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	6...35
Plug gauge according to 60 947-7-1	Size	B 9
Continuous current of terminal for conductor size		125 A/35 mm ²
Continuous current rating of cross-connection 2...5-pole	A	(QL 2) 125
Continuous current rating of cross-connection 6...10-pole	A	(QL 2) 125

Rated data according to UL/CSA

Voltage/current/conductor size	UL	600 V/95 A/2 AWG
Voltage/current/conductor size	CSA	600 V/110 A/6...1 AWG

Ordering data

Type		Cat. No.	Qty.
KrG		0170020000	10

UL @ CE @

28/70/63.5

15 mm/M 6/-

1000 V*/125 A/35 mm²

8 kV/3

3...6

6...35

6...35

10...35

6...35

B 9

125 A/35 mm²

(QL 2) 125

600 V/95 A/2 AWG

600 V/110 A/6...1 AWG

Cat. No. Qty.

0170020000 10

UL @ CE @ DNV

28/70/53

-/M 6/-

1000 V*/125 A/35 mm²

8 kV/3

3...6

125 A/35 mm²

(QL 2) 125

600 V/115 A/2 AWG

600 V/110 A/6...1 AWG

Cat. No. Qty.

0170320000 10

End plate, hard paper

	Cat. No.	Qty.
	EP 1 (2)	0205100000 10
	EP 1 (2)	0205200000 10



0180700000, 0205300000

0180800000, 0205400000 tropic-proof



Partition, hard paper (thickness in mm)

	Cat. No.	Qty.
	TW 1 (2)	0151400000 10
	TW 1 (2)	0164600000 10



0177100000 B/L/H (incl. TS 32) mm

0179900000 B/L/H (incl. TS 35) mm



Cross-connection

	2-pole	QL 2	0193900000 5
	3-pole	QL 3	0407600000 5
	4-pole	QL 4	0407700000 5



Cover

	AH 28	0326660000 5
--	-------	---------------------



Marking tags

	1	2	3	4	5	6	DEK	Standard
--	---	---	---	---	---	---	-----	----------

DEK 5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

During conductor connection, observe clearance and creepage distances. Insert partitions if necessary.

Feed-through terminals

SAKG 28 II G



28/70/53
-/M 6/-
1000 V*/125 A/35 mm ²
8 kV/3
3...6
125 A/35 mm ²
(QL 2) 125

	Cat. No.	Qty.
	0185020000	10

	Cat. No.	Qty.
	0205100000	10
	0205200000	10

	Cat. No.	Qty.

	Qty.
	0151400000 10
	0164600000 10

2/120/75.5

QL 2	0193900000	5
QL 3	0407600000	5
QL 4	0407700000	5

AH 28	0326660000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 28 III



28/70/63.5
15 mm/M 6/-
1000 V*/125 A/35 mm ²
8 kV/3
3...6
B 9

600 V/95 A/2 AWG	600 V/135 A/8...2 AWG	
	Cat. No.	Qty.
	0170820000	10

	Cat. No.	Qty.
	0205100000	10
	0205200000	10

	Cat. No.	Qty.

	Qty.
	0151400000 10
	0164600000 10

2/120/75.5

AH 28	0326660000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 32 I SAKG 32/35 I



32/87/84
32/87/84.5
26 mm/M 8/-
1000 V*/150 A/50 mm ²
8 kV/3
6...12
10...70
10...70
10...70
10...35
B 11
150 A/50 mm ²
(QL 2) 150

600 V/165 A/3 AWG	600 V/170 A/1...2/0 AWG		
	Qty.		Qty.
	0286620000		0637120000

	Cat. No.	Qty.
	0205300000	10
	0205400000	10

	Cat. No.	Qty.
	0180700000	10
	0180800000	10

	Qty.
	0177100000 10
	0179900000 10

2/160/90.5
2/160/90.5

QL 2	0194000000	5
QL 3	0441500000	5
QL 4	0441600000	5

AH 32	0326760000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 32 II SAKG 32/35 II



32/80/53
32/80/51
-/M 8/-
1000 V*/150 A/50 mm ²
8 kV/3
6...12
150 A/50 mm ²
(QL 2) 150

600 V/200 A/3 AWG	600 V/170 A/1...2/0 AWG		
	Qty.		Qty.
	0170420000		0637320000

	Cat. No.	Qty.
	0205100000	10
	0205200000	10

	Cat. No.	Qty.
	0180700000	10
	0180600000	10

	Qty.
	0151400000 10
	0164600000 10

2/120**/75.5
2/120**/75.5

QL 2	0194000000	5
QL 3	0441500000	5
QL 4	0441600000	5

AH 32	0326760000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 32 II G SAKG 32/35 II G



32/80/53
32/80/53
-/M 8/-
1000 V*/150 A/50 mm ²
8 kV/3
6...12
150 A/50 mm ²
(QL 2) 150

600 V/170 A/1...2/0 AWG			
	Qty.		Qty.
	0185120000		0637420000

	Cat. No.	Qty.
	0205100000	10
	0205200000	10

	Cat. No.	Qty.
	0180700000	10
	0180600000	10

	Qty.
	0151400000 10
	0164600000 10


2/120**/75.5
2/120**/75.5

QL 2	0194000000	5
QL 3	0441500000	5
QL 4	0441600000	5

AH 32	0326760000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 32 III SAKG 32/35 III



32/94/84
32/94/84.5
26 mm/M 8/-
1000 V*/150 A/50 mm ²
8 kV/3
6...12
10...70
10...70
10...70
10...35
B 11
150 A/50 mm ²

600 V/165 A/3 AWG	600 V/185 A/1...2/0 AWG		
	Qty.		Qty.
	0286720000		0637220000

	Cat. No.	Qty.
	0205300000	10
	0205400000	10

	Cat. No.	Qty.
	0180700000	10
	0180800000	10

	Qty.
	0177100000 10
	0179900000 10

2/160/90.5
2/160/90.5

QL 2	0194000000	5
QL 3	0441500000	5
QL 4	0441600000	5

AH 32	0326760000	5
-------	-------------------	---

DEK 5	see "Accessories"
-------	-------------------

* During conductor connection, observe clearance and creepage distances. Insert partitions if necessary
 ** For Cat. No. **0180600000** and **0180700000**: length = 160 mm.

Feed-through terminals

SAKG 70 II G SAKG 70/35 II G



Ⓢ Ⓡ Ⓜ DNV

Width/length/height (mm)	with TS 32	32/84/54
Width/length/height (mm)	with TS 35 x 7.5	32/84/53
Insulation stripping length/clamping screw/screwdriver blade		-/M 8/-

Dimensions/approvals

Width/length/height (mm)	with TS 32	32/84/54
Width/length/height (mm)	with TS 35 x 7.5	32/84/53
Insulation stripping length/clamping screw/screwdriver blade		-/M 8/-

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	1000 V*/192 A/70 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Further technical data

Tightening torque range	Nm	6...12
Torque setting with electric screwdriver type DMS 2		

Clampable conductor

Solid H07V-U	mm ²	
Stranded H07V-R	mm ²	10...95
Flexible H07V-K	mm ²	10...95
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	10...35
Plug gauge according to 60 947-7-1	Size	B 12
Continuous current of terminal for conductor size		192 A/90 mm ²
Continuous current rating of cross-connection 2...5-pole	A	(QL 2) 192
Continuous current rating of cross-connection 6...10-pole	A	


Rated data according to UL/CSA

Voltage/current/conductor size	UL	
Voltage/current/conductor size	CSA	600 V/200 A/2/0...4/0 AWG

Ordering data

Version	KrG	Qty.	Qty.	0150420000 10	0636620000 10
---------	-----	------	------	---------------	---------------

SAKG 40 I SAKG 40/35 I



Ⓢ Ⓡ Ⓜ Ⓢ

Width/length/height (mm)	40/95/84
Width/length/height (mm)	46/95/85.5
Insulation stripping length/clamping screw/screwdriver blade	27 mm/M 10/-

SAKG 40 II SAKG 40/35 II



Ⓢ Ⓡ Ⓜ Ⓢ DNV

Width/length/height (mm)	40/90/53
Width/length/height (mm)	46/90/53
Insulation stripping length/clamping screw/screwdriver blade	-/M 10/-

SAKG 40 II G SAKG 40/35 II G



Ⓢ Ⓡ Ⓜ

Width/length/height (mm)	40/90/55
Width/length/height (mm)	46/90/55
Insulation stripping length/clamping screw/screwdriver blade	-/M 10/-

Rated voltage/current/cross-section	1000 V*/232 A/95 mm ²
Rated impulse voltage/pollution severity	8 kV/3

Tightening torque range	Nm	10...20
Torque setting with electric screwdriver type DMS 2		

Solid H07V-U	mm ²	
Stranded H07V-R	mm ²	10...95
Flexible H07V-K	mm ²	10...95
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	10...35
Plug gauge according to 60 947-7-1	Size	B 12
Continuous current of terminal for conductor size		232 A/95 mm ²
Continuous current rating of cross-connection 2...5-pole	A	(QL 2) 232
Continuous current rating of cross-connection 6...10-pole	A	

Voltage/current/conductor size	UL	600 V/195 A/4/0 AWG
Voltage/current/conductor size	CSA	600 V/250 A/2/0...4/0 AWG

Version	KrG	Qty.	Qty.	0170520000 10	0637720000 5
---------	-----	------	------	---------------	--------------

End plate, hard paper (thickness mm)

0205100000, 0180500000		
0205200000, 0180600000	tropic-proof	

EP 1 (2)	Cat. No.	Qty.	0205100000 10
EP 1 (2)	Cat. No.	Qty.	0205200000 10

EP 2 (2)	Cat. No.	Qty.	0205300000 10
EP 2 (2)	Cat. No.	Qty.	0205400000 10

EP 2 (2)	Cat. No.	Qty.	0205300000 10
EP 2 (2)	Cat. No.	Qty.	0205400000 10

EP 2 (2)	Cat. No.	Qty.	0205300000 10
EP 2 (2)	Cat. No.	Qty.	0205400000 10

0180700000, 0205300000		
0180800000, 0205400000	tropic-proof	

EP 1/35 (2)	Cat. No.	Qty.	0180500000 10
EP 1/35 (2)	Cat. No.	Qty.	0180600000 10

EP 2/35 (2)	Cat. No.	Qty.	0180700000 10
EP 2/35 (2)	Cat. No.	Qty.	0180800000 10

EP 2/35 (2)	Cat. No.	Qty.	0180700000 10
EP 2/35 (2)	Cat. No.	Qty.	0180800000 10

EP 2/35 (2)	Cat. No.	Qty.	0180700000 10
EP 2/35 (2)	Cat. No.	Qty.	0180800000 10

Partition, hard paper (thickness mm)

0151400000		
0164600000	tropic-proof	

TW 1 (2)	Cat. No.	Qty.	0151400000 10
TW 1 (2)	Cat. No.	Qty.	0164600000 10

TW 2 (2)	Cat. No.	Qty.	0177100000 10
TW 2 (2)	Cat. No.	Qty.	0179900000 10

TW 2 (2)	Cat. No.	Qty.	0177100000 10
TW 2 (2)	Cat. No.	Qty.	0179900000 10

TW 2 (2)	Cat. No.	Qty.	0177100000 10
TW 2 (2)	Cat. No.	Qty.	0179900000 10

0177100000	B/L/H (incl. TS 32) mm	2/120/75.5
0179900000	B/L/H (incl. TS 35) mm	2/120/75.5

2/160/90.5		2/160/90.5
2/160/90.5		2/160/90.5

2/160/90.5		2/160/90.5
2/160/90.5		2/160/90.5

2/160/90.5		2/160/90.5
2/160/90.5		2/160/90.5

Cross-connection

2-pole, QL 2	Qty.	0194000000 10
3-pole, QL 3	Qty.	0441500000 10
4-pole, QL 4	Qty.	0441600000 10

Qty.	Qty.	0194100000 10
Qty.	Qty.	0263500000 10
Qty.	Qty.	0409800000 10

Qty.	Qty.	0194100000 10
Qty.	Qty.	0263500000 10
Qty.	Qty.	0409800000 10

Qty.	Qty.	0194100000 10
Qty.	Qty.	0263500000 10
Qty.	Qty.	0409800000 10

Cover

AH 32	Qty.	0326760000 5
-------	------	--------------

AH 40	Qty.	0326860000 5
-------	------	--------------

AH 40	Qty.	0326860000 5
-------	------	--------------

AH 40	Qty.	0326860000 5
-------	------	--------------

Marking tags

1 2 3 4 5 6	DEK	Standard	DEK 5	see "Accessories"
-------------	-----	----------	-------	-------------------

DEK 5	see "Accessories"
-------	-------------------

DEK 5	see "Accessories"
-------	-------------------

DEK 5	see "Accessories"
-------	-------------------

Mounting rails, end brackets, further marking material see "Accessories"

*During conductor connection, observe clearance and creepage distances. Insert partitions if necessary.

Feed-through terminals

SAKG 40 III SAKG 40/35 III



UL @ 3 4
40/100/84
46/100/85.5
27 mm/M 10/-
1000 V*/232 A/95 mm ²
8 kV/3
10...20
10...95
10...95
10...95
10...35
B 12
232 A/95 mm ²

600 V/195 A/4/0 AWG
600 V/230 A/2/0...4/0 AWG
Qty. Qty.
0286920000 10 0637620000 5

EP 2 (2)	Cat. No.	Qty.
EP 2 (2)	0205300000	10
EP 2 (2)	0205400000	10

EP 2/35 (2)	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10

TW 2 (2)	Qty.
TW 2 (2)	0177100000 10
TW 2 (2)	0179900000 10

2/160/90.5
2/160/90.5

QL 2	0247000000	5
QL 3	0444400000	5
QL 4	0444500000	5

AH 40	0326860000	5
-------	------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 46 II SAKG 46/35 II



UL @ 3 4
46/106/55
46/106/54.5
-/M 12/-
1000 V*/309 A/150 mm ²
8 kV/3
14...31
309 A/150 mm ²

600 V/285 A/4/0 AWG
600 V/365 A/300 MCM
Qty. Qty.
0170620000 10 0637920000 5

EP 2 (2)	Cat. No.	Qty.
EP 2 (2)	0205300000	10
EP 2 (2)	0205400000	10

EP 2/35 (2)	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10

TW 2 (2)	Qty.
TW 2 (2)	0177100000 10
TW 2 (2)	0179900000 10

2/160/90.5
2/160/90.5

QL 2	0247000000	5
QL 3	0444400000	5
QL 4	0444500000	5

AH 46	0326960000	5
-------	------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 46 II G SAKG 46/35 II G



@ 3 4 DNV
46/106/57.5
46/106/57
-/M 12/-
1000 V*/309 A/150 mm ²
8 kV/3
14...31
309 A/150 mm ² (QL 2) 309

600 V/285 A/4/0 AWG
600 V/365 A/300 MCM
Qty. Qty.
0185320000 10 0638020000 5

EP 2 (2)	Cat. No.	Qty.
EP 2 (2)	0205300000	10
EP 2 (2)	0205400000	10

EP 2/35 (2)	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10

TW 2 (2)	Qty.
TW 2 (2)	0177100000 10
TW 2 (2)	0179900000 10


2/160/90.5
2/160/90.5

QL 2	0247000000	5
QL 3	0444400000	5
QL 4	0444500000	5

AH 46	0326960000	5
-------	------------	---

DEK 5	see "Accessories"
-------	-------------------

SAKG 54 II SAKG 54/35 II



UL @ 3 4
54/122/57
54/122/57
-/M 16/-
1000 V*/415 A/240 mm ²
8 kV/3
25...60
415 A/240 mm ² (QL 2) 415

600 V/380 A/500 MCM
600 V/600 A/300...500 MCM
Qty. Qty.
0170720000 10 0638120000 5

EP 2 (2)	Cat. No.	Qty.
EP 2 (2)	0205300000	10
EP 2 (2)	0205400000	10

EP 2/35 (2)	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10


TW 2 (2)	Qty.
TW 2 (2)	0177100000 10
TW 2 (2)	0179900000 10

2/160/90.5
2/160/90.5

QL 2	0264400000	5
QL 3	0408000000	5
QL 4	0247400000	5

DEK 5	see "Accessories"
-------	-------------------

SAKG 54 II G SAKG 54/35 II G



UL @ 3 4 DNV
54/122/60
54/122/60
-/M 16/-
1000 V*/415 A/240 mm ²
8 kV/3
25...60
415 A/240 mm ² (QL 2) 415

600 V/380 A/500 MCM
600 V/600 A/300...500 MCM
Qty. Qty.
0185420000 10 0638220000 5

EP 2 (2)	Cat. No.	Qty.
EP 2 (2)	0205300000	10
EP 2 (2)	0205400000	10

EP 2/35 (2)	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10


TW 2 (2)	Qty.
TW 2 (2)	0177100000 10
TW 2 (2)	0179900000 10

2/160/90.5
2/160/90.5

QL 2	0264400000	5
QL 3	0408000000	5
QL 4	0247400000	5

DEK 5	see "Accessories"
-------	-------------------

SAKG 46/I AL SAKG 46/II AL



46/112/74
23 mm/M 12/M 14/-
1000 V*/309 A/150 mm ²
8 kV/3
14...31/25...40
50...240
35...185

Qty. Qty.
1287920000** 5

EP 2 (2)	Cat. No.	Qty.
EP 2 (2)	0205300000	10
EP 2 (2)	0205400000	10

EP 2/35 (2)	Cat. No.	Qty.
EP 2/35 (2)	0180700000	10
EP 2/35 (2)	0180800000	10

TW 2 (2)	Qty.
TW 2 (2)	0177100000 10
TW 2 (2)	0179900000 10

2/160/90.5
2/160/90.5

QL 2	0194000000	5
QL 3	0441500000	5
QL 4	0441600000	5

AH 46	0326960000	5
-------	------------	---

DEK 5	see "Accessories"
-------	-------------------

SAK-series

* During conductor connection, observe clearance and creepage distances. Insert partitions if necessary.
** Suitable for connection of 1 aluminium conductor of max 185 mm²

*** Suitable for connection of 2 aluminium conductors of max. 185 mm²

Stud terminals


SS 6 SS 6/35




KST 5 KST 5/35



KST 6 KST 6/35



KST 8 KST 8/35



Dimensions/approvals

Width/length/height (mm)	with TS 32	
Width/length/height (mm)	with TS 35 x 7.5	
Insulation stripping length/clamping screw/screwdriver blade		

Rated data

Rated voltage/current/cross-section		
Rated impulse voltage/pollution severity		

Further technical data

Tightening torque range	Nm	
Torque setting with electric screwdriver type DMS 2		

Clampable conductor

Solid H07V-U	mm ²	
Stranded H07V-R	mm ²	
Flexible H07V-K	mm ²	
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	
Plug gauge according to 60 947-7-1	Size	
Continuous current of terminal for conductor size		
Continuous current rating of cross-connection 2...5-pole	A	
Continuous current rating of cross-connection 6...10-pole	A	

Rated data according to UL/CSA

Voltage/current/conductor size	UL	
Voltage/current/conductor size	CSA	

Ordering data

Version		Qty.	
KrG			
PA			
PPO			
KrG			
for TS 35 x 7.5	PA		
for TS 35 x 15/2.3	PA		

18/40/62		
18/49.5/54.5		
-/M 6/-		

24/60/55		
24/62.5/49.5		
-/M 5/-		

24/60/62		
24/62.5/54.5		
-/M 6/-		

24/60/72		
24/62.5/64.5		
-/M 8/-		

1000 V ¹⁾ /76 A/16 mm ²		
6 kV/3		

1000 V ¹⁾ /57 A/10 mm ²		
8 kV/3		

1000 V ¹⁾ /76 A/16 mm ²		
8 kV/3		

1000 V ¹⁾ /125 A/35 mm ²		
8 kV/3		

3...6		

2...4		

3...6		

6...12		

82 A/16 mm ²		
-------------------------	--	--

65 A/10 mm ²		
-------------------------	--	--

82 A/16 mm ²		
-------------------------	--	--

135 A/35 mm ²		
--------------------------	--	--

--	--	--

--	--	--

200		
-----	--	--

200		
-----	--	--

Partition, (thickness mm)

PA		
Hard paper		
HM		
HM		

Width/length/height (incl. TS 32) mm	2/129/93
Width/length/height (incl. TS 35) mm	2/70/62.5

Cross-connection

2-pole	QL 2	028430000	20
3-pole	QL 3	027900000	20



Marking tags

1	2	3	4	5	6	DEK	Standard
---	---	---	---	---	---	-----	----------

Mounting rails, end brackets, further marking material see "Accessories"

Cat. No.	Qty.
TW SS6 (TS32)	0455860000 10

TW-GW2 (TS35)	0607100000 20
---------------	---------------

TW right	1718530000 10
TW left 2)	1752800000 10

TW right	1718530000 10
TW left	1752800000 10

TW right	1718530000 10
TW left	1752800000 10

QL 2	9503390000 1
QL 2	9501350000 5

TW right	1718530000 10
TW left	1752800000 10

QL 2	9501360000 1
------	--------------

DEK 5	see "Accessories"
-------	-------------------

DEK 5	see "Accessories"
-------	-------------------

DEK 5	see "Accessories"
-------	-------------------

DEK 5	see "Accessories"
-------	-------------------

* Depends on cable lug

1) with partition

2) Left AP is required only once at beginning of terminal strip

PE terminals

EK 2.5 N EK 2.5/35



EK 4 EK 4/35



EK 6/35



EK 10 EK 10/35



Dimensions/approvals													
Width/length/height (mm)	with TS 32	6/36.5/49.5	8/40/51.5	8/56/44	10/40/51.5								
Width/length/height (mm)	with TS 35 x 7.5	6/56/40	6.5/56/44	12 mm/M 3.5/4.0/0.8	10/56/44								
Insulation stripping length/clamping screw/screwdriver blade		10 mm/M 2.5/3.5 x 0.6	12 mm/M 3/3.5 x 0.6		12 mm/M 4/5.5 x 1.0								
Rated data according to IEC 60 947-7-2													
Rated voltage/current with PEN/cross-section		-/-/2.5 mm ²	-/-/4 mm ²	-/-/6 mm ²	-/-/10 mm ²								
Rated voltage/rated impulse voltage acc. to VDE 0110/1.89/ pollution severity													
Further technical data													
Tightening torque range	Nm	0.4...0.8/0.5...1.0*	0.5...1.0/0.5...1.0*	1.2...1.6/0.5...1.0*	1.2...2.4/0.5...1.0*								
Clampable conductor													
Solid H07V-U	mm ²	0.5...4	0.5...6	0.5...10	0.5...10								
Stranded H07V-R	mm ²	0.5...2.5	0.5...4	1.5...6	1.5...6								
Flexible H07V-K	mm ²	0.5...4	0.5...4	0.5...10	0.5...10								
Flexible H07V-K and ferrule DIN 46 228/1	mm ²	0.5...2.5	0.5...4	0.5...6	0.5...10								
Cable AWG	Nr.	22...14	22...10	20...8	20...8								
Plug gauge according to 60 947-7-1	Size	A 3	A 4	A 5	B 6								
Ordering data		Version	Qty.	Qty.	Qty.	Qty.							
		Green/yellow PA	0474360000 100	0661060000 100	0661260000 100	0354660000 80 0661360000 100							
		Blank											
		Two clamping yokes blank											
		Hexagon socket blank											
Support block		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
		SH 2	0494920000	10	SH 2	0494920000	10	SH 2	0494920000	10	SH 2	0494920000	10
For insulation of mounting rails in insulated-earth installations													
SK - key, 8mm													
Marking tags		Print											
		DEK	Standard	DEK 6	see "Accessories"	DEK 6.5	see "Accessories"	DEK 8	see "Accessories"	DEK 5	see "Accessories"		
Mounting rails, end brackets, further marking material see "Accessories"													

* For centre screw

PE terminals

EK 16
EK 16/35



12/50/57.5	16 mm/M 4/5.5 x 1.0
12/56/50	-/-/16 mm ²
1.2...2.4/0.8...1.0*	2.5...16
2.5...16	2.5...16
2.5...16	2.5...16
4...16	4...16
12...6	12...6
B 6	B 6
Qty.	Qty.
0374660000 50	0190160000 50

Type	Cat. No.	Qty.
SH 2	0494920000	10

DEK 5 see "Accessories"

EK 35**
EK 35/35



18/58/67.5	20 mm/M 6/6.5 x 1.2
16/58/60	-/-/35 mm ²
2.5...5.0/ **	6...16
16...50	16...50
10...35	10...35
10...35	10...35
10...2	10...2
B 9	B 9
Qty.	Qty.
0354760000 20	0661460000 20

Type	Cat. No.	Qty.
SH 2	0494920000	10

DEK 5 see "Accessories"

EK 2



10/52/38	14 mm/M 4/-
-/-/10	-/-/10
1.2...2.4/2.0...4.0*	1.5...10
1.5...10	1.5...10
1.5...10	1.5...10
1.5...10	1.5...10
16...8	16...8
B 6	B 6
Qty.	Qty.
0323100000	20

Type	Cat. No.	Qty.
SH 2	0494920000	10


SAKE 35



14/46/39	16 mm/M 6/-
-/-/35 mm ²	-/-/35 mm ²
2.5...5.0/2.0...4.0*	6...35
6...35	6...35
6...16	6...16
10...35	10...35
8...2	8...2
B 8	B 8
Qty.	Qty.
0144400000	20

Type	Cat. No.	Qty.
SH 2	0494920000	10

SAKE 70



18/94/59.5	25 mm/M 8/-
-/-/70 mm ²	-/-/70 mm ²
6.0...12/2.0...4.0*	10...70
10...70	10...70
10...70	10...70
10...70	10...70
6...0	6...0
B 10	B 10
Qty.	Qty.
0213200000	20
1338300000	10

Type	Cat. No.	Qty.
SH 2	0494920000	10

EK 95/35



25/76/100/92	27 mm/M 10/-
25/76/100/92	-/-/95 mm ²
10.0...20.0/1.2...2.4*	10...120
10...95	10...95
10...95	10...95
10...95	10...95
6...4/0	6...4/0
B 12	B 12
Qty.	Qty.
0535300000	10
0535400000	10

Type	Cat. No.	Qty.
SH 2	0494920000	10


0235000000

SAK-series

** ADm f. EK 35/35 = 1.2 - 2.4 Nm
ADm f. EK 35 = 0.8 - 1.6 Nm


Fuse terminals

ASK 1¹⁾ ASK 1/35¹⁾



Width/length/height (mm)	with TS 32	8/58/45,5
Width/length/height (mm)	with TS 35 x 7.5	8/58/44
Insulation stripping length/clamping screw/screwdriver blade		9 mm/M 3/3.5 x 0.6
Rated data/feed through-terminal base		
Rated voltage/current/cross-section		500 V/6.3 A ²⁾ /4 mm ²
Rated impulse voltage/pollution severity		6 kV/3
Further technical data		
Tightening torque range	Nm	0.5...1.0
Torque setting with electric screwdriver type DMS 2		2
Clampable conductor		
Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 3
Continuous current rating of cross-connection 2...5-pole	A	(QB 2...4) 10
Continuous current rating of cross-connection 6...10-pole	A	

KDKS 1¹⁾ KDKS 1/35¹⁾




Width/length/height (mm)	8/73.5/59,8	
Width/length/height (mm)	8/73.5/55,7	
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6	
Rated data/feed through-terminal base		
Rated voltage/current/cross-section	500 V/6.3 A/4 mm ²	
Rated impulse voltage/pollution severity	6 kV/3	
Further technical data		
Tightening torque range	Nm	0.5...1.0
Torque setting with electric screwdriver type DMS 2		2
Clampable conductor		
Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 4
Continuous current rating of cross-connection 2...5-pole	A	(QB 2...4) 10
Continuous current rating of cross-connection 6...10-pole	A	

SAKS 1 SAKS 1/35



Width/length/height (mm)	13/54/61	
Width/length/height (mm)	13/54/54	
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 4/5.5 x 1.0	
Rated data/feed through-terminal base		
Rated voltage/current/cross-section	500 V/6.3 A ³⁾ /10 mm ²	
Rated impulse voltage/pollution severity	6 kV/3	
Further technical data		
Tightening torque range	Nm	1.2...2.4
Torque setting with electric screwdriver type DMS 2		4
Clampable conductor		
Solid H07V-U	mm ²	0.5...16
Stranded H07V-R	mm ²	1.5...10
Flexible H07V-K	mm ²	0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...10
Plug gauge according to 60 947-7-1	Size	B 6
Continuous current rating of cross-connection 2...5-pole	A	(QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A	(QL 6...10) 36

SAKS 1/G25 SAKS 1/35/G25



Width/length/height (mm)	13/54/61	
Width/length/height (mm)	13/54/54	
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 4/5.5 x 1.0	
Rated data/feed through-terminal base		
Rated voltage/current/cross-section	500 V/6.3 A ³⁾ /10 mm ²	
Rated impulse voltage/pollution severity	6 kV/3	
Further technical data		
Tightening torque range	Nm	1.2...2.4
Torque setting with electric screwdriver type DMS 2		4
Clampable conductor		
Solid H07V-U	mm ²	0.5...16
Stranded H07V-R	mm ²	1.5...10
Flexible H07V-K	mm ²	0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...10
Plug gauge according to 60 947-7-1	Size	B 6
Continuous current rating of cross-connection 2...5-pole	A	(QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A	(QL 6...10) 36

Dimensions/approvals

Width/length/height (mm)	with TS 32	8/58/45,5
Width/length/height (mm)	with TS 35 x 7.5	8/58/44
Insulation stripping length/clamping screw/screwdriver blade		9 mm/M 3/3.5 x 0.6

Rated data/feed through-terminal base

Rated voltage/current/cross-section	500 V/6.3 A ²⁾ /4 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data

Tightening torque range	Nm	0.5...1.0
Torque setting with electric screwdriver type DMS 2		2

Clampable conductor

Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 3
Continuous current rating of cross-connection 2...5-pole	A	(QB 2...4) 10
Continuous current rating of cross-connection 6...10-pole	A	

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/6.3 A/12 max. AWG
Voltage/current/conductor size	CSA	300 V/6.3 A/26...12 AWG

Ordering data

Version	PA	Qty.	Qty.
	KrG	0474560000	100
	Beige Wemid		

End plate/partition (thickness mm)



Type	Cat. No.	Qty.
AP (1.5)	0380360000	20

Type	Cat. No.	Qty.
AP 1 KDKS	9503330000	25
Wemid	9532470000	25
for TW (2.0)		
	0607000000	20

Type	Cat. No.	Qty.
AP (2.5)	0191320000	20
Wemid beige	0191300000	20
for TW (2.0)		
	0607000000	20

Type	Cat. No.	Qty.
AP (2.5)	0191320000	20
Wemid-beige	0191300000	
for TW (2.0)		
	0607000000	20

G-fuse inserts

Acc. to IEC 60127-2 (VDE 0820 T.2 BI 1) rated current (A):	0.10 fast	0430300000	10
	0.20 fast	0430400000	10
	0.25 fast	0430500000	10
	0.50 fast	0430600000	10
	1.0 fast	0430700000	10
	1.6 fast	0430800000	10
	2.0 fast	0430900000	10
	2.5 fast	0431000000	10
	3.15 fast		
	4.0 fast		
	5.0 fast		
	6.3 fast		

5 x 20 mm	0430300000	10
5 x 20 mm	0430400000	10
5 x 20 mm	0430500000	10
5 x 20 mm	0430600000	10
5 x 20 mm	0430700000	10
5 x 20 mm	0430800000	10
5 x 20 mm	0430900000	10
5 x 20 mm	0431000000	10

5 x 20 mm	0430300000	10
5 x 20 mm	0430400000	10
5 x 20 mm	0430500000	10
5 x 20 mm	0430600000	10
5 x 20 mm	0430700000	10
5 x 20 mm	0430800000	10
5 x 20 mm	0430900000	10
5 x 20 mm	0431000000	10

5 x 25 mm	0.25 (m)	0546900000	10
	0.5 (m)	0510300000	10
	0.8 (m)	0646400000	10
	1 (m)	0265800000	10
	10 (m)	0193100000	10
	2 (f)	0192700000	10
	4 (f)	0192800000	10
	6.3 (f)	0192900000	10

Contact sleeve

0553300000	100
------------	-----

Contact sleeve

0553300000	100
------------	-----

Screw cap/disconnector lever (spare)

TH	0377060000	100
SIHA	1593020000	100

TH	0377060000	100
SIHA	1593020000	100

SK (5 x 20)	0282100000	20
-------------	------------	----

SK (5 x 25)	0282000000	20
-------------	------------	----

Marking tags

Red pull lever	Print	DEK	Standard	DEK 8	see "Accessories"
1	2	3	4	5	6

DEK 8	see "Accessories"
-------	-------------------

DEK 5	see "Accessories"
-------	-------------------


DEK 5	see "Accessories"
-------	-------------------

Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ Multipole interruptible with group marking carrier
Sch2 2-pole Cat. No. 1359500000, 1000 mm Cat. No. 0337400000

Fuse terminals

KSKM 1 KSKM 1/35



13/69/62
13/69/63
12 mm/-/-

250 V/6.3 A¹⁾/10 mm²

0.5...16

0.5...10

B 6

600 V/10 A/22...8 AWG

Qty. Qty.

9509570000 20 9509600000 20

Type	Cat. No.	Qty.
AP (3)	9509630000	20


5 x 20 mm

0.10 (f)	0430300000	10
0.20 (f)	0430400000	10
0.25 (f)	0430500000	10
0.50 (f)	0430600000	10
1.00 (f)	0430700000	10
1.60 (f)	0430800000	10
2.00 (f)	0430900000	10
2.50 (f)	0431000000	10
3.15 fast	0431100000	10
4.0 fast	0431200000	10
5.0 fast	0431300000	10
6.3 fast	0431400000	10

5 x 20 SBL 0446100000 40

DEK 5 see "Accessories"

KSKM 2 KSKM 2/35



13/69/62
13/69/63
12 mm/-/-

250 V/13 A²⁾/10 mm²

0.5...16

0.5...10

B 6

600 V/15 A/22...8 AWG

Qty. Qty.

9509580000 20 9509610000 20


Type	Cat. No.	Qty.
AP (3)	9509630000	20

1 x 1/4"

1 x 1/4" SBL 0446200000 40

DEK 5 see "Accessories"

KSKM 3 KSKM 3/35



13/69/62
13/69/63
12 mm/-/-

440 V/10 A/10 mm²

0.5...16

0.5...10

B 6

600 V/15 A/22...8 AWG

Qty. Qty.

9509620000 20

Type	Cat. No.	Qty.
AP (3)	9509630000	20

1 1/4 x 1/4"

E 2 A	0294500000	10
E 3 A	0295700000	10
E 5 A	0294600000	10
E 7 A	0295800000	10
E 10 A	0293900000	10


1 1/4 x 1/4" SBL 0446300000 40

DEK 5 see "Accessories"

1) Max. fuse rating according to DIN 41 660, IEC 127 CEE4 Type 1
2) Fuse according to BS 1362

Fuse terminals

SAKS 3 SAKS 3/35



Width/length/height (mm) with TS 32	13/54/61
Width/length/height (mm) with TS 35 x 7.5	13/54/55
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 4/5.5 x 1
Rated data/feed through-terminal base	
Rated voltage/current/cross-section	500 V/10 A/10 mm ²
Rated impulse voltage/pollution severity	6 kV/3
Further technical data	
Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4
Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 1.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

SAKS 4 SAKS 4/35



Width/length/height (mm)	24/75/73
Width/length/height (mm)	24/75/66
Insulation stripping length/clamping screw/screwdriver blade	14 mm/M 4/5.5 x 1
Rated data/feed through-terminal base	
Rated voltage/current/cross-section	400 V**/16 A/10 mm ²
Rated impulse voltage/pollution severity	6 kV/3
Further technical data	
Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4
Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 1.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

SAKS 5 SAKS 5/35



Width/length/height (mm)	28/80/80.5
Width/length/height (mm)	28/80/66
Insulation stripping length/clamping screw/screwdriver blade	13 mm/M 4/5.5 x 1
Rated data/feed through-terminal base	
Rated voltage/current/cross-section	400 V/63 A***/16 mm ²
Rated impulse voltage/pollution severity	6 kV/3
Further technical data	
Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4
Clampable conductor	
Solid H07V-U	mm ² 1.5...16
Stranded H07V-R	mm ² 1.5...16
Flexible H07V-K	mm ² 1.5...16
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 1.5...16
Plug gauge according to 60 947-7-1	Size B 7
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

SAKS 2 SAKS 2/35



Width/length/height (mm)	28/80/81.5
Width/length/height (mm)	28/80/75
Insulation stripping length/clamping screw/screwdriver blade	12 mm/M 4/5.5 x 1
Rated data/feed through-terminal base	
Rated voltage/current/cross-section	500 V/10 (25) A***/10 mm ²
Rated impulse voltage/pollution severity	6 kV/3
Further technical data	
Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4
Clampable conductor	
Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 0.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

Dimensions/approvals

Width/length/height (mm)	with TS 32	
Width/length/height (mm)	with TS 35 x 7.5	
Insulation stripping length/clamping screw/screwdriver blade		

Rated data/feed through-terminal base

Rated voltage/current/cross-section	500 V/10 A/10 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data

Tightening torque range	Nm 1.2...2.4
Torque setting with electric screwdriver type DMS 2	4

Clampable conductor

Solid H07V-U	mm ² 0.5...16
Stranded H07V-R	mm ² 1.5...10
Flexible H07V-K	mm ² 0.5...10
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ² 0.5...10
Plug gauge according to 60 947-7-1	Size B 6
Continuous current rating of cross-connection 2...5-pole	A (QL 2...5) 47
Continuous current rating of cross-connection 6...10-pole	A (QL 6...10) 36

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/10 A/22...10 AWG
Voltage/current/conductor size	CSA	600 V/10 A/22...10 AWG

Ordering data

Version		Qty.		Qty.
KrG	0248920000 ³⁾ 20	0667520000 ³⁾ 20		
KrG	0297520000 ⁴⁾ 20	0328920000 ⁴⁾ 20		

Neozed D 01

Type	Cat. No.	Qty.
AP (2.5)	0191320000	
HP for		
TW (2.0)	0607000000	

Neozed D 02

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000 ²⁾	20

Diazed E 16

Type	Cat. No.	Qty.
TW HP (2.0)	0607000000 ²⁾	20

End plate/partition (thickness mm)

PA	Type	Cat. No.	Qty.
HP	for		
	TW (2.0)	0607000000	

Cross-connection



Fixing screws for cross-connections

Fuse inserts

1 1/4" x 1/4"	Nominal current (A):	Fuse insert
	0.5 fast	E 0.5 A 0533800000
	1.0 fast	E 1 A 0525500000
	2.0 fast	E 2 A 0294500000
	3.0 fast	E 3 A 0295700000
	5.0 fast	E 5 A 0294600000
	7.0 fast	E 7 A 0295800000
	10.0 fast	E 10 A 0293900000

G fuse inserts 5 x 30 mm

(500 V~/0.032...6.3 A).

Available from Wickmann-Werke GmbH, Annastr. 113, 58453 Witten, Germany, Phone ++492302/6620

D fuse inserts

Rated voltage 400 V	
E 14/2	0137400000 10
E 14/4	0137500000 10
E 14/6	0328300000 10
E 14/10	0328400000 10
E 14/16	0328500000 10

Rated voltage 400 V	
E 18/20	0361300000 10
E 18/25	0361400000 10
E 18/35	0361500000 10
E 18/50	0361600000 10
E 18/63	0361700000 10

Rated voltage 500 V	
E 10 A	0208500000 25
E 16 A	0208600000 25
E 20 A	0208700000 25
E 25 A	0208800000 25

Screw cap (spare)

red	SK (5 x 30)	0282000000 20
black	SK (1/4"x1 1/4")	0428900000 20

SK 0339410000 20

SK 0359310000 20

SK 0284110000 20

Marking tags

	1	2	3	4	5	6	DEK	Standard
--	---	---	---	---	---	---	-----	----------

DEK 5 see "Accessories"

DEK 5 see "Accessories"

DEK 5 see "Accessories"

DEK 5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ only for TS 32

²⁾ Also for 440 V- with neozed marina fuse
³⁾ Current for overload up to 10 A, for short circuit up to 25 A

³⁾ For fuse inserts 1 1/4" x 1/4" DEF 63
⁴⁾ For fuse inserts 5 x 30

Fuse terminals

SAKS 4 USA



UL		
24/75/73		
24/75/66		
14 mm/M 4/5.5 x 1		
400 V/30 A/10 mm ²		
6 kV/3		
1.2...2.4		
4		
0.5...16		
1.5...10		
0.5...10		
0.5...10		
B 6		
(QL 2...5) 47		
(QL 6...10) 36		
600 V/30 A/20...8 AWG		
600 V/30 A/22...8 AWG		
	Qty.	Qty.
0162220000	20	0178220000
10.3 x 38,1		
Type	Cat. No.	Qty.
TW HP (2.0)	0607000000	20
QL 2	0328000000	20
QL 3	0328100000	20
QL 4	0328200000	20
QL 10	0339000000	20
SS M 4	0136400000	100
BS M 4 x 9	0103300000	100
SK (w. spring)	0161730000	20
DEK 5	see "Accessories"	


Fuse terminals with fault indicator



Dimensions/approvals	
Terminal width (+ 0.2 assembly tolerance)	mm 8
Insulation stripping length	mm 9
Connection data	
Screw connection, solid	
Screw connection, flexible/ferrule with/without plastic collar	
Conductor cross-section	
VDE rated data	
Current	
Voltage	
LED-current (24...60 V)	
LED-current (115...230 V)	
LED-current (24...230 V)	
Incandescent lamp-current	
Neon lamp-current	
Cross-section	
Ordering data	
	24 V~
↔	24 V~ ASK 1 LD 0222760000 25
↔	48 V~ ASK 1 LD 0225260000 25
↔	60 V~ ASK 1 LD 0226460000 25
↔	115 V~ ASK 1 LD 0225460000 25
↔	230 V~ ASK 1 LD 0225660000 25
	24 V~ ASK 1 LD 0222860000 25
	48 V~ ASK 1 LD 0225360000 25
	60 V~ ASK 1 LD 0226360000 25
	115 V~ ASK 1 LD 0225560000 25
	230 V~ ASK 1 LD 0225760000 25
Mountable on	
TS 32 and TS 35	
Accessories	
Mounting rail	
	TS 32 0122800000
	TS 35x7.5 0383400000
	TS 35x15 0498000000
End brackets (thickness mm)	for TS 32 EWK 1 0206160000 50
	for TS 35 EW 35 0383560000 50
End plate/End plate (thickness mm)	AP PA (1.5) 0380360000 20
Cross-connections	
Type 'QL'	
Cross-connection	
Type 'QB'	QB 2 ¹⁾ 0461100000 100
	QB 3 ¹⁾ 0461200000 50
	QB 4 ¹⁾ 0461300000 50
	QB 5 ¹⁾ 0545400000
	QB 58 ¹⁾ 0545300000
Fixing screw (fits QL)	straight
	angled
Disconnect lever (spare)	TH (spare) 0377060000 100
Mounting rails, end brackets, further marking material see "Accessories"	

¹⁾When using QB, the rated cross-current reduces to max. 2.5 mm²

ASK 1 LD




Warning:
In the event of a faulty fuse, the connection system is live!

UL		
8		
9		
0.5...4 mm ²		
0.5...4 mm ²		
AWG 22...12		
6.3 A		
24...230 V (depending on terminal)		
≤ 2 mA		
≤ 2 mA		
4 mm ²		
Type	Cat. No.	Qty.
ASK 1 LD	8050810000	25
ASK 1 LD	0222760000	25
ASK 1 LD	0225260000	25
ASK 1 LD	0226460000	25
ASK 1 LD	0225460000	25
ASK 1 LD	0225660000	25
ASK 1 LD	0222860000	25
ASK 1 LD	0225360000	25
ASK 1 LD	0226360000	25
ASK 1 LD	0225560000	25
ASK 1 LD	0225760000	25
Mountable on		
TS 32 and TS 35		
Accessories		
Mounting rail		
	TS 32	0122800000
	TS 35x7.5	0383400000
	TS 35x15	0498000000
End brackets (thickness mm)	for TS 32	EWK 1 0206160000 50
	for TS 35	EW 35 0383560000 50
End plate/End plate (thickness mm)	AP PA (1.5) 0380360000 20	
Cross-connections		
Type 'QL'		
Cross-connection		
Type 'QB'	QB 2 ¹⁾	0461100000 100
	QB 3 ¹⁾	0461200000 50
	QB 4 ¹⁾	0461300000 50
	QB 5 ¹⁾	0545400000
	QB 58 ¹⁾	0545300000
Fixing screw (fits QL)	straight	
	angled	
Disconnect lever (spare)	TH (spare)	0377060000 100

KDKS 1

Fuse insert 5x20



Warning:
In the event of a faulty fuse, the connection system is live!

UL		
8		
9		
0.5...4 mm ²		
0.5...4 mm ²		
AWG 22...12		
6.3 A		
24...230 V (depending on terminal)		
≤ 2 mA		
≤ 2 mA		
4 mm ²		
Type	Cat. No.	Qty.
KDKS 1	8146450000	25
KDKS 1	8148930000	25
KDKS 1	8148920000	25
KDKS 1	8142840000	25
KDKS 1	8148910000	25
Mountable on		
TS 32 and TS 35		
Accessories		
Mounting rail		
	TS 32	0122800000
	TS 35x7.5	0383400000
	TS 35x15	0498000000
End brackets (thickness mm)	for TS 32	EWK 1 0206160000 50
	for TS 35	EW 35 0383560000 50
End plate/End plate (thickness mm)	AP PA (1.5) 0380360000 20	
Cross-connections		
Type 'QL'		
Cross-connection		
Type 'QB'	QB 2 ¹⁾	0461100000 100
	QB 3 ¹⁾	0461200000 50
	QB 4 ¹⁾	0461300000 50
	QB 5 ¹⁾	0545400000
	QB 58 ¹⁾	0545300000
Fixing screw (fits QL)	straight	
	angled	
Disconnect lever (spare)	TH (spare)	0377060000 100

SAK-series

Fuse terminals

with fault indicator




Dimensions/approvals	
Width/length/height (mm)	with TS 32
Width/length/height (mm)	with TS 35 x 7.5
Terminal width (+ 0.2 assembly tolerance)	mm
Insulation stripping length/clamping screw/screwdriver blade	
Connection data	
Screw connection, solid	
Screw connection, flexible	
Conductor cross-section	
Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	
VDE rated data	
Voltage/current	
LED-current (24...60 V)	
LED-current (115...230 V)	
Incandescent lamp-current	
Neon lamp-current	
Cross-section	

Ordering data		Voltage
Fuse insert		
5 x 20	LED	24 V~
Acc. to IEC 60127-2 (VDE 0820 T.2 BI 1)		
without indicator		24 V~
		48 V~
		48 V=
		24 V=
		48 V=
		115 V=
		230 V=
Fuse insert		
5 x 25	LED	24 V~
Acc. to DIN 41576		
without indicator		48 V=
		115 V=
		230 V=

Accessories	
Mounting rail	
End brackets (thickness mm)	for TS 32 for TS 35
End plate (thickness mm)	
Cross-connection	
Type 'QL'	
Cross-connection	
Type 'QB'	
Fixing screw (fits QL)	
Screw cap (spare)	
Neon lamp	

SAKS 1

Fuse insert 5x20/5x25



Warning:
In the event of a faulty fuse, the connection system is live!


Dimensions/approvals	
Width/length/height (mm)	
Terminal width (+ 0.2 assembly tolerance)	mm
Insulation stripping length/clamping screw/screwdriver blade	
Connection data	
Screw connection, solid	
Screw connection, flexible	
Conductor cross-section	
Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	
VDE rated data	
Voltage/current	
LED-current (24...60 V)	
LED-current (115...230 V)	
Incandescent lamp-current	
Neon lamp-current	
Cross-section	

Type	Cat. No.	Qty.
SAKS 1 LD		
SAKS 1 LD	0371420000	10 0225820000 10
Acc. to IEC 60127-2 (VDE 0820 T.2 BI 1)	1111220000	10 1111320000 10
without indicator		
		0214020000 10
SAKS 1 GL		
SAKS 1 GL	0173220000	10
	0378920000	10
SAKS 1 GL		
SAKS 1 GL	0385320000	10 8068330000 10
	0306120000	10 0199920000 10
SAK 1 LD		
SAK 1 LD		on demand
SAKS GL		
SAKS GL		on demand
SAKS 1 GL		
SAKS 1 GL	0309320000	10 0198620000 10

Type	Cat. No.	Qty.
TS 32	0122800000	
TS 35x7.5	0383400000	
TS 35x15	0498000000	
EWK 1 (8.5)	0206160000	50
EW 35 (8.5)	0383560000	50
AP KrG (3)	0191320000	20
SK (5 x 20)	0282100000	20
SK (5 x 25)	0282000000	100

SAKS 4

Fuse insert E14/D 01
(e.g. Neozed D 01)



Warning:
In the event of a faulty fuse, the connection system is live!


Dimensions/approvals	
Width/length/height (mm)	
Terminal width (+ 0.2 assembly tolerance)	mm
Insulation stripping length/clamping screw/screwdriver blade	
Connection data	
Screw connection, solid	
Screw connection, flexible	
Conductor cross-section	
Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	
VDE rated data	
Voltage/current	
LED-current (24...60 V)	
LED-current (115...230 V)	
Incandescent lamp-current	
Neon lamp-current	
Cross-section	

Type	Cat. No.	Qty.
SAKS 4		
SAKS 4		
TS 32 Neon lamp		
Voltage		
115 V=	0101820000	10
480 V=	0102120000	10

Type	Cat. No.	Qty.
TS 32	0122800000	
EWK 1 (8.5)	0206160000	50

SAKS 6

Fuse insert 11/4" x 1/4"
acc. to DEF 63



Warning:
In the event of a faulty fuse, the connection system is live!


Dimensions/approvals	
Width/length/height (mm)	
Terminal width (+ 0.2 assembly tolerance)	mm
Insulation stripping length/clamping screw/screwdriver blade	
Connection data	
Screw connection, solid	
Screw connection, flexible	
Conductor cross-section	
Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	
VDE rated data	
Voltage/current	
LED-current (24...60 V)	
LED-current (115...230 V)	
Incandescent lamp-current	
Neon lamp-current	
Cross-section	

Type	Cat. No.	Qty.
SAKS 6 KrG		
SAKS 6 KrG	0531820000	40
for 1 1/4" x 1/4" acc. to DEF 63		
Voltage		
115 V=	0101820000	10
480 V=	0102120000	10
exchangable neon lamps (please order separately)		

Type	Cat. No.	Qty.
TS 32	0122800000	
EWK 1 (8.5)	0206160000	50
AP KrG	0146720000	20
QL 2	0191400000	50
QL 3	0191500000	50
QL 4	0191600000	20
QL 10	0338800000	20
BSM 3x6 m.SS	0346200000	100
Neon lamp 230 V~	0550300000	
Neon lamp 115 V~	0550200000	

SAKS 7

Fuse insert 5x20/5x25



Warning:
In the event of a faulty fuse, the connection system is live!


Dimensions/approvals	
Width/length/height (mm)	
Terminal width (+ 0.2 assembly tolerance)	mm
Insulation stripping length/clamping screw/screwdriver blade	
Connection data	
Screw connection, solid	
Screw connection, flexible	
Conductor cross-section	
Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	
VDE rated data	
Voltage/current	
LED-current (24...60 V)	
LED-current (115...230 V)	
Incandescent lamp-current	
Neon lamp-current	
Cross-section	

Type	Cat. No.	Qty.
SAKS 7 KrG		
SAKS 7 KrG	0576120000	40
for 5 x 25		
SAKS 7 KrG		
SAKS 7 KrG	0573120000	40
for 5 x 20		
exchangable neon lamps (please order separately)		

Type	Cat. No.	Qty.
TS 32	0122800000	
EWK 1 (8.5)	0206160000	50
AP KrG (3)	0146720000	20
QL 2	0207800000	20
QL 3	0207900000	20
QL 4	0208000000	20
QL 10	0338900000	20
BSM 4x9 m.SS	0133300000	100
Neon lamp 230 V~	0550300000	
Neon lamp 115 V~	0550200000	

Fuse inserts and gauge rings for Weidmüller fuse terminals




Fuse inserts

for terminal type	Size (mm)	Rated voltage (V)	Rated current (A)	Type	Cat. No.	Qty.			
G fuse inserts 5 x 20 without indicator acc. to IEC 60127-2 (VDE 0820 T.2 Bl 1)									
SAKS 1	5 x 20 Breaking capacity 1500 A (at 250 V, 50 Hz, cos φ = 0.7)	250	0.1 (F)	G 20/0.10A/F	0430300000	10			
SAKS 7			0.2 (F)	G 20/0.20A/F	0430400000	10			
ASK 1			0.25 (F)	G 20/0.25A/F	0430500000	10			
WSI 6 			0.5 (F)	G 20/0.50A/F	0430600000	10			
			0.63 (F)	G 20/0.63A/F	0430900000	10			
			1.0 (F)	G 20/1.00A/F	0430700000	10			
			1.6 (F)	G 20/1.60A/F	0430800000	10			
			2.0 (F)	G 20/2.00A/F	0430900000	10			
			2.5 (F)	G 20/2.50A/F	0431000000	10			
			3.15 (F)	G 20/3.15A/F	0431100000	10			
			4.0 (F)	G 20/4.00A/F	0431200000	10			
			5.0 (F)	G 20/5.00A/F	0431300000	10			
			6.3 (F)	G 20/6.30A/F	0431400000	10			
G fuse inserts 5 x 25 with indicator acc. to DIN 41576¹⁾									
SAKS 1	5 x 25 m. K.1) Breaking capacity 80 A (at 250 V, 50 Hz, cos φ = 1)	250	0.25 (M)	G 25/0.25A/M	0546900000	10			
SAKS 7			0.5 (M)	G 25/0.50A/M	0510300000	10			
WSI 6 			0.8 (M)	G 25/0.80A/M	0646400000	10			
			1 (M)	G 25/1.00A/M	0265800000	10			
			10 (M) ⁵⁾	G 25/10.0A/M	0193100000	10			
			2 (F)	G 25/2.00A/F	0192700000	10			
			4 (F)	G 25/4.00A/F	0192800000	10			
			6.3 (F)	G 25/6.30A/F	0192900000	10			
			Fuse inserts 1 1/4" x 1/4" without indicator acc. to BS 88						
			SAKS 3 ²⁾	33 kA Breaking capacity 33 kA fast	440	E 0.5 A	GZ 0.5A/F	0533800000	10
SAKS 6 	E 1 A	GZ 1.0A/F	0525500000			10			
	E 2 A	GZ 2.0A	0294500000			10			
	E 3 A	GZ 3.0A	0295700000			10			
	E 5 A	GZ 5.0A	0294600000			10			
	E 7 A	GZ 7.0A	0295800000			10			
	E 10 A	GZ 10.0A	0293900000			10			
D fuse inserts E 16 with indicator acc. to DIN 49360 (diazed)									
SAKS 2 	E 10 A E 16 A E 20 A E 25 A	500	10	E 16/10A RT	0208500000	25			
			16	E 16/16A GR	0208600000	25			
			20	E 16/20A BL	0208700000	25			
			25	E 16/25A GE	0208800000	25			
D fuse inserts E 14 Size D 01 and E 18 size D 02 with indicator acc. to DIN 49522 (neozed)³⁾									
SAKS 4 ⁴⁾ 	E 14/2 E 14/4 E 14/6 E 14/10 E 14/16 E 18/20	400	2	E 14/2A RS	0137400000	10			
			4	E 14/4A BR	0137500000	10			
			6	E 14/6A GN	0328300000	10			
			10	E 14/10A RT	0328400000	10			
			16	E 14/16A GR	0328500000	10			
			20	E 18/20A BL	0361300000	10			
SAKS 5 	E 18/25 E 18/35 E 18/50 E 18/63	400	25	E 18/25A GE	0361400000	10			
			35	E 18/35A SW	0361500000	10			
			50	E 18/50A WS	0361600000	10			
			63	E 18/63A KU	0361700000	10			

(F) = fast
(M) = medium-delayed action

- Note:**
- 1) The SIBA company also supplies 5 x 25 G fuse inserts with indicators in a shipbuilding model for 450 V AC.
 - 2) 5 x 30 (500 V AC) fuse inserts for SAKS 3 are available from the WICKMANN company
 - 3) The LINDNER company also supplies neozed fuse cartridges in an additional shipbuilding mode for 440 V AC.
 - 4) Fuse cartridges with the dimensions 1"x1/4" ≅ 25.4x6.35 mm and 13/32"x1 1/8" ≅ 10.3x38.1 mm are not included in product line.
 - 5) Only for SAKS 1 and SAKS 7.

Gauge rings

For terminal type	Gauge ring type	Amp.	Colour	Type	Cat. No.	Qty.
SAKS 4 and 4/35 	P 14/2	2	Pink	P 14/2D01 RS	0138000000	50
	P 14/4	4	Brown	P 14/4D01 BR	0138100000	50
	P 14/6	6	Green	P 14/6D01 GN	0328600000	50
	P 14/1	10	Red	P 14/10D01 RT	0328700000	50
	SAKS 5 and 5/35 	P 18/20	20	Blue	P 18/20D02 BL	0361800000
P 18/25		25	Yellow	P 18/25D02 GE	0361900000	50
P 18/35		35	Black	P 18/35D02 SW	0362000000	50
P 18/50		50	White	P 18/50D02 WS	0362100000	50
SAKS 2 and 2/35 	P 16/10	10	Red	P 16/10 RT	0208900000	100
	P 16/16	16	Grey	P 16/16 GR	0209000000	100
	P 16/20	20	Blue	P 16/20 BL	0209100000	100

Disconnect test terminals

SAKR SAKR/35



Dimensions/approvals	
Width/length/height (mm)	with TS 32 6.5/42/40.5/54.5 (opened)
Width/length/height (mm)	with TS 35 x 7.5 6.5/46/38/52
Insulation stripping length/clamping screw/screwdriver blade	8 mm/M 3/3.5 x 0.6

Rated data	
Rated voltage/current/cross-section	400 V ⁶⁾ /10 A/4 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data	
Tightening torque range	Nm 0.5...1.0/0.5 StB
Torque setting with electric screwdriver type DMS 2	2/1

Clampable conductor	
Solid H07V-U	mm ² 0.5...4
Stranded H07V-R	mm ² 1.5...4
Flexible H07V-K	mm ² 0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
With/without plastic insulating collar	mm ² 0.5...4
Plug gauge according to 60 947-7-1	Size A 3
Continuous current rating of cross-connection 2...5-pole	A (QB 2...25) 10
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/10 A/26...12 AWG
Voltage/current/conductor size	CSA 300 V/10 A/26...12 AWG

Ordering data	Type	Qty.	Qty.
	KrG		0412120000 100
	PA		0412160000 100 0172160000 100
	Without diode PA		
	With diode PA		
	Blue PA		0412180000 100 0172180000 100
	Orange PA		1461960000 100
	KrG		0412220000 100
With 2 StB ⁵⁾	PA		0412260000 100 0183360000 100
With 2 StB ⁵⁾	without diode PA		
With 2 StB ⁵⁾	Blue		0412280000 100 0183380000 100

End plate (thickness mm)	Type	Cat. No.	Qty.
	KrG	AP (1.5)	0211320000 20
	PA	AP (1.5)	0211360000 20
	Blue PA	AP (1.5)	0211380000 20

Partition (thickness mm)	Type	Cat. No.	Qty.
	TW HP (1.0)	0297100000	20

Cross-connection	
QB 4	2-pole QB 2 ⁴⁾ 0482700000 100
	3-pole QB 3 ⁴⁾ 0482800000 50
	4-pole QB 4 ⁴⁾ 0482900000 50
	25-pole QB 25 blank ⁴⁾ 0134000000 20

Contact sleeve (spare)	



Test plug	PS 2.3 0180400000 20

Diode plug (spare)	
without diode	
with diode 1N4007	DLS 2 0321060000 50
with diode 1N4007	DLS 2 + 0630160000 50
with jumper	DLS 2 - 0547760000 50
	DLS 2 0547660000 25

Marking tags	Print
	DEK Standard DEK 6.5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

SAKR-D SAKR-D/35



Width/length/height (mm)	6.5/42/40.5/57 (with DLS 2)
Width/length/height (mm)	6.5/46/38/54.5
Insulation stripping length/clamping screw/screwdriver blade	8 mm/M 3/3.5 x 0.6

Rated data	
Rated voltage/current/cross-section	400 V/10 A/4 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data	
Tightening torque range	Nm 0.5...1.0/0.5 StB
Torque setting with electric screwdriver type DMS 2	2/1

Clampable conductor	
Solid H07V-U	mm ² 0.5...4
Stranded H07V-R	mm ² 1.5...4
Flexible H07V-K	mm ² 0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
With/without plastic insulating collar	mm ² 0.5...4
Plug gauge according to 60 947-7-1	Size A 3
Continuous current rating of cross-connection 2...5-pole	A (QB 2...25) 10
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/10 A/26...12 AWG
Voltage/current/conductor size	CSA 300 V/10 A/26...12 AWG

Ordering data	Type	Qty.	Qty.
	KrG		0412120000 100
	PA		0412960000 100 0299960000 50
	Without diode PA		
	With diode PA		
	Blue PA		0413060000 50 0185760000 50
	Orange PA		0263660000 50 0299560000 50
	KrG		0412220000 100
With 2 StB ⁵⁾	PA		0546460000 100
With 2 StB ⁵⁾	without diode PA		
With 2 StB ⁵⁾	Blue		0413160000 50

End plate (thickness mm)	Type	Cat. No.	Qty.
	AP (1.5)	0211360000	20

Partition (thickness mm)	Type	Cat. No.	Qty.
	TW HP (1.0)	0297100000	20

Cross-connection	
QB 4	2-pole QB 2 ⁴⁾ 0482700000 100
	3-pole QB 3 ⁴⁾ 0482800000 50
	4-pole QB 4 ⁴⁾ 0482900000 50
	25-pole QB 25 blank ⁴⁾ 0134000000 20

Contact sleeve (spare)	


Test plug	PS 2.3 0180400000 20

Diode plug (spare)	
without diode	
with diode 1N4007	DLS 2 0321060000 50
with diode 1N4007	DLS 2 + 0630160000 50
with jumper	DLS 2 - 0547760000 50
	DLS 2 0547660000 25

Marking tags	Print
	DEK 6.5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

DKT 4 DKT 4/35



Width/length/height (mm)	6/65/56.5/70 (opened)
Width/length/height (mm)	6/65/56.5/70
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6

Rated data	
Rated voltage/current/cross-section	400V/10 A/4 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data	
Tightening torque range	Nm 0.5...1.0/0.5 StB
Torque setting with electric screwdriver type DMS 2	2/1

Clampable conductor	
Solid H07V-U	mm ² 0.5...4
Stranded H07V-R	mm ² 1.5...4
Flexible H07V-K	mm ² 0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
With/without plastic insulating collar	mm ² 0.5...4
Plug gauge according to 60 947-7-1	Size A 3
Continuous current rating of cross-connection 2...5-pole	A (QB 2...4) 10
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/10 A/26...12 AWG
Voltage/current/conductor size	CSA 300 V/10 A/26...12 AWG

Ordering data	Type	Qty.	Qty.
	KrG		0687360000 50 0687460000 50
	PA		
	Without diode PA		
	With diode PA		
	Blue PA		0327860000 50 0327960000 50
	Orange PA		
	KrG		0327860000 50 0327960000 50
With 2 StB ⁵⁾	PA		1304860000 50 1304960000 50
With 2 StB ⁵⁾	without diode PA		
With 2 StB ⁵⁾	Blue		

End plate (thickness mm)	Type	Cat. No.	Qty.
	AP (1.5)	0687560000	20

Partition (thickness mm)	Type	Cat. No.	Qty.
	TW HP (2.0)	0607000000	20

Cross-connection	
QB 4	2-pole QB 2 ⁴⁾ 0482700000 100
	3-pole QB 3 ⁴⁾ 0482800000 50
	4-pole QB 4 ⁴⁾ 0482900000 50
	25-pole QB 25 blank ⁴⁾ 0134000000 20

Contact sleeve (spare)	



Test plug	PS 2.3 0180400000 20

Diode plug (spare)	
without diode	
with diode 1N4007	DLS 2 0321060000 50
with diode 1N4007	DLS 2 + 0630160000 50
with jumper	DLS 2 - 0547760000 50
	DLS 2 0547660000 25

Marking tags	Print
	DEK 6 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

DKT 4 V DKT 4 V/35



Width/length/height (mm)	6/65/56.5/70 (opened)
Width/length/height (mm)	6/65/56.5/70
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6

Rated data	
Rated voltage/current/cross-section	400 V/10 A/4 mm ²
Rated impulse voltage/pollution severity	6 kV/3

Further technical data	
Tightening torque range	Nm 0.5...1.0/0.5 StB
Torque setting with electric screwdriver type DMS 2	2/1

Clampable conductor	
Solid H07V-U	mm ² 0.5...4
Stranded H07V-R	mm ² 1.5...4
Flexible H07V-K	mm ² 0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
With/without plastic insulating collar	mm ² 0.5...4
Plug gauge according to 60 947-7-1	Size A 3
Continuous current rating of cross-connection 2...5-pole	A (QB 2...4) 10
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/10 A/26...12 AWG
Voltage/current/conductor size	CSA 300 V/10 A/26...12 AWG

Ordering data	Type	Qty.	Qty.
	KrG		
	PA		
	Without diode PA		
	With diode PA		
	Blue PA		
	Orange PA		
	KrG		
With 2 StB ⁵⁾	PA		
With 2 StB ⁵⁾	without diode PA		
With 2 StB ⁵⁾	Blue		

End plate (thickness mm)	Type	Cat. No.	Qty.
	AP (1.5)	0687560000	20

Partition (thickness mm)	Type	Cat. No.	Qty.
	TW HP (2.0)	0607000000	20

Cross-connection	
QB 4	2-pole QB 2 ⁴⁾ 0482700000 100
	3-pole QB 3 ⁴⁾ 0482800000 50
	4-pole QB 4 ⁴⁾ 0482900000 50
	25-pole QB 25 blank ⁴⁾ 0134000000 20

Contact sleeve (spare)	

Test plug	PS 2.3 0180400000 20

Diode plug (spare)	
without diode	
with diode 1N4007	DLS 2 0321060000 50
with diode 1N4007	DLS 2 + 0630160000 50
with jumper	DLS 2 - 0547760000 50
	DLS 2 0547660000 25

Marking tags	Print
	DEK 6 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"


1) without DLS
2) with DLS empty

3) with DLS 1N4007
4) When using QB the rated cross-current reduces to max. 2.5 mm²

5) With DKT 4 only on upper terminal level
6) As disconnect test terminal rated voltage 250 V

Disconnect test terminals

ASK 1 ASK 1/35



RU @

8/58/49

8/58/44

9 mm/M 3/3.5 x 0.6

500 V/19 A/4 mm²

6 kV/3

0.5...1.0

2

0.5...4

1.5...4

0.5...4

0.5...4

A 3

(QB 2...4) 10

300 V/15 A/12 max. AWG

300 V/6.3 A/26...12 AWG

Qty.

0456360000 100

0105260000 100

Type	Cat. No.	Qty.
------	----------	------

AP (1.5)	0380360000	20
----------	-------------------	----

TW HP (2.0)	0607000000	20
-------------	-------------------	----

QB 2 ⁴)	0461100000	100
---------------------	-------------------	-----

QB 3 ⁴)	0461200000	50
---------------------	-------------------	----

QB 4 ⁴)	0461300000	50
---------------------	-------------------	----

multipole interruptable with group marking carrier SchS 2; 2-pole (Cat. No. **1359500000**) 1000 mm (Cat. No. **0337400000**)


K sleeve	0553300000	100
----------	-------------------	-----

DEK 5 FW	see "Accessories"	
----------	-------------------	--

Feed-through terminals with tab connection

AST 1 AST1/35

6.3
2.8



UL @ DNV

Dimensions/approvals	
Width/length/height (mm)	with TS 32 6.5/58/53.5
Width/length/height (mm)	with TS 35 x 7.5 6.5/58/46
Insulation stripping length/clamping screw/screwdriver blade	

Rated data	
Rated voltage/-current	500 V ¹⁾ /-
Rated cross-section for clamping yokes	-
Rated cross-section tab	6.3/2.8 mm
Rated Voltage VDE 0110/1.89/pollution severity	6 kV/3

Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

Clampable conductor	
Solid H07V-U	mm ²
Stranded H07V-R	mm ²
Flexible H07V-K	mm ²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
Plug gauge according to 60 947-7-1	Size
Continuous current of terminal for conductor size	
Continuous current rating of cross-connection 2...5-pole	A
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/13 A/-
Voltage/current/conductor size	CSA 300 V/16 A/-

Ordering data		Version	
			Qty.
			Qty.
			Qty.
			Qty.
			Qty.
			Qty.

End plate/partition/small partition (thickness mm)			Type	Cat. No.	Qty.
AP	TW	TSch 1	KrG AP (3.0)	0266420000	20
			Blue KrG AP (1.5)	0266460000	20
			PA AP (1.5)	0460560000	20
			PA TW (1.5)	0130160000	20
			HP TW (0.5)	0474700000	20
			HP TW (2.0)	0607000000	20
			TSch 1	0319160000	100

Cross-connection		Type	Cat. No.	Qty.
Q4	2-pole	Q 2	0336700000	50
	3-pole	Q 3	0336800000	50
	4-pole	Q 4	0336900000	50
	10-pole	Q 10	0368800000	20
	25-pole			

Plug adapter		Type	Cat. No.	Qty.
	2-pole	STA 2.5/2	0165860000	100
	3-pole	STA 2.5/3	0165960000	50
	4-pole	STA 2.5/4	0190360000	50
	5-pole	STA 2.5/5	0166060000	50
	8-pole	STA 2.5/8	0166160000	50

Test plug/socket		Type	Cat. No.	Qty.
	Plug-test socket without using QL for TS 32	StB 14	0168600000	50
	PS	PS 2.3	0180400000	20
	StB	StB 14	0168600000	50

Insulation sleeve		Type	Cat. No.	Qty.
	IH 2.8	IH 2.8	0386060000	100
	IH 6.3	IH 6.3	0386260000	100

Marking tags		Print	Type	Cat. No.	Qty.
	1	DEK	Standard	DEK 6.5	see "Accessories"
	2				
	3				
	4				
	5				
	6				

Mounting rails, end brackets, further marking material see "Accessories"

AST 3 AST 3/35

6.3
2.8



UL @ DNV

Width/length/height (mm)	6.5/40/47.5
Width/length/height (mm)	6.5/44/40

Rated data	
Rated voltage/-current	500 V ¹⁾ /-
Rated cross-section for clamping yokes	-
Rated cross-section tab	2.5/1.0 mm ²
Rated Voltage VDE 0110/1.89/pollution severity	6 kV/3

Further technical data	
Tightening torque range	Nm
Torque setting with electric screwdriver type DMS 2	

Clampable conductor	
Solid H07V-U	mm ²
Stranded H07V-R	mm ²
Flexible H07V-K	mm ²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
Plug gauge according to 60 947-7-1	Size
Continuous current of terminal for conductor size	
Continuous current rating of cross-connection 2...5-pole	A
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/13 A/-
Voltage/current/conductor size	CSA 300 V/16 A/-

Ordering data		Version	
			Qty.
			Qty.
			Qty.
			Qty.
			Qty.
			Qty.

End plate/partition/small partition (thickness mm)			Type	Cat. No.	Qty.
AP	TW	TSch 1	KrG AP (3.0)	0298120000	20
			Blue KrG AP (1.5)	0460560000	20
			PA AP (1.5)	0460560000	20
			PA TW (1.5)	0130160000	20
			HP TW (0.5)	0297100000	20
			HP TW (2.0)	0297100000	20
			TSch 1	0319160000	100

Cross-connection		Type	Cat. No.	Qty.
Q4	2-pole	Q 2	0336700000	50
	3-pole	Q 3	0336800000	50
	4-pole	Q 4	0336900000	50
	10-pole	Q 10	0368800000	20
	25-pole			

Plug adapter		Type	Cat. No.	Qty.
	2-pole	STA 2.5/2	0165860000	100
	3-pole	STA 2.5/3	0165960000	50
	4-pole	STA 2.5/4	0190360000	50
	5-pole	STA 2.5/5	0166060000	50
	8-pole	STA 2.5/8	0166160000	50

Test plug/socket		Type	Cat. No.	Qty.
	Plug-test socket without using QL for TS 32	StB 14	0168600000	50
	PS	PS 2.3	0180400000	20
	StB	StB 14	0168600000	50

Insulation sleeve		Type	Cat. No.	Qty.
	IH 2.8	IH 2.8	0386060000	100
	IH 6.3	IH 6.3	0386260000	100

Marking tags		Print	Type	Cat. No.	Qty.
	1	DEK	Standard	DEK 6	see "Accessories"
	2				
	3				
	4				
	5				
	6				

Mounting rails, end brackets, further marking material see "Accessories"

AST 4 AST 4/35

6.3
2.8



UL @

Width/length/height (mm)	6.5/40/47.5
Width/length/height (mm)	6.5/44/40
Insulation stripping length/clamping screw/screwdriver blade	

Rated data	
Rated voltage/-current	500 V ¹⁾ /-
Rated cross-section for clamping yokes	2.5 mm ²
Rated cross-section tab	2.5/1.0 mm ²
Rated Voltage VDE 0110/1.89/pollution severity	6 kV/3

Further technical data	
Tightening torque range	0.4...0.7 Nm
Torque setting with electric screwdriver type DMS 2	1

Clampable conductor	
Solid H07V-U	mm ²
Stranded H07V-R	mm ²
Flexible H07V-K	mm ²
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²
Plug gauge according to 60 947-7-1	Size
Continuous current of terminal for conductor size	
Continuous current rating of cross-connection 2...5-pole	A
Continuous current rating of cross-connection 6...10-pole	A

Rated data according to UL/CSA	
Voltage/current/conductor size	UL 300 V/13 A/22...12 AWG
Voltage/current/conductor size	CSA 300 V/16 A/24...12 AWG

Ordering data		Version	
			Qty.
			Qty.
			Qty.
			Qty.
			Qty.
			Qty.

End plate/partition/small partition (thickness mm)			Type	Cat. No.	Qty.
AP	TW	TSch 1	KrG AP (3.0)	0298120000	20
			Blue KrG AP (1.5)	0460560000	20
			PA AP (1.5)	0460560000	20
			PA TW (1.5)	0130160000	20
			HP TW (0.5)	0297100000	20
			HP TW (2.0)	0297100000	20
			TSch 1	0319160000	100

Cross-connection		Type	Cat. No.	Qty.
Q4	2-pole	Q 2	0336700000	50
	3-pole	Q 3	0336800000	50
	4-pole	Q 4	0336900000	50
	10-pole	Q 10	0368800000	20
	25-pole			

Plug adapter		Type	Cat. No.	Qty.
	2-pole	STA 2.5/2	0165860000	100
	3-pole	STA 2.5/3	0165960000	50
	4-pole	STA 2.5/4	0190360000	50
	5-pole	STA 2.5/5	0166060000	50
	8-pole	STA 2.5/8	0166160000	50

Test plug/socket		Type	Cat. No.	Qty.
	Plug-test socket without using QL for TS 32	StB 14	0168600000	50
	PS	PS 2.3	0180400000	20
	StB	StB 14	0168600000	50


Insulation sleeve		Type	Cat. No.	Qty.
	IH 2.8	IH 2.8	0386060000	100
	IH 6.3	IH 6.3	0386260000	100

Marking tags		Print	Type	Cat. No.	Qty.
	1	DEK	Standard	DEK 6	see "Accessories"
	2				
	3				
	4				
	5				
	6				

Mounting rails, end brackets, further marking material see "Accessories"

AST 5 AST 5/35

6.3
2.8



UL @ DNV

Width/length/height (mm)	6.5/58/53.5
Width/length/height (mm)	6.5/58/46
Insulation stripping length/clamping screw/screwdriver blade	

Rated data	
Rated voltage/-current	500 V ¹⁾ /-
Rated cross-section for clamping yokes	4 mm ²
Rated cross-section tab	2.5/1.0 mm ²
Rated Voltage VDE 0110/1.89/pollution severity	6 kV/3

Further technical data	
Tightening torque range	0.5...1.0 Nm
Torque setting with electric screwdriver type DMS 2	2

Feed-through terminals with tab connection

SAK 4 S SAK 4 S/35

6.3
2.8



Width/length/height (mm)	with TS 32	6.5/40/51.5
Width/length/height (mm)	with TS 35 x 7.5	6.5/40/49.5
Insulation stripping length/clamping screw/screwdriver blade		12 mm/M 3/3.5 x 0.6

Dimensions/approvals

Width/length/height (mm)	with TS 32	6.5/40/51.5
Width/length/height (mm)	with TS 35 x 7.5	6.5/40/49.5
Insulation stripping length/clamping screw/screwdriver blade		12 mm/M 3/3.5 x 0.6

Rated data

Rated voltage/-current		500 V ¹⁾ /16 A
Rated cross-section for clamping yokes		4 mm ²
Rated cross-section tab	6.3/2.8 mm	2.5/1.0 mm ²
Rated Voltage VDE 0110/1.89/pollution severity		6 kV/3

Further technical data

Tightening torque range	Nm	0.5...1.0
Torque setting with electric screwdriver type DMS 2		2

Clampable conductor

Solid H07V-U	mm ²	0.33...6
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 4
Continuous current of terminal for conductor size		
Continuous current rating of cross-connection 2 pole	A	(QL 2...10) 36 A at 6 mm ²
Continuous current rating of cross-connection multipole	A	

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/13 A/26...12 AWG
Voltage/current/conductor size	CSA	300 V/13 A/26...12 AWG

Ordering data

Version

Slotted KrG	Qty.	0401220000	100
Slotted blue KrG	Qty.		
Slotted PA	Qty.	0401260000	100
Unslotted KrG	Qty.	0630360000	100

SAK 4 SS SAK 4 SS/35

6.3
2.8



Width/length/height (mm)		6.5/40/51.5
Width/length/height (mm)		6.5/40/49.5
Insulation stripping length/clamping screw/screwdriver blade		12 mm/M 3/3.5 x 0.6

Rated voltage/-current		500 V ¹⁾ /16 A
Rated cross-section for clamping yokes		4 mm ²
Rated cross-section tab		2.5/1.0 mm ²
Rated Voltage VDE 0110/1.89/pollution severity		6 kV/3

Tightening torque range	Nm	
Torque setting with electric screwdriver type DMS 2		

Solid H07V-U	mm ²	0.33...6
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 4
Continuous current of terminal for conductor size		
Continuous current rating of cross-connection 2 pole	A	(QL 2...10) 36 A at 6 mm ²
Continuous current rating of cross-connection multipole	A	

Voltage/current/conductor size	UL	300 V/13 A/18...14 AWG
Voltage/current/conductor size	CSA	300 V/13 A/18...14 AWG

Slotted KrG	Qty.	0479620000	10
Slotted blue KrG	Qty.		
Slotted PA	Qty.	0479660000	100
Unslotted KrG	Qty.	0630460000	100
	Qty.	0352920000	10

SAKR F SAKR F/35

2.8



Width/length/height (mm)		6.5/42/40.5/54.5 (opened)
Width/length/height (mm)		6.5/42/40.5/32.5
Insulation stripping length/clamping screw/screwdriver blade		8 mm/M 3/3.5 x 0.6

Rated voltage/-current		250 V ¹⁾ /10 A
Rated cross-section for clamping yokes		4 mm ²
Rated cross-section tab		-/1.0 mm ²
Rated Voltage VDE 0110/1.89/pollution severity		6 kV/3

Tightening torque range	Nm	0.5...1.0
Torque setting with electric screwdriver type DMS 2		1

Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...2.5
Plug gauge according to 60 947-7-1	Size	A 3
Continuous current of terminal for conductor size		
Continuous current rating of cross-connection 2 pole	A	(QB 2...25) 10
Continuous current rating of cross-connection multipole	A	

Voltage/current/conductor size	UL	300 V/10 A/22...12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/26...12 AWG

Slotted KrG	Qty.		
Slotted blue KrG	Qty.		
Slotted PA	Qty.	0663660000	100
Unslotted KrG	Qty.	6382870000	100
		with 1 StB 6	

End plate/partition/small partition (thickness mm)

Type	Cat. No.	Qty.
AP (1.5)	0117920000	20
AP (1.5)	0117960000	20
AP (1.5)	0130160000	20
TW (1.0)	0297100000	20



Type	Cat. No.	Qty.
AP (1.5)	0117920000	20
AP (1.5)	0117970000	20
AP (1.5)	0117960000	20
TW (1.5)	0130160000	20
TW (1.0)	0297100000	20

Type	Cat. No.	Qty.
AP (1.5)	0211360000	20
TW (1.0)	0297100000	20

Cross-connection

Type	Cat. No.	Qty.
QL 2	0130600000	100
QL 3	0130700000	100
QL 4	0130800000	50
QL 10	0338200000	20



Type	Cat. No.	Qty.
QL 2	0130600000	100
QL 3	0130700000	100
QL 4	0130800000	50
QL 10	0338200000	20

Type	Cat. No.	Qty.
QB 2*	0482700000	100
QB 3*	0482800000	50
QB 4*	0482900000	50
QB 25 blank*	0134000000	20

BS M 3 x 4.5



BS M 3 x 24



BS M 3x4.5	1593210000	100
------------	------------	-----

BS M 3x4.5	1593210000	100
------------	------------	-----

Test plug/socket



PS

PS 2.3	0180400000	20
--------	------------	----

Insulation sleeve




IH 2.8	0386060000	100
IH 6.3	0386260000	100

IH 2.8	0386060000	100
IH 6.3	0386260000	100

IH 2.8	0386060000	200
--------	------------	-----

Marking tags



DEK Standard

DEK 6.5	see "Accessories"
---------	-------------------

DEK 6.5	see "Accessories"
---------	-------------------

DEK 6.5	see "Accessories"
---------	-------------------

Mounting rails, end brackets, further marking material see "Accessories"

¹⁾ With insulation sleeve

¹⁾ The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used

Feed-through terminals with tab connection

DK 4 SS/35



UL CE LR

Dimensions/approvals
 Width/length/height (mm) with TS 32
 Width/length/height (mm) with TS 35 x 7.5
 Insulation stripping length/clamping screw/screwdriver blade

6/54/60.5

Rated data

Rated voltage/-current
 Rated cross-section for clamping yokes
 Rated cross-section tab 6.3/2.8 mm
 Rated Voltage VDE 0110/1.89/pollution severity

400 V¹/2 x 16 A
 -
 2.5/1.0 mm²
 8 kV/3

Further technical data

Tightening torque range Nm
 Torque setting with electric screwdriver type DMS 2

Clampable conductor

Solid H07V-U mm²
 Stranded H07V-R mm²
 Flexible H07V-K mm²
 Flexible H07V-K and ferrule according to DIN 46 228/1 mm²
 With/without plastic insulation collar
 Plug gauge according to 60 947-7-1 Size
 Continuous current of terminal for conductor size
 Continuous current rating of cross-connection 2 pole A
 Continuous current rating of cross-connection multipole A

(QL 2...10) 20

Rated data according to UL/CSA

Voltage/current/conductor size UL
 Voltage/current/conductor size CSA

300 V/10 A/22...12 AWG
 300 V/10 A/22...12 AWG

Ordering data

Version PA

Cat. No. Qty.
0217160000 100

DK 4 SS/35 only 2.8



UL CE LR

6/54/60.5

400 V¹/2x10
 -
 1.0 mm²
 4 kV/3

(QL 2...10) 20

300 V/10 A/22...12 AWG
 300 V/10 A/22...12 AWG

Cat. No. Qty.
0297060000 100

DK 4 S DK 4 S/35



UL CE LR

6/54/59.5
 6/54/60.5
 9 mm/M 3/3.5 x 0.6

400 V¹/2 x 10
 4 mm²
 1.0 mm²
 6 kV/3

0.5...1.0
 2

0.5...4
 1.5...4
 0.5...4


0.5...4
 A 3

(QL 2...10) 20

300 V/10 A/22...12 AWG
 300 V/10 A/22...12 AWG

Qty. Qty.
0631260000 100 **0686660000** 100

DK 4 S only 2.8 DK 4 S/35 only 2.8



UL CE LR

6/54/59.5
 6/54/60.5
 9 mm/M 3/3.5 x 0.6

400 V¹/2 x 10
 4 mm²
 1.0 mm²
 6 kV/3

0.5...1.0
 2

0.5...4
 1.5...4
 0.5...4

0.5...4
 A 3

(QL 2...10) 20

300 V/10 A/22...12 AWG
 300 V/10 A/22...12 AWG

Qty. Qty.
0631160000 100 **0686560000** 100

End plate (thickness mm)



PA

Type Cat. No. Qty.
 AP (1.5) **0631360000** 20

Type Cat. No. Qty.
 AP (1.5) **0631360000** 20

Type Cat. No. Qty.
 AP (1.5) **0631360000** 20

Type Cat. No. Qty.
 AP (1.5) **0631360000** 20

Partition



for TS 32 HP

TW HP (2.0) **0607000000** 20

TW HP (2.0) **0607000000** 20

Small partition



TSch 6

TSch 6 **0190260000** 100

TSch 6 **0190260000** 100

TSch 6 **0190260000** 100

TSch 6 **0190260000** 100

Cross-connection



Q 3

2-pole Q 2 **0336400000** 50
 3-pole Q 3 **0336500000** 50
 4-pole Q 4 **0336600000** 50
 10-pole Q 10 **0368600000** 20

2-pole Q 2 **0336400000** 50
 3-pole Q 3 **0336500000** 50
 4-pole Q 4 **0336600000** 50
 10-pole Q 10 **0368600000** 20

2-pole Q 2 **0336400000** 50
 3-pole Q 3 **0336500000** 50
 4-pole Q 4 **0336600000** 50
 10-pole Q 10 **0368600000** 20

2-pole Q 2 **0336400000** 50
 3-pole Q 3 **0336500000** 50
 4-pole Q 4 **0336600000** 50
 10-pole Q 10 **0368600000** 20

Test plug/socket



StB

Plug test socket without using QL
 Plug test socket for use with QL

StB 8.5 **0215700000** 50

StB 8.5 **0215700000** 50

StB 8.5 **0215700000** 50

StB 8.5 **0215700000** 50

Insulation sleeve



PS


PS 2.3 **0180400000** 20
 IH 2.8 **0386060000** 100
 IH 6.3 **0386260000** 100

PS 2.3 **0180400000** 20
 IH 2.8 **0386060000** 100
 IH 6.3 **0386260000** 100

PS 2.3 **0180400000** 20
 IH 2.8 **0386060000** 100
 IH 6.3 **0386260000** 100

PS 2.3 **0180400000** 20
 IH 2.8 **0386060000** 100
 IH 6.3 **0386260000** 100

Marking tags



DEK

Print

Standard

DEK 6 see "Accessories"

DEK 6 see "Accessories"

DEK 6 see "Accessories"

DEK 6 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

¹) With insulation sleeve

Feed-through terminals

Disconnect terminals for wrap connection acc. to DIN 41 611, Part 2 and for spring-clip connection acc. to DIN 41 611, Part 4

DK 4 T
Pin 1 x 1



DK 4 T
Pin 0.8 x 1.6



DK 4 T
Pin 0.8 x 2.4



SAKRT
Pin 1 x 1/0.8 x 2.4 and 0.8 x 1.6



Dimensions

Width/length/height (mm) with TS 32
 Insulation stripping length/clamping screw/screwdriver blade

6/50/58.5/75.5
9 mm/M 3/3.5 x 0.6

6/50/60.5/77.5
9 mm/M 3/3.5 x 0.6

6/50/67.5/84.5
9 mm/M 3/3.5 x 0.6

6/42/40.5/54.5
8 mm/M 3/3.5 x 0.6

Rated data

Rated voltage/current/cross-section
Rated impulse voltage VDE 0110/1.89/pollution severity

250 V/8 A/4 mm²
4 kV/3

250 V/10 A/4 mm²
4 kV/3

250 V/10 A/4 mm²
4 kV/3

250 V/6/8 A/4 mm²
4 kV/3

Further technical data

Tightening torque range Nm
Torque setting with electric screwdriver type DMS 2

0.5...1.0
1

0.5...1.0
1

0.5...1.0
1

0.5...1.0
2

Clampable conductor

Solid H07V-U mm²
Stranded H07V-R mm²
Flexible H07V-K mm²
Flexible H07V-K and ferrule according to DIN 46 228/1
With/without plastic insulating collar mm²
Plug gauge according to IEC 60 947-1 Size

0.5...4
1.5...4
0.5...4
0.5...4
A3

0.5...4
1.5...4
0.5...4
0.5...4
A3

0.5...4
1.5...4
0.5...4
0.5...4
A3

0.5...4
1.5...4
0.5...4
0.5...4
A3

Continuous current of terminal block for conductor size
Continuous current rating of cross-connection 2-pole
Continuous current rating of cross-connection multipole

(Q 2...10) 32
(Q 2...10) 32

(Q 2...10) 32
(Q 2...10) 32

(Q 2...10) 32
(Q 2...10) 32

(QB 2...10) 10
(QB 2...10) 10

Rated data according to UL/CSA

Voltage/current/conductor size UL
Voltage/current/conductor size CSA

—
—

—
—

—
—

—
—

Ordering data

Pin	Type	Cat. No.	Qty.
Right	PA	0536560000	50
Links	PA		
Horizontal right	PA		
Horizontal assembly	Vertical right		
Vertical assembly	Vertical right		
	Vertical right		
	Vertical left		

Type	Cat. No.	Qty.
Right	0536560000	50
Links		
Horizontal right		
Horizontal assembly		
Vertical assembly		

Type	Cat. No.	Qty.
Right		
Links		
Horizontal right	0370460000 ¹⁾	50
Horizontal assembly		
Vertical assembly		
	0370360000 ¹⁾	

Type	Cat. No.	Qty.
Right		
Links		
Horizontal right		
Horizontal assembly		
Vertical assembly		
	0527760000 ¹⁾	50

Type	Cat. No.	Qty.
Right		
Links		
Horizontal right		
Horizontal assembly		
Vertical assembly		

DK 4 QT

bridgeable on both levels Right PA

1398460000¹⁾ 50

End plate/partition (thickness mm)

Type	Cat. No.	Qty.
PA	AP (1.5) 0359260000	20
	AP (DK4 QT) 1397160000	20
Blue PA	AP (1.5) 0359280000	20
	TW (2.0) 0607000000	20

Type	Cat. No.	Qty.
PA	AP (1.5) 0359260000	20
Blue PA	AP (1.5) 0359280000	20
	TW (2.0) 0607000000	20

Type	Cat. No.	Qty.
PA	AP (1.5) 0359260000	20
Blue PA	AP (1.5) 0359280000	20
	TW (2.0) 0607000000	20

Type	Cat. No.	Qty.
PA	AP (1.5) 0359260000	20
Blue PA	AP (1.5) 0359280000	20
	TW (2.0) 0607000000	20

Type	Cat. No.	Qty.
PA	AP (1.5) 0211360000	20
Blue PA	AP (1.5) 0359280000	20
	TW (2.0) 0607000000	20

Small partition

Type	Cat. No.	Qty.
TSch 4	TSch 4 0363360000	100

Type	Cat. No.	Qty.
TSch 4	TSch 4 0363360000	100

Type	Cat. No.	Qty.
TSch 4	TSch 4 0363360000	100

Type	Cat. No.	Qty.
TSch 4	TSch 4 0363360000	100

Type	Cat. No.	Qty.
TSch 4	TSch 4 0363360000	100

Cross-connection/covers

Type	Cat. No.	Qty.
Q 3	Q 2 0336400000	50
	Q 3 0336500000	50
	Q 4 0336600000	50
	Q 10 0368600000	20
	QB 2* 0482700000	100
	QB 3* 0482800000	50
	QB 4* 0482900000	50
25-pole		

Type	Cat. No.	Qty.
Q 3	Q 2 0336400000	50
	Q 3 0336500000	50
	Q 4 0336600000	50
	Q 10 0368600000	20
	QB 2* 0482700000	100
	QB 3* 0482800000	50
	QB 4* 0482900000	50

Type	Cat. No.	Qty.
Q 3	Q 2 0336400000	50
	Q 3 0336500000	50
	Q 4 0336600000	50
	Q 10 0368600000	20
	QB 2* 0482700000	100
	QB 3* 0482800000	50
	QB 4* 0482900000	50

Type	Cat. No.	Qty.
Q 3	Q 2 0336400000	50
	Q 3 0336500000	50
	Q 4 0336600000	50
	Q 10 0368600000	20
	QB 2* 0482700000	100
	QB 3* 0482800000	50
	QB 4* 0482900000	50

Type	Cat. No.	Qty.
Q 3	Q 2 0336400000	50
	Q 3 0336500000	50
	Q 4 0336600000	50
	Q 10 0368600000	20
	QB 2* 0482700000	100
	QB 3* 0482800000	50
	QB 4* 0482900000	50
	QB 25 blank* 0134000000	20

Test plug/socket

Type	Cat. No.	Qty.
StB	StB 8.5 (ø23) 0215700000	50
PS	PS 2.3 0180400000	20

Type	Cat. No.	Qty.
StB	StB 8.5 (ø23) 0215700000	50
PS	PS 2.3 0180400000	20

Type	Cat. No.	Qty.
StB	StB 8.5 (ø23) 0215700000	50
PS	PS 2.3 0180400000	20

Type	Cat. No.	Qty.
StB	StB 8.5 (ø2.3) 0215700000	50
PS	PS 2.3 0180400000	20

Type	Cat. No.	Qty.
StB	StB 8.5 (ø2.3) 0215700000	50
PS	PS 2.3 0180400000	20

Type	Cat. No.	Qty.
FW/FS	dekafix 6 see "Accessories"	

Type	Cat. No.	Qty.
FW/FS	dekafix 6 see "Accessories"	

Type	Cat. No.	Qty.
FW/FS	dekafix 6 see "Accessories"	

Type	Cat. No.	Qty.
FW/FS	dekafix 6 see "Accessories"	

Type	Cat. No.	Qty.
FW/FS	dekafix 6 see "Accessories"	

Mounting rails, end brackets, further marking material see "Accessories"

* The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used.
** Only to be used with PA-version


¹⁾ Shock-proof with ADP4 cover profile (see section "Accessories")

Feed-through terminals and disconnect test terminals


with solder connection

SAK 2.5/M.LS


With screen lug



SAK 2.5 L SAK 2.5 L/35



SAK 2.5 LL SAK 2.5 LL/35



SAKR L SAKR L/35

Disconnect terminal



Dimensions/approvals

Width/length/height (mm)	with TS 32	
Width/length/height (mm)	with TS 35 x 7.5	
Insulation stripping length/clamping screw/screwdriver blade		

Rated data

Rated voltage/current/cross-section	250 V/20 A/2.5/1.5 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity	4 kV/3

Further technical data

Tightening torque range	Nm	0.4...0.7
Torque setting with electric screwdriver type DMS 2		1

Clampable conductor

Solid H07V-U	mm ²	0.5...6
Stranded H07V-R	mm ²	0.5...2.5
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46 228/1	mm ²	0.5...2.5
Plug gauge according to 60 947-7-1	Size	A 3

Continuous current of terminal block for conductor size		
Continuous current rating of cross-connection 2-pole	A	(Q 2...10) 24
Continuous current rating of cross-connection multipole	A	

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/10 A/22...12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/22...12 AWG

Ordering data

Type	Cat. No.	Qty.
KrG	0309120000	100
Blue KrG		
KrS		
PA		
Blue PA		
KrG		
PA		
Blue PA		

Type	Cat. No.	Qty.
KrG	0309120000	100
Blue KrG	0351470000	100
KrS		
PA		
Blue PA		
KrG		
PA		
Blue PA		

Type	Cat. No.	Qty.
KrG	0351420000	100
Blue KrG	0351470000	100
KrS		
PA		
Blue PA		
KrG		
PA		
Blue PA		

Type	Cat. No.	Qty.
KrG	0323620000	100
Blue KrG	0323670000	100
KrS		
PA		
Blue PA		
KrG		
PA		
Blue PA		

Type	Cat. No.	Qty.
KrG	0412360000	100
Blue KrG	0412380000	100
KrS		
PA		
Blue PA		
KrG		
PA		
Blue PA		

End plate/partition (thickness mm)

Type	Cat. No.	Qty.
AP (1.5)	0309220000	20
Blue AP (1.5)	0309270000	20
PA		
Blue PA		
PA	0302860000	20
HP	0297100000	20
HP	0607000000	20



Type	Cat. No.	Qty.
AP (1.5)	0309220000	20
Blue AP (1.5)	0309270000	20
PA		
Blue PA		
PA	0302860000	20
HP	0297100000	20
HP	0607000000	20

Type	Cat. No.	Qty.
AP (1.5)	0309220000	20
Blue AP (1.5)	0309270000	20
PA		
Blue PA		
PA	0302860000	20
HP	0297100000	20
HP	0607000000	20

Type	Cat. No.	Qty.
AP (1.5)	0309220000	20
Blue AP (1.5)	0309270000	20
PA		
Blue PA		
PA	0302860000	20
HP	0297100000	20
HP	0607020000	20

Type	Cat. No.	Qty.
AP (1.5)	0211360000 ¹⁾	20
Blue AP (1.5)	0211380000	20
PA		
Blue PA		
PA	0412460000 [*]	100
HP	0412480000 [*]	100

Small partition

TSch 1	0319160000	100
--------	-------------------	-----



TSch 1	0319160000	100
--------	-------------------	-----

TSch 1	0319160000	100
--------	-------------------	-----

Cross-connection

Type	Cat. No.	Qty.
Q 2	0337000000	50
Q 3	0337100000	50
Q 4	0337200000	50
Q 10	0368700000	20
25-pole		



Q 2	0337000000	50
Q 3	0337100000	50
Q 4	0337200000	50
Q 10	0368700000	20

Q 2	0337000000	50
Q 3	0337100000	50
Q 4	0337200000	50
Q 10	0368700000	20

Q 2	0337000000	50
Q 3	0337100000	50
Q 4	0337200000	50
Q 10	0368700000	20

QB 2**	0482700000	100
QB 3**	0482800000	50
QB 4**	0482900000	50
QB 25 blank**	0134000000	20

Test plug/socket

StB	Plug-test socket without using QL
PS	Plug-test-socket for use with QL



StB 8.5(ø23)	0280600000	50
StB 29.5(ø4)	0133400000	50
PS 2.3	0180400000	20
PS 4	0299600000	20

StB 8.5(ø23)	0280600000	50
StB 29.5(ø4)	0133400000	50
PS 2.3	0180400000	20
PS 4	0299600000	20

StB 8.5(ø23)	0280600000	50
StB 29.5(ø4)	0133400000	50
PS 2.3	0180400000	20
PS 4	0299600000	20

PS 2.3	0180400000	20
--------	-------------------	----

Cover


AD 4	0303400000	50
BSK M3x22	0128900000	100

AD 4	0303400000	50
BSK M3x22	0128900000	100

AD 4	0303400000	50
BSK M3x22	0128900000	100

Marking tags

DEK	Standard	DEK 6	see "Accessories"
-----	----------	-------	-------------------



DEK 6	see "Accessories"
-------	-------------------

DEK 6	see "Accessories"
-------	-------------------

DEK 6.5	see "Accessories"
---------	-------------------

Mounting rails, end brackets, further marking material see "Accessories"

* Soldering lug on left-hand side

** The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used.

¹⁾ For TS 32 and TS 35

²⁾ Contact-proof cross-connection with ADP 4 cover profile (see "Accessories")

Disconnect test terminals with solder connections


SAKR L

With 2 StB 6



SAKR LL

With 2 StB 6



SAKR LL

With 2 StB 6



Dimensions/approvals

Width/length/height (mm)	with TS 32	
Width/length/height (mm)	with TS 35 x 7.5	
Insulation stripping length/clamping screw/screwdriver blade		

Rated data

Rated voltage/current/cross-section	250 V/10 A/4/1.5 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity	4 kV/3

Further technical data

Tightening torque range	Nm	0.5...1.0
Torque setting with electric screwdriver type DMS 2		1

Clampable conductor

Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46228/1		
With/without plastic insulating collar	mm ²	0.5...4
Plug gauge according to 60 947-7-1	Size	A 3

Continuous current of terminal block for conductor size		
Continuous current rating of cross-connection 2 pole	A	(QB 2...25) 10
Continuous current rating of cross-connection multipole	A	

Rated data according to UL/CSA

Voltage/current/conductor size	UL
Voltage/current/conductor size	CSA

Ordering data

Type	Qty.
KrG	
Blue KrG	
KrS	
PA	0518160000*100 0183560000 100
Blue PA	
KrG	
KrS	
PA	0572660000 100
Blue PA	

6.5/50/40.5/54.5 (opened)

8 mm/M 3/3.5 x 0.6

250 V/10 A/4/1.5 mm²

4 kV/3

0.5...1.0

1

0.5...4

1.5...4

0.5...4

0.5...4

A 3

(QB 2...25) 10

A



6.5/58/40.5/54.5 (opened)

250 V/10 A/1.5 mm²

4 kV/3

300 V/10 A/22...12 AWG

Qty.

6.5/58/40.5/54.5 (opened)

250 V/10 A/1.5 mm²

4 kV/3

Qty.

End plate/partition (thickness mm)

Type	Cat. No.	Qty.
AP		
TW		
KrG		
Blue KrG		
PA	AP (1.5) 0211360000 20	
Blue PA	AP (1.5) 0211380000 20	
PA		
HP	TW (0.5) 0474700000 20	
HP	TW (2.0) 0607000000 20	



Type Cat. No. Qty.

KrG

Blue KrG

PA

Blue PA

PA

HP

HP

Type Cat. No. Qty.

AP (1.5) 0211320000 20

AP (1.5) 0211360000 20

AP (1.5) 0211380000 20

TW (0.5) 0474700000 20

TW (2.0) 0607000000 20

Type Cat. No. Qty.

AP (1.5) 0211320000 20

AP (1.5) 0211360000 20

AP (1.5) 0211380000 20

TW (0.5) 0474700000 20

TW (2.0) 0607000000 20

Small partition



Cross-connection


Type	Cat. No.	Qty.
QB 3		
QB 4		
2-pole	QB 2** 0482700000 100	
3-pole	QB 3** 0482800000 50	
4-pole	QB 4** 0482900000 50	
10-pole		
25-pole	QB 25 blank** 0134000000 20	

Test plug/socket

Type	Cat. No.	Qty.
PS		
PS 2.3	0180400000 20	
PS 2.3	0180400000 20	

Marking tags

Type	Cat. No.	Print
DEK		Standard
DEK 6.5	see "Accessories"	
DEK 6.5	see "Accessories"	
DEK 6.5	see "Accessories"	



Mounting rails, end brackets, further marking material see "Accessories"

* Soldering lug on left-hand side

** The conductor cross-section for the screw connection is reduced to 2.5 mm² when QB is used.

Disconnect test terminals with solder connections

TAL
2 solder connections

TAL
4 solder connections

SAKK 4
Ceramic feed-through terminals for use in high temperature ranges up to max. 210°C

SAKK 10



Dimensions/approvals

Width/length/height (mm) with TS 32 with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade

4/48/36/50 (opened)

4/54/36/50 (opened)

8/40/53

11.5/40/53

Rated data

Rated voltage/current/cross-section
Rated impulse voltage VDE 0110/1.89/pollution severity

63 V/10 A/1.5 mm²
1.5 kV/3

63 V/10 A/1.5 mm²
1.5 kV/3

800 V/32 A/4 mm²

800 V/57 A/10 mm²

Further technical data

Tightening torque range Nm
Torque setting with electric screwdriver type DMS 2

Nm

0.5...1

1.2...2

Clampable conductor

Solid H07V-U mm²
Stranded H07V-R mm²
Flexible H07V-K mm²
Flexible H07V-K and ferrule according to DIN 46 228/1 mm²
Plug gauge according to 60 947-7-1 Size

0.5...6 mm²

2.5...16 mm²

0.5...4 mm²

2.5...10 mm²

A 4

B 6

35 A/6 mm²

63 A/16 mm²

36

47

36

36

Rated data according to UL/CSA

Voltage/current/conductor size UL
Voltage/current/conductor size CSA

Ordering data

Type Cat. No. Qty.
KrG
Blue KrG
KrS
PA **0212060000** 100
Blue PA
KrG
KrS
PA
Blue PA
Ceramic

Cat. No. Qty.

Cat. No. Qty.

Cat. No. Qty.

Cat. No. Qty.

End plate/partition (thickness mm)

AP TW

KrG
Blue KrG
PA
Blue PA
PA

Type Cat. No. Qty.

Type Cat. No. Qty.

SAKK 4 **1598080000** 50

SAKK 10 **1598090000** 50

AP/SAKK 4/10 **9502630000** 10

AP/SAKK 4/10 **9502630000** 10

AP (1.5) **0212260000** 20

AP (1.5) **0212260000** 20

Small partition

Cross-connection

Q 3 QB 4

2-pole
3-pole
4-pole
10-pole
25-pole

Type Cat. No. Qty.

Type Cat. No. Qty.

QL 2 **9509420000** 100

QL 2 **9509470000** 100

QL 3 **9509430000** 100

QL 3 **9509480000** 50

QL 4 **9509440000** 50

QL 4 **9509490000** 50

QL 10 **9509450000** 20

QL 10 **9509500000** 20

VH 13.5 **0248500000** 100

VH 12.5 **9509510000** 50

BS (M3 X 20) **0303000000** 100

BS (M3 X 20) **0303000000** 100

Additional accessories

SST **0152700000**

SST **0152700000**

MEW 1/32 **0445600000**

MEW 1/32 **0445600000**

EK 2 **0323100000**

EK 2 **0323100000**

Marking tags

DEK Standard On demand

On demand


On demand

Mounting rails, end brackets, further marking material see "Accessories"

SAK-series


Feed-through terminals for initiators and actuators

DLI 2.5




6/65/49	6/65/49
7 mm/M 2.5/3.5 x 0.6	7 mm/M 2.5/3.5 x 0.6

DLI 2.5 LD PNP



6/65/49	6/65/49
7 mm/M 2.5/3.5 x 0.6	7 mm/M 2.5/3.5 x 0.6

DLI 2.5 LD NPN



6/65/49	6/65/49
7 mm/M 2.5/3.5 x 0.6	7 mm/M 2.5/3.5 x 0.6

DLD 2.5



6/82/49	6/82/49
7 mm/M 2.5/3.5 x 0.6	7 mm/M 2.5/3.5 x 0.6

Dimensions/approvals

Width/length/height (mm)	with TS 35 x 7.5
Insulation stripping length/clamping screw/screwdriver blade	

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	250 V/20 A/2.5 mm ²
Rated impulse voltage/pollution severity	4 kV/3

Further technical data

Tightening torque range	Nm	0.4...0.6
Torque setting with electric screwdriver type DMS 2		1

Clampable conductor

Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	0.5...2.5
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule according to DIN 46228/1	mm ²	0.5...2.5
Plug gauge according to 60 947-7-1	Size	A 3
Continuous current of terminal for conductor size		20 A/2.5 mm ²
Continuous current rating of cross-connection 2...5-pole	A	(Q 2...10) 20
Continuous current rating of cross-connection 6...10-pole	A	(Q 2...10) 20

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/10 A/26...12 AWG
Voltage/current/conductor size	CSA	300 V/10 A/26...12 AWG

Ordering data

Standard			
with diode 1N4007			
with LED red (5...30 V)			
with LED green (5...30 V)			
with LED and diode 1N4007			
with LED and diode 1N4007			
Block of 10 ¹⁾	(w/o)	1411360000	10
Block of 10 ¹⁾	(with dekafix)	1579070000	10
Fuse inserts			

End plate/Small partition

AP-DLI	AP-DLD	Part-AP	TSch 1
			(thickness 1.5 mm)

Test plug/plug socket

StB 8.5	PS
StB 8.5 (ø23)	0215700000 50
PS 2.3	0180400000 20

Cross-connection

Q 2	1312500000 50
Q 3	1312600000 50
Q 4	1312700000 50
Q 10	1313100000 20
Q 20	1399800000 20
QL 2	0297200000 100
VH 4.2	1345800000 100
VQB1.5/50BL	1633280000 5
VQB1.5/50RT	1633290000 5
VQB1.5/50SW	1635120000 5

VQB

Snap fit, external cross-connection VQB 1.5.	For cross-connections for more than 20 terminals, replace VH with VH 4.2 (134580) without internal thread
--	---

Group marking

WT 4	1341060000 100
SF 10	0332400000 1000
SG 10	0332500000 1000

Cover

HP 4	0485400000 20
HP 4	0485860000 20

Marking tags


1	2	3	4	5	6	DEK	Standard
---	---	---	---	---	---	-----	----------

Mounting rails, end brackets, further marking material see "Accessories"

1) DLI 2.5/35/10 = Block of 10 with built-in cross-connections * only in upper busbar

Feed-through terminals for initiators and actuators

DLA 2.5



6/65/49
7 mm/M 2.5/3.5 x 0.6

250 V**/17.5 A/2.5 mm ²
4 kV/3
0.4...0.6
1
0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm ²
(Q 2...20) 20

300 V/10 A/26...12 AWG
300 V/10 A/26...12 AWG
Cat. No. Qty.
1565970000 100

(w. dekafix) 1578380000 10
(w/o dekafix) 1578390000 10

Type	Cat. No.	Qty.
AP	1313260000	20
TSch 1	0319160000	100

StB8.5*(ø23) 0215700000 50
PS 2.3 0180400000 20


Q 2 1312500000 50
Q 3 1312600000 50
Q 4 1312700000 50
Q 10 1313100000 20
Q 20 1399800000 20

QL 2 0297200000 100
VH 4.2 1345800000 100
VQB1.5/50 BL 1633280000 5
VQB1.5/50 RT 1633290000 5
VQB1.5/50 SW 1635120000 5

WT 4 1341060000 100
SF 10 0332400000 1000
SG 10 0332500000 1000
ADP 0485400000 20
HP 4 0485860000 20

DEK 6 see "Accessories"

DLA 2.5/D



6/65/49
7 mm/M 2.5/3.5 x 0.6

250 V**/17.5 A/2.5 mm ²
4 kV/3
0.4...0.6
1
0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm ²
(Q 2...20) 20

300 V/10 A/26...12 AWG
300 V/10 A/26...12 AWG
Cat. No. Qty.
1578400000 100

Type	Cat. No.	Qty.
AP	1313260000	20
TSch 1	0319160000	100

StB8.5*(ø23) 0215700000 50
PS 2.3 0180400000 20


Q 2 1312500000 50
Q 3 1312600000 50
Q 4 1312700000 50
Q 10 1313100000 20
Q 20 1399800000 20

QL 2 0297200000 100
VH 4.2 1345800000 100
VQB1.5/50 BL 1633280000 5
VQB1.5/50 RT 1633290000 5
VQB1.5/50 SW 1635120000 5

WT 4 1341060000 100
SF 10 0332400000 1000
SG 10 0332500000 1000
ADP 0485400000 20
HP 4 0485860000 20

DEK 6 see "Accessories"

DLA 2.5/LD



6/65/49
7 mm/M 2.5/3.5 x 0.6

5-30 V/17.5 A/2.5 mm ²
0.8 kV/3
0.4...0.6
1
0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm ²
(Q 2...20) 20

300 V/10 A/26...12 AWG
5-30 V/10 A/26...12 AWG
Cat. No. Qty.
1578430000 100
1578440000 100

Type	Cat. No.	Qty.
AP	1313260000	20
TSch 1	0319160000	100

StB8.5*(ø23) 0215700000 50
PS 2.3 0180400000 20

Q 2 1312500000 50
Q 3 1312600000 50
Q 4 1312700000 50
Q 10 1313100000 20
Q 20 1399800000 20

QL 2 0297200000 100
VH 4.2 1345800000 100
VQB1.5/50 BL 1633280000 5
VQB1.5/50 RT 1633290000 5
VQB1.5/50 SW 1635120000 5

WT 4 1341060000 100
SF 10 0332400000 1000
SG 10 0332500000 1000
ADP 0485400000 20
HP 4 0485860000 20

DEK 6 see "Accessories"

DLA 2.5/LD/D



6/65/49
7 mm/M 2.5/3.5 x 0.6

5-30 V/17.5 A/2.5 mm ²
0.8 kV/3
0.4...0.6
1
0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm ²
(Q 2...20) 20

300 V/10 A/26...12 AWG
5-30 V/10 A/26...12 AWG
Cat. No. Qty.
(LED red) 1578470000 100
(LED green) 1578480000 100
(LED red) 1578490000 10
(LED green) 1578500000 10

Type	Cat. No.	Qty.
AP	1313260000	20
TSch 1	0319160000	100

StB8.5*(ø23) 0215700000 50
PS 2.3 0180400000 20

Q 2 1312500000 50
Q 3 1312600000 50
Q 4 1312700000 50
Q 10 1313100000 20
Q 20 1399800000 20

QL 2 0297200000 100
VH 4.2 1345800000 100
VQB1.5/50 BL 1633280000 5
VQB1.5/50 RT 1633290000 5
VQB1.5/50 SW 1635120000 5

WT 4 1341060000 100
SF 10 0332400000 1000
SG 10 0332500000 1000
ADP 0485400000 20
HP 4 0485860000 20

DEK 6 see "Accessories"

DLD 2.5/PE



6/74.5/49
7 mm/M 2.5/3.5 x 0.6

250 V**/17.5 A/2.5 mm ²
4 kV/3
0.4...0.6
1
0.5...4
0.5...2.5
0.5...4
0.5...2.5
A 3
20 A/2.5 mm ²
(Q 2...20) 20

300 V/10 A/26...12 AWG
300 V/10 A/26...12 AWG
Cat. No. Qty.
1595950000 100

Type	Cat. No.	Qty.
AP	1595960000	20
AP (Part-AP)	1595970000	
TSch 1	0319160000	100

StB8.5*(ø23) 0215700000 50
PS 2.3 0180400000 20


Q 2 1312500000 50
Q 3 1312600000 50
Q 4 1312700000 50
Q 10 1313100000 20
Q 20 1399800000 20

QL 2 0297200000 100
VH 4.2 1345800000 100
VQB1.5/50 BL 1633280000 5
VQB1.5/50 RT 1633290000 5
VQB1.5/50 SW 1635120000 5

WT 4 1341060000 100
SF 10 0332400000 1000
SG 10 0332500000 1000
ADP 0485400000 20
HP 4 0485860000 20

DEK 6 see "Accessories"

KDKS1/PE



8/91/65
8 mm/M 3 ² /M 2.5 ³ /3.5 x 0.6

500 V/6.3 A/4 mm ²
6 kV/3
0.5...1 ² /0.4...0.7 ³
2/1 ^{***}
0.5...4
0.5...4
0.5...4
0.5...4
A 4 ² / A 3 ³

-/22...12 AWG
Cat. No. Qty.
9528110000 50

not combine with
DLI / DLA
Wemid **9532450000** 50

5 x 20 without core indicator		
Type	Cat. No.	Qty.
AP	9503330000	50
AP Wemid	9532470000	50

StB8.5*(ø23) 0215700000 50
PS 2.3 0180400000 20

QB 2 0461100000 50
QB 3 0461200000 50
QB 4 0461300000 50


** If the cross-connection runs via the PE connection of the DLA, or if a pole is generally skipped, the rated voltage is reduced to 30 V-
²) A4 clamping position = max 4 mm² ... ³) A3 clamping position = max 2.5 mm² ... ferrule with/without plastic insulating collar

Feed-through terminals for initiators and motors

VLI 1.5



VLI 1.5PE





MAK 2.5




Dimensions/approvals

Width/length/height (mm) with TS 35 x 7.5 
 Insulation stripping length/clamping screw/screwdriver blade

 6/79/64
 8 mm/M 2.5/3.5 x 0.6

 6/69/63
 8 mm/M 2.5/3.5 x 0.6

 6/88/64
 8 mm/M 2.5/3.5 x 0.6

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section

250 V/17.5 A/1.5 mm²

250 V/17.5 A/1.5 mm²

500 V (L-L)/250 V (L-PE)

Rated impulse voltage/pollution severity

4 kV/3

4 kV/3

6 kV/3

Further technical data

Tightening torque range Nm

0.4...0.6**

0.4...0.6

0.4...0.6

Torque setting with electric screwdriver type DMS 2

1

1

1

Clampable conductor

Solid H07V-U mm²

0.5...4.0

0.5...4.0

0.5...4.0

Stranded H07V-R mm²

0.5...2.5

0.5...2.5

0.5...2.5

Flexible H07V-K mm²

0.5...4

0.5...4

1.5...4

Flexible H07V-K and ferrule DIN 46 228/1 mm²

0.5...2.5

0.5...2.5

0.5...2.5

Flexible H07V-K and ferrule with plastic insul. collar mm²

0.5...2.5

0.5...2.5

0.5...2.5

Plug gauge according to 60 947-7-1 Size

A3

A3

A3

Continuous current of terminal for conductor size

24 A/2.5 mm²

24 A/2.5 mm²

24 A/4 mm²

Continuous current rating of cross-connection, multipole A

24

24

24

Rated data according to UL/CSA

Voltage/current/conductor size UL

300 V/10 A/26...12 AWG

300 V/10 A/26...12 AWG

300 V/10 A/26...12 AWG

Voltage/current/conductor size CSA

300 V/10 A/26...12 AWG

300 V/10 A/26...12 AWG

300 V/10 A/26...12 AWG

Ordering data

Version

 Cat. No. Qty.


 Cat. No. Qty.

 Cat. No. Qty.

PA **1633250000** 50

1633310000 50

1615270000 50

 **1631650000** 50

End plate/partition

End plate

Type Cat. No. Qty.
 AP VLI1.5 **1633260000** 20

Type Cat. No. Qty.
 APVLI1.5/PE **1633320000** 20

Type Cat. No. Qty.
 AP MAK2.5 **1615280000** 20

Partial end plate for VLI1.5 – MAK2.5 combination

TEAP2 MAK2.5 **1633330000** 20

TEAP VLI1.5 **1633270000** 20

TEAP2 MAK2.5 **1633330000** 20

Partial end plate for VLI1.5 – VLI1.5PE combination

TEAP VLI1.5 **1633270000** 20

TEAP1 MAK2.5 **1633340000** 20

TEAP1 MAK2.5 **1633340000** 20

Partial end plate for VLI1.5PE – MAK2.5 combination

Cross-connection

VQB 50-pole, snap-fit, external cross-connection

VQB1.5/50BL* **1633280000** 5

VQB1.5/50BL* **1633280000** 5

VQB1.5/50BL* **1633280000** 5

VQB1.5/50RT* **1633290000** 5

VQB1.5/50RT* **1633290000** 5

VQB1.5/50RT* **1633290000** 5

VQB1.5/50SW* **1635120000** 5

VQB1.5/50SW* **1635120000** 5

VQB1.5/50SW* **1635120000** 5



QB 25-pole external cross-connection

QB 25 SW* **0520000000** 20

QB 25 RT* **0520060000** 20

QB 25 BL* **0520080000** 20


Group marking

Tag carrier

for S 10 tags

Marking tags

Print



DEK

Standard

T 5 **0348500000** 100

T 5 **0348500000** 100

T 5 **0348500000** 100

SF 10 **0332400000**1000

SF 10 **0332400000**1000

SF 10 **0332400000**1000

SG 10 **0332500000**1000

SG 10 **0332500000**1000

SG 10 **0332500000**1000

DEK 5 see "Accessories"

DEK 5 see "Accessories"

DEK 5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* When using cross-connection bridges, the connected cross-section is reduced by one level
 ** 0.4...0.45 for lower connection level

Disconnect test terminal against induced high voltage

PPT/35



SAKH 6



Measures to minimize risks of electric voltage peaks in control systems of power plants and transforming stations:

- Insulation between installation and control cable by pulling disconnect plugs.
- Grounding of control cable is possible on an appropriate location of the workplace.
- Easy connection of electric isolation of counting, control and communication circuits.

Electricity Supply Industry Standard ESI 12-4 1973

The Electricity Supply Industry Standard ESI 12-4 1973 defines a detailed specification of control and protection equipment. The main functions of these installations are as follows:

- Insulation of the control cables located in front of ground or installation lines with increased potential, which is required to prevent unintentional contact of service staff with live parts.
- Separation of control cables from local control circuits.
- Application also includes test connections for auxiliary control circuits and / or local control circuits.
- Grounding of control cables and / or auxiliary control circuits.
- Bundled disconnection of all auxiliary control circuits from potential earth.
- A test voltage can be applied using the screening connection of the control cable, which is normally routed on the enclosure, with the help of an appropriate separation. This permits to check whether the screening line is correctly functioning. For this test, an insulated feed-through plate is required.

ESI 12-4:

"Terminating Equipment for Pilot Cables subject to Induced Transient Voltages exceeding 650 V rms".

Dimensions/approvals		PPT/35		SAKH 6		
Width/length/height (mm)	with TS 35 x 7.5	15/138/79				
Insulation stripping length/clamping screw/screwdriver blade		12 mm			12 mm	
Rated data according to IEC 60 947-7-1						
Rated voltage/current		15 kV ac (ESI 12-4)**/30 A		1 kV ac / 1.5 kV dc / 47 A		
Rated impulse voltage/pollution severity				>15 kV (from terminal to terminal)		
Clampable conductor						
Solid H07V-U	mm ²	0.5...10		0.5... 6		
Stranded H07V-R	mm ²	0.5...10*		0.5... 6		
Ordering data		Version	Cat. No.	Qty.	Cat. No.	Qty.
		EP	PPT/35 3835020000	10	SAKH 6 0126600000	50
			incl. disconnect plug and displacement tool (if min. 10 items are ordered)			
End plate		EP	AP/PPT (3) 3835120000	10	AP	0131700000 20
Disconnect plug			TST/PPT 3835360000	10		
Displacement tool		PA	PH/PPT 3835260000	10		
			The disconnect plug may only be removed with the displacement tool.			
Test plug/socket			PS (4) 0299600000	20		
			StB 17 0147100000	50		
Insulated mounting rail		PVC 35 x 1.5 mm	TSK 35 0514300000	1		
Marking tags		Print				
	DEK	Standard	DEK 5 see "Accessories"		DEK 5 see "Accessories"	

DEK Standard

DEK 5 see "Accessories"

DEK 5 see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

SAK-series

* Also two push-on tabs are possible
** mounted on an insulated mounting rail

Rail mounting TS 15

Feed-through terminals
Protective conductor terminals
Fuse terminals
Disconnect test terminals

AKZ 1.5
AKZ 1.5/10



AKZ 2.5



AKZ 4
AKZ 4/10
AKZ 4 Wemid



AKZ 4 for test adapter
AKZ 4/10 for test adapter



Max. technical data

Dimensions/approvals	
Width/length/height (mm)	with TS 15

Insulation stripping length/clamping screw/screwdriver blade

Rated data VDE 0611 Part 1/8.92/IEC 60 947-7-1	
Rated voltage/current/cross-section	250 V/17.5 A/1.5 mm ²
Rated impulse voltage / pollution severity	4 kV/3

Further technical data

Tightening torque range	Nm	0.4...0.6
Torque setting with electric screwdriver type DMS 2		1

Clampable conductor

Solid H07V-U	mm ²	0.5...2.5
Stranded H07V-R	mm ²	1.5
Flexible H07V-K	mm ²	0.5...1.5
Flexible H07V-K and ferrule DIN 46 228/1	mm ²	0.5...1.5
Flexible H07V-K and ferrule with plastic insul. collar	mm ²	0.5...1.5
Max. clamping range in mm ² /plug gauge acc. to IEC 60 947-1		0.2...2.5 / A 1

Continuous current rating of cross-connection 2-pole	A	24
Continuous current rating of cross-connection multipole	A	24

Rated data according to UL/CSA

Voltage/current/conductor size	UL	150 V/15 A/22...14 AWG
Voltage/current/conductor size	CSA	300 V/10 A/24...16 AWG

Ordering data

Type	Cat. No.	Qty.
KrG		
PA	0340460000	100
Blue PA	0340480000	100
PA	(10pol./no.mk.) 0358060000	10
PA	(10pol./w.mk.) 0358160000	10

21.5 A / 2.5 mm ²	
5/25/25	

7 mm/M 2.5/3.0 x 0.5

250 V/17.5 A/1.5 mm ²	
4 kV/3	

0.4...0.6	
1	

0.5...2.5	
1.5	
0.5...1.5	
0.5...1.5	
0.5...1.5	
0.2...2.5 / A 1	

24	
24	

Rated data according to UL/CSA

150 V/15 A/22...14 AWG	
300 V/10 A/24...16 AWG	

Ordering data

Type	Cat. No.	Qty.
	TS 15	

26 A / 4 mm ²	
5/25.5/28	

7 mm/M 2.5/3.0 x 0.5

250 V/24 A/2.5 mm ²	
4 kV/3	

0.4...0.6	
1	

0.5...4	
1.5...2.5	
0.5...4	
0.5...2.5	
0.5...2.5	
0.13...4.0 / A 3	

24	
24	

Rated data according to UL/CSA

300 V/10 A/26...12 AWG	
300 V/10 A/26...12 AWG	

Ordering data

Type	Cat. No.	Qty.
	TS 15	
	(with pin)	0697160000 100
	(with pin)	0697180000 100
	(without pin)	0175960000 100
	AKZ 2.5 w. AP	0385860000 50

38.5 A / 6 mm ²	
6/27/30	

8 mm/M 3/3.5 x 0.6

400 V/32 A/4 mm ²	
6 kV/3	

0.5...1.0	
2	

0.5...6	
1.5...4	
0.5...4	
0.5...4	
0.5...4	
0.2...6.0 / A 3	

32	
32	

Rated data according to UL/CSA

300 V/27A/22...12 AWG	
300 V/10 A/24...12 AWG	

Ordering data

Type	Cat. No.	Qty.
	TS 15	
		0294320000 100
		0294360000 100
		0294380000 100
	(10pol./no.mk.)	0359560000 10
	(10pol./w.mk.)	0359660000 10
	AKZ 4 Wemid	9537110000 100

38.5 A / 6 mm ²	
60/27/30	

9 mm/M 3/3.5 x 0.6

500 V/32 A/4 mm ²	
6 kV/3	

0.5...1.0	
2	

0.5...6	
1.5...4	
0.5...4	
0.5...4	
0.5...4	
0.2...6.0 / A 3	

32	
32	

Rated data according to UL/CSA

300V/27 A/22...12 AWG	
300 V/10 A/24...12 AWG	

Ordering data

Type	Cat. No.	Qty.
	TS 15	
		for test adapter 1538260000 100
	w.mk./f.test ad.	1489360000 10
	ATA1,10-pole	1633240000 5

End plate (thickness mm)

Type	Cat. No.	Qty.
KrG		
Wemid		
PA	AP (1.5)	0340560000 50
Blue PA		

Partition (thickness mm)

Type	Cat. No.	Qty.
KrG		
PA		
Blue PA		

Small partition

Type	Cat. No.	Qty.
PA		

Cross-connection

Type	Cat. No.	Qty.
Q 2	0368200000	50
Q 3	0368300000	50
Q 4	0368400000	50
Q 5	0660300000	20
Q 10	0368500000	20

Switchable cross-connection link

Type	Cat. No.	Qty.
VL		
BS		
VH		

Cover/Profiled material for covers for finger-safety*

Type	Cat. No.	Qty.

Test plug/socket

Type	Cat. No.	Qty.
StB	StB 8.5	0215700000 50
PS		
K sleeve	PS 2.3	0180400000 20

Marking tags

Type	Cat. No.	Qty.
DEK	DEK 5	see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* not for terminals made from PA

End plate (thickness mm)

Type	Cat. No.	Qty.
KrG		
Wemid		
PA	AP (2.5)	0697360000 50
Blue PA	AP (2.5)	0697380000 50

Partition (thickness mm)

Type	Cat. No.	Qty.
KrG		
PA		
Blue PA		

Small partition

Type	Cat. No.	Qty.
PA		

Cross-connection

Type	Cat. No.	Qty.
Q 2	0368200000	50
Q 3	0368300000	50
Q 4	0368400000	50
Q 5	0660300000	20
Q 10	0368500000	20

Switchable cross-connection link

Type	Cat. No.	Qty.
VL		
BS		
VH		

Cover/Profiled material for covers for finger-safety*

Type	Cat. No.	Qty.

Test plug/socket

Type	Cat. No.	Qty.
StB	StB 8.5	0215700000 50
PS		
K sleeve	PS 2.3	0180400000 20

Marking tags

Type	Cat. No.	Qty.
DEK	DEK 5	see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* not for terminals made from PA

End plate (thickness mm)

Type	Cat. No.	Qty.
KrG		
Wemid		
PA	AP (1.5)	0294420000 20
Blue PA	AP (1.5)	0294480000 20

Partition (thickness mm)

Type	Cat. No.	Qty.
KrG		
PA		
Blue PA		

Small partition

Type	Cat. No.	Qty.
PA		

Cross-connection

Type	Cat. No.	Qty.
Q 2	0336400000	50
Q 3	0336500000	50
Q 4	0336600000	50
Q 10	0368600000	20

Switchable cross-connection link

Type	Cat. No.	Qty.
VL	VL 2	0446700000 50
VH	VH 10	0446600000 50
BS	BS M 2.5x14	0266800000 100

Cover/Profiled material for covers for finger-safety*

Type	Cat. No.	Qty.

Test plug/socket

Type	Cat. No.	Qty.
StB	StB 8.5	0215700000 50
PS		
K sleeve	PS 2.3	0180400000 20

Marking tags

Type	Cat. No.	Qty.
DEK	DEK 6	see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* not for terminals made from PA

Rail mounting TS 15

AK 4 AK 4/10



38.5 A / 6 mm²

UL **CE**
60/32/34

9 mm/M 3/3.5 x 0.6

690 V/32 A/4 mm²
8 kV/3

0.5...1.0
2

0.5...6
1.5...4

0.5...4
0.5...4

0.5...4
0.2...6.0 / A 3

20
20

TS 15 Cat. No. Qty.

0489560000 100

(10pol./no.mk.) **0366560000** 10
(10pol./w.mk.) **0469560000** 10

Type Cat. No. Qty.

BB 3 (8.0) **0366660000** 50
combined AP + end brackets

TW/AP (1.5) **1331760000** 20

TSch 4 **0363360000** 100

Q 2 **0369000000** 50

Q 3 **0369100000** 50

Q 4 **0369200000** 50

Q 10 **0369300000** 20

AD 4 **0303400000** 50

BSKM 25x18 **0303300000** 100

StB 8.5 **0215700000** 50

PS 2.3 **0180400000** 20

DEK 6 see "Accessories"

AKE 2.5



UL **CE**

5/28/27

7 mm/M 2.5/3.0 x 0.5

IEC 60 947-7-2

-/-/2.5 mm²
4 kV/3

0.4...0.6
1

0.5...4
1.5...2.5

0.5...4
0.5...2.5

0.5...2.5
0.13...4.0 / A 3

TS 15 Cat. No. Qty.

1303360000 100

(green/yellow)

Type Cat. No. Qty.

-/-/26...12 AWG
-/-/26...12 AWG

AKE 4



UL **CE**

7/32/34

9 mm/M 3/3.5 x 0.6

IEC 60 947-7-2

-/-/4 mm²
8 kV/3

0.5...1.0
2

0.5...6
1.5...4

0.5...4
0.5...2.5

0.5...2.5
0.13...4.0 / A 3

TS 15 Cat. No. Qty.

0380260000 100

(green/yellow)

Type Cat. No. Qty.

-/-/22...12 AWG
-/-/26...12 AWG

AKE 4 MS



CE

7/27.5/30

9 mm/M 3/3.5 x 0.6

-/-/4 mm²

0.8...1.6
3

0.5...4
1.5...4

0.5...4
0.5...4

0.5...4
0.5...4.0 / A 3

TS 15 Cat. No. Qty.

0211200000 50

-/-/22...14 AWG

Type Cat. No. Qty.

ASK 1

Fuse terminal



UL **CE**

8/58/34

9 mm/M 3/3.5 x 0.6

500 V/6.3 A¹/4 mm²
6 kV/3

0.5...1.0
2

0.5...4
1.5...4

0.5...4
0.5...2.5

0.5...2.5
0.13...4.0 / A 3

(QB 2...4) 10

300 V/10 A/22...12 AWG

300 V/6.3 A/26...12 AWG

TS 15 Cat. No. Qty.

0376860000 100

5 x 20 without indicator

Type Cat. No. Qty.

AP (1.5) **0380360000** 20

QB 2¹) insul. **0461100000** 50

QB 3¹) insul. **0461200000** 50

QB 4¹) insul. **0461300000** 50

3-pole ganging with tag bar
SchS 2, snapped onto three
disconnect levers
(Cat. No. **0337400000**)

K sleeve **0553300000** 100

DEK 6.5 see "Accessories"

SAKR

Isolating blade terminal with 2 sockets or with 2 clamping screws



6.5/42/45

8 mm/M 3/3.5 x 0.6

400 V²/10 A/4 mm²
6 kV/3

0.5...1.0
2

0.5...4
1.5...4

0.5...4
0.5...4

0.5...4
0.13...4.0 / A 3

(QB 2...4) 10

TS 15 Cat. No. Qty.

with 2 StB **0412860000** 100

w. clamp.screw **0412760000** 100

Type Cat. No. Qty.

AP (1.5) **0211360000** 20

QB 2¹) insul. **0482700000** 50

QB 3¹) insul. **0482800000** 50

QB 4¹) insul. **0482900000** 50

QB 25¹) blank **0134000000** 20

PS 2.3 **0180400000** 20

DEK 6.5 see "Accessories"

¹) The conductor cross-section is * With contact sleeve 19 A reduced to max. 2.5 mm² when QB is used.

²) As disconnect test terminal: rated voltage 250 V

Feed-through terminals for TS 15

Tab connection
Solder connection

AKZ 4 SS

AKZ 4 SS

AKZ 4 S

AKZ 4 SF



Dimensions/approvals	AKZ 4 SS	AKZ 4 SS	AKZ 4 S	AKZ 4 SF
Width/length/height (mm)	with TS 15 6/28.5/30.5	6/28.5/30.5	6/27/30	6/27/30
Insulation stripping length/clamping screw/screwdriver blade			9 mm/M 3/3.5 x 0.6	9 mm/M 3/3.5 x 0.6
Rated data				
Rated voltage*/current/cross-section	400 V/8 A/2.5/1 mm ²	400 V/8 A/1 mm ²	400 V/8 A/4/1 mm ²	400 V/8 A/4/1 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity	6 kV/3	6 kV/3	6 kV/3	6 kV/3
Further technical data				
Tightening torque range	Nm		0.5...1.0	0.5...1.0
Torque setting with electric screwdriver type DMS 2			2	2
Clampable conductor				
Solid H07V-U	mm ²		0.5...4	0.5...4
Stranded H07V-R	mm ²		1.5...4	1.5...4
Flexible H07V-K	mm ²	Tab connec. 6.3 and 2.8 mm	0.5...4	0.5...4
Flexible H07V-K and ferrule DIN 46 228/1	mm ²		0.5...4	0.5...4
Flexible H07V-K and ferrule with plastic insul. collar	mm ²		0.5...4	0.5...4
Max. clamping range in mm ² /plug gauge acc. to IEC 60 947-1 Size			0.2...4/A 3	0.2...4/A 3
Continuous current rating of cross-connection 2-pole	A	20	20	20
Continuous current rating of cross-connection multipole	A	20	20	20
Rated data according to UL/CSA				
Voltage/current/conductor size	UL	150 V/10 A/22...12 AWG	150 V/20 A/22...12 AWG	
Voltage/current/conductor size	CSA	300 V/10 A/24...12 AWG	300 V/10 A/24...12 AWG	300 V/10 A/24...12 AWG
Ordering data	Type	Type	Type	Type
	TS 15	TS 15	TS 15	TS 15
	Cat. No.	Cat. No.	Cat. No.	Cat. No.
	Qty.	Qty.	Qty.	Qty.
	KrG			
	PA	0324560000	0324460000	0158760000
	Blue PA			
	PA			
End plate (thickness mm)	Type	Cat. No.	Qty.	Type
	PA	AP (1.5)	0294460000	20
	PA			
	Blue PA			
	HP			
	HP			
	BB			
Partition (thickness mm)	Type	Cat. No.	Qty.	Type
	PA	TW (0.5)	0348260000	50
	HP			
	HP			
Small partition				
Cross-connection				
	Q 2	0369000000	50	Q 2
	Q 3	0369100000	50	Q 3
	Q 4	0369200000	50	Q 4
	Q 10	0369300000	20	Q 10
Switchable cross-connection link				
	VL 2	0446700000	50	VL 2
	VH 10	0446600000	50	VH 10
	BSM 2.5x14	0266800000	100	BSM 2.5x14
Test plug/socket				
	StB	Plug test socket ø 2.3	StB 8.5	0215700000
	PS		PS 2.3	0180400000
Cover				
Insulation sleeves				
	IH 2.8	0386060000	100	IH 2.8
	IH 6.3	0386260000	100	IH 6.3
Marking tags				
	Print			
	DEK	Standard	DEK 6	see "Accessories"
			DEK 6	see "Accessories"
			DEK 6	see "Accessories"
			DEK 6	see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"				

* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

Feed-through terminals for TS 15

AL 1



6.5/32/21
400 V/16 A/1 mm ²
6 kV/3
0.5...1
0.5...1
TS 15 Cat. No. Qty.
0137320000 100
Type Cat. No. Qty.
AP (1.0) 0164100000 100
EP (1.0) 0164500000 100
TW (0.5) 0166800000 50
TSch 4 0363360000 100
Q 2 0368200000 50
Q 3 0368300000 50
Q 4 0368400000 50
Q 10 0368500000 20
VL 2 0446700000 50
VH 10 0446600000 50
BSM 2.5 x 14 0266800000 100
StB 8.5 0215700000 50
PS 2.3 0180400000 20
AD 4 0303400000 50
BSKM 25x18 0303300000 100
DEK 6.5 see "Accessories"

AKZ 1.5 L



5/34.5/25
7 mm / M 2.5 / 3.0 x 0.5
250 V/16 A/1.5 mm ²
4 kV/3
0.4...0.7
1
0.5...2.5
1.5
0.5...1.5
0.5...1.5
0.5...1.5
0.2...2.5 / A 1
24
24
150 V/10 A/24...16 AWG
TS 15 Cat. No. Qty.
0340160000 100
Type Cat. No. Qty.
AP (1.5) 0329660000 20
TW (0.5) 0166800000 50
Q 2 0368200000 50
Q 3 0368300000 50
Q 4 0368400000 50
Q 10 0368500000 20
StB 8.5 0215700000 50
PS 2.3 0180400000 20
DEK 5 see "Accessories"

AKZ 4 L



6/35.5/30
9 mm / M 3 / 3.5 x 0.6
250 V/16 A/4/1.5 mm ²
4 kV/3
0.5...1.0
2
0.5...4
1.5...4
0.5...4
0.5...4
0.5...4
0.2...4.0 / A 3
20
20
300 V/20 A/22...12 AWG
300 V/10 A/24...12 AWG
TS 15 Cat. No. Qty.
0334820000 100
0334860000 100
Type Cat. No. Qty.
AP (1.5) 0294420000 20
AP (1.5) 0294460000 20
AP (1.5) 0294480000 20
TW (0.5) 0348260000 50
TSch 4 0363360000 100
Q 2 0336400000 50
Q 3 0336500000 50
Q 4 0336600000 50
Q 10 0368600000 20
VL 2 0446700000 50
VH 10 0446600000 50
BSM 2.5 x 14 0266800000 100
StB 8.5 0215700000 50
PS 2.3 0180400000 20
AD 4 0303400000 50
BSKM 25x18 0303300000 100
DEK 6 see "Accessories"

AKZ 4 LL



6/44/30
250 V/16 A/1.5 mm ²
4 kV/3
0.5...1.5
1.5
0.5...1.5
0.2...2.5 / -
20
20
300 V/20 A/22...12 AWG
300 V/10 A/24...12 AWG
TS 15 Cat. No. Qty.
0346460000 100
Type Cat. No. Qty.
AP (1.5) 0294460000 20
TW (0.5) 0348260000 50
TSch 4 0363360000 100
Q 2 0336400000 50
Q 3 0336500000 50
Q 4 0336600000 50
Q 10 0368600000 20
VL 2 0446700000 50
VH 10 0446600000 50
BSM 2.5 x 14 0266800000 100
StB 8.5 0215700000 50
PS 2.3 0180400000 20
AD 4 0303400000 50
BSKM 25x18 0303300000 100
DEK 6 see "Accessories"


Feed-through terminals for TS 15

Solder connection
Spring-clip connection
 acc. to DIN 41611 Part 4
Wrap connection
 acc. to DIN/IEC 352 Part 1

AKZ 1.5 T



AKZ 1.5 T



AKZ 1.5 T



AKZ 2.5 K




Dimensions/approvals	with TS 15	AKZ 1.5 T	AKZ 1.5 T	AKZ 1.5 T	AKZ 2.5 K		
Width/length/height (mm)		5/25/45	5/25/39.5	5/28/44	5/26/46.7		
Pin size		0.8 x 1.6	1 x 1	0.8 x 1.6	0.8 x 1.6		
Insulation stripping length/clamping screw/screwdriver blade		7 mm/M 2.5/3.0 x 0.5	7 mm/M 2.5/3.0 x 0.5	7 mm/M 2.5/3.0 x 0.5	7 mm/M 2.5/3.0 x 0.5		
Rated data							
Rated voltage/current/cross-section		125 V/8 A/1.5 mm ²	125 V/8 A/1.5 mm ²	125 V/8 A/1.5 mm ²	125 V/10 A/2.5 mm ²		
Rated impulse voltage VDE 0110/1.89/pollution severity		2.5 kV/3	2.5 kV/3	2.5 kV/3	2.5 kV/3		
Further technical data							
Tightening torque range	Nm	0.4...0.7	0.4...0.7	0.4...0.7	0.4...0.6		
Torque setting with electric screwdriver type DMS 2		1	1	1	1		
Clampable conductor							
Solid H07V-U	mm ²	0.5...2.5	0.5...2.5	0.5...2.5	0.5...4		
Stranded H07V-R	mm ²	1.5	1.5	1.5	1.5...2.5		
Flexible H07V-K	mm ²	0.5...1.5	0.5...1.5	0.5...1.5	0.5...2.5		
Flexible H07V-K and ferrule DIN 46 228/1	mm ²	0.5...1.5	0.5...1.5	0.5...1.5	0.5...2.5		
Flexible H07V-K and ferrule with plastic insul. collar	mm ²	0.5...1.5	0.5...1.5	0.5...1.5	0.5...2.5		
Max. clamping range in mm ² /plug gauge acc. to IEC 60 947-1	Size	0.13...2.5 / A1	0.13...2.5 / A1	0.13...2.5 / A1	0.13...4.0 / A3		
Continuous current rating of cross-connection 2-pole	A	24	24	24	24		
Continuous current rating of cross-connection multipole	A	24	24	24	24		
Rated data according to UL/CSA							
Voltage/current/conductor size	UL	300 V/10 A/26...14 AWG	300 V/10 A/26...14 AWG	300 V/10 A/26...14 AWG	300 V/10 A/26...14 AWG		
Voltage/current/conductor size	CSA	300 V/10 A/24...16 AWG	300 V/10 A/24...16 AWG	300 V/10 A/24...16 AWG	300 V/10 A/26...10 AWG		
Ordering data	Pin versions	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
	0.6 x 0.6	AKZ 1.5 T	0442560000	100	AKZ 1.5 T	0483660000	100
	1.0 x 1.0	AKZ 1.5 T	0357960000	100	AKZ 1.5 T	0357860000	100
	0.8 x 1.6 horizont.	AKZ 1.5 W	0329460000	100			
	0.8 x 1.6 vertical						
	0.8 x 2.4 horizontal						
	0.8 x 2.4 vertical						
Mounting, horizontal	Mounting, vertical						
End plate (thickness mm)	PA	AP (1.5) 0340560000 50	AP (1.5) 0340560000 50	AP (1.5) 0340560000 50	AP (2.5) 0697260000 50		
Partition (thickness mm)	PA				TW (1.5) 0318560000 20		
Small partition							
Cross-connection							
	2-pole	Q 2 0368200000 50	Q 2 0368200000 50	Q 2 0368200000 50	Q 2 0368200000 50		
	3-pole	Q 3 0368300000 50	Q 3 0368300000 50	Q 3 0368300000 50	Q 3 0368300000 50		
	4-pole	Q 4 0368400000 50	Q 4 0368400000 50	Q 4 0368400000 50	Q 4 0368400000 50		
	10-pole	Q 10 0368500000 20	Q 10 0368500000 20	Q 10 0368500000 20	Q 10 0368500000 20		
Switchable cross-connection link							
	VL						
	BS						
	VH						
Test plug/socket							
	StB	Plug test socket ø 2.3	StB 8.5 0215700000 50	StB 8.5 0215700000 50	StB 8.5 0215700000 50		
	PS		PS 2.3 0180400000 20	PS 2.3 0180400000 20	PS 2.3 0180400000 20		
Marking tags	Print						
	DEK	Standard	DEK 5 see "Accessories"	DEK 5 see "Accessories"	DEK 5 see "Accessories"		
Mounting rails, end brackets, further marking material see "Accessories"							

Feed-through terminals for TS 15

AKZ 2.5 K



AKZ 2.5 K



AKZ 4 T



AKZ 4 T



AKZ 4 T



AKZ 4 ST




AKZ 2.5 K			AKZ 2.5 K			AKZ 4 T			AKZ 4 T			AKZ 4 T			AKZ 4 ST		
5/26/46.7			5/47.5/27			6/27/48.5			6/27/50.5			6/27/57.8			6/27/50.2		
0.8 x 1.6			0.8 x 1.6			1 x 1			0.8 x 1.6			0.8 x 2.4			0.8 x 1.6		
7 mm/M 2.5/3.0 x 0.5			7 mm/M 2.5/3.0 x 0.5			9 mm/M 3/3.5 x 0.6			9 mm/M 3/3.5 x 0.6			9 mm/M 3/3.5 x 0.6			-		
250 V/8 A/2.5 mm ²			250 V/8 A/2.5 mm ²			250 V/10 A/4 mm ²			250 V/10 A/4 mm ²			250 V/10 A/4 mm ²			250 V/10 A/2.5 mm ²		
4 kV/3			4 kV/3			4 kV/3			4 kV/3			4 kV/3			4 kV/3		
0.4...0.6			0.4...0.6			0.5...1.0			0.5...1.0			0.5...1.0					
1			1			2			2			2					
0.5...4			0.5...4			0.5...4			0.5...4			0.5...4					
1.5...2.5			1.5...2.5			1.5...4			1.5...4			1.5...4					
0.5...2.5			0.5...2.5			0.5...4			0.5...4			0.5...4					
0.5...2.5			0.5...2.5			0.5...4			0.5...4			0.5...4					
0.5...2.5			0.5...2.5			0.5...4			0.5...4			0.5...4					
0.13...4.0 / A3			0.13...4.0 / A3			0.13...4.0 / A3			0.13...4.0 / A3			0.13...4.0 / A3			0.5...2.5 / -		
24			24			20			20			20			20		
24			24			20			20			20			20		
300 V/10 A/26...14 AWG			300 V/10 A/26...14 AWG			300 V/10 A/26...14 AWG			300 V/10 A/26...14 AWG			300 V/10 A/26...14 AWG			300 V/10 A/26...14 AWG		
300 V/10 A/26...10 AWG			300 V/10 A/26...10 AWG			300 V/10 A/24...12 AWG			300 V/10 A/24...12 AWG			300 V/10 A/24...12 AWG			300 V/10 A/24...12 AWG		
Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
AKZ 2.5 K	0695460000	100	AKZ 2.5 K	0695960000	100	AKZ 4 T	0445860000	100	AKZ 4 T	0344160000	100				AKZ 4 ST	0439260000	100
AKZ 2.5 K	0695660000	100	AKZ 2.5 K	0696160000	100				AKZ 4 T	0344060000	100						
												AKZ 4 T	0366460000	100			
												AKZ 4 T	0461660000	100			
AP (2.5)	0697260000	50	AP (2.5)	0697260000	50	AP (1.5)	0294460000	20	AP (1.5)	0294460000	20	AP (1.5)	0294460000	20	AP (1.5)	0294460000	20
TW (1.5)	0318560000	20	TW (1.5)	0318560000	20	TW (1.5)	0348260000	50	TW (1.5)	0348260000	50	TW (1.5)	0348260000	50	TW (1.5)	0348260000	50
						TSch 4	0363360000	100	TSch 4	0363360000	100	TSch 4	0363360000	100			
Q 2	0368200000	50	Q 2	0368200000	50	Q 2	0336400000	50	Q 2	0336400000	50	Q 2	0336400000	50	Q 2	0369000000	50
Q 3	0368300000	50	Q 3	0368300000	50	Q 3	0336500000	50	Q 3	0336500000	50	Q 3	0336500000	50	Q 3	0369100000	50
Q 4	0368400000	50	Q 4	0368400000	50	Q 4	0336600000	50	Q 4	0336600000	50	Q 4	0336600000	50	Q 4	0369200000	50
Q 10	0368500000	20	Q 10	0368500000	20	Q 10	0368600000	20	Q 10	0368600000	20	Q 10	0368600000	20	Q 10	0369300000	20
						VL 2	0446700000	50	VL 2	0446700000	50	VL 2	0446700000	50			
						VH 10	0446600000	50	VH 10	0446600000	50	VH 10	0446600000	50			
						BSM 2.5x14	0266800000	100	BSM 2.5x14	0266800000	100	BSM 2.5x14	0266800000	100			
StB 8.5	0215700000	50	StB 8.5	0215700000	50	StB 8.5	0215700000	50	StB 8.5	0215700000	50	StB 8.5	0215700000	50	StB 8.5	0215700000	50
PS 2.3	0180400000	20	PS 2.3	0180400000	20	PS 2.3	0180400000	20	PS 2.3	0180400000	20	PS 2.3	0180400000	20	PS 2.3	0180400000	20
DEK 5	see "Accessories"		DEK 5	see "Accessories"		DEK 6	see "Accessories"		DEK 6	see "Accessories"		DEK 6	see "Accessories"		DEK 6	see "Accessories"	

SAK-series

Feed-through terminals for TS 15

for temperature measuring circuits


AKZ 4/TC



Weidmüller's thermocouple terminals are specially designed for transmitting the smallest voltages in temperature measuring circuits. Special busbars ensure that no false signals occur in the terminal when temperature differences exist in the positive and negative path. This high measuring precision is necessary for, e.g. test beds for aircraft engines, for complicated chemical processes, control systems, etc.

- Busbar material corresponds to thermal and compensating conductors
- Clear thermocouple marking
- 2-pole blocks per thermocouple
- Row width 14 mm, incl. end plate

Configuration of a temperature measuring circuit



- | | |
|--------------------------|-----------------------------------|
| 1 Thermocouple (sensor) | 4 Reference point |
| 2 Thermocouple terminals | 5 Supply conductors (to and from) |
| 3 Compensating conductor | 6 Measuring device |

The thermocouple terminals displayed in this measurement circuit are used to thermo-electrically transmit thermal e.m.f. of the thermocouple to the reference point and indicating device. Thermocouple terminals are required for the construction of temperature measuring circuits.

Dimensions		
Width/length/height (mm)	with TS 15	14/27/30
Insulation stripping length/clamping screw/screwdriver blade		9 mm/M 3/3.5 x 0.6
Rated data		
Rated voltage/current/cross-section		-/~/4 mm ²
Further technical data		
Tightening torque range	Nm	0.5...1
Torque setting with electric screwdriver type DMS 2		2
Clampable conductor		
Solid H07V-U	mm ²	0.5...4
Stranded H07V-R	mm ²	1.5...4
Flexible H07V-K	mm ²	0.5...4
Flexible H07V-K and ferrule DIN 46 228/1	mm ²	0.5...2.5
Flexible H07V-K and ferrule with plastic insul. collar	mm ²	0.5...2.5
Plug gauge acc. to IEC 60 947-1	Size	A 3
Continuous current of terminal for conductor size		
Continuous current rating of cross-connection 2-pole	A	
Continuous current rating of cross-connection multipole	A	
Ordering data		
Version		TS 15
for thermocouples	Type J	Cat. No.
Acc. to IEC 584	Type T	Fe - CuNi
(DIN 43710)	Type K	Cu - CuNi
	Type E	NiCr - Ni
		NiCr - CuNi
		Qty.
		1627010000 20
		on demand
		1677130000 20
		on demand

End plate			Cat. No.	Qty.
	AP (thickness 1.5 mm)	PA	0294460000	20
Partition			Cat. No.	Qty.
	TW (thickness 0.5 mm)	PA	0348260000	50

Thermocouple, type J	
Thermocouple acc. to IEC 584 (DIN 43 710)	Busbar
	Constantan (CuNi)
	Iron (Fe)



Marking tags		Print
	1 2 3 4 5 6	Material VO

DEK 5/6 **1789590000** 500

Mounting rails, end brackets, further marking material see "Accessories"

Multipole terminal blocks


Screw/tab connection

MK 5/2

KS 2...10

BK 2...12

MK 6/2...6/6



Dimensions/approvals

Width/length/height (mm)	40/18/15.5	see table below	see table below	see table below
--------------------------	------------	-----------------	-----------------	-----------------

Insulation stripping length/clamping screw/screwdriver blade	5 mm/M 2.5/3.5 x 0.6	8 mm/M 3/4.0 x 0.8	8 mm/M 3/4.0 x 0.8	9 mm/M 4/4.0 x 0.8
--	----------------------	--------------------	--------------------	--------------------

Rated data according to IEC 60 947-7-1

Rated voltage/current/cross-section	500 V/24 A/2.5 mm ²	500 V/24 A/2.5 mm ²	400 V/32 A/4 mm ²	690 V/41 A/6 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity	6 kV/3	6 kV/3	6 kV/3	8 kV/3

Further technical data

Tightening torque range	Nm 0.4...0.45	0.5...0.7	0.5...0.7	1.2...2.0
Torque setting with electric screwdriver type DMS 2	1	2	2	4

Clampable conductor

Solid H07V-U	mm ² 0.5...4	0.5...4	0.5...4	0.5...6
Stranded H07V-R	mm ² 1.5...2.5	1.5...2.5	1.5...4	1.5...6
Flexible H07V-K	mm ² 0.5...2.5	0.5...2.5	0.5...4	0.5...6
Flexible H07V-K and ferrule DIN 46 228/1	mm ² 0.5...1.5	0.5...1.5	0.5...4	0.5...4
Flexible H07V-K and ferrule with plastic insul. collar	mm ² 0.5...1.5	0.5...1.2	0.5...4	0.5...4
Max. clamping range in mm ² /plug gauge acc. to IEC 60 947-1	Size 0.2...4.0 / A 2	0.2...4.0 / A 2	0.33...4.0 / A 3	0.33...6.0 / A 3

Rated data according to UL/CSA

Voltage/current/conductor size	UL	300 V/20 A/22...12 AWG	300 V/10 A/22...12 AWG	300 V/30 A/22...10 AWG
Voltage/current/conductor size	CSA	300 V/25 A/24...12 AWG	300 V/10 A/22...12 AWG	300 V/40 A/22...10 AWG

Ordering data

Versions


Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	
2-pole	MK 5/2 KrG	0243820000	100	KS 2 KrG ²⁾	0134420000	100	BK 2 KrG	0624720000	50	MK 6/2 KrG	0620420000	50
3-pole				KS 4 KrG ²⁾	0140320000	50	BK 3 KrG	0624920000	50	MK 6/3 KrG	0620320000	50
4-pole							BK 4 KrG	0625120000	50	MK 6/4 KrG	0620220000	20
4-pole												
6-pole				KS 6 KrG ²⁾	0140620000	50	BK 6 KrG	0625220000	50	MK 6/6 KrG	0620120000	20
6-pole												
8-pole												
8-pole												
10-pole				KS 10 KrG ²⁾	0141620000	20						
12-pole	Cover			Cover			BK 12 KrG	0625320000	50			
12-pole	D2 (for MK 5/2)	0244060000	50	D2 (for KS 2)	0134500000	100						
				D4 (for KS 4)	0140500000	50						
				D6 (for KS 6)	0140800000	50						
				D10 (for KS 10)	0141800000	20						




Cover D 2
(for MK 5/2)




Cover D 4
(for KS 4)



Cover




Marking tag cover



Dimensions

Type	a	b
BK 2	20	-
BK 3	31	11
BK 4	38	18
BK 6	52	32
BK 12	92	72.5



Dimens. Length/attach. dim.

Type	KRG
MK 6/2	23.5
MK 6/3	36.5
MK 6/4	49.5
MK 6/6	75.5

Expansion rivet

--	--	--	--	--

Marking strips

printed	1 ...	ELSo 2	0142800000	50	BSTb 28/2	0203600000	50	BSTb 17/6	0304600000	50
		ELSo 4	0142900000	50	BSTb 28/3	0203800000	50			
		ELSo 6	0143000000	50	BSTb 28/4	0197300000	50			
		ELSo 10	0143500000	50	BSTb 28/6	0197500000	50			
					BSTb 28/12	0198800000	50			
unprinted		ELSo 2	0142800000	50	BSTo 28/2	0203500000	50			
		ELSo 4	0142900000	50	BSTo 28/3	0203700000	50			
		ELSo 6	0143000000	50	BSTo 28/4	0197200000	50			
		ELSo 10	0143100000	50	BSTo 28/6	0197400000	50			
					BSTo 28/12	0198700000	50			


Mounting rails, end brackets, further marking material see "Accessories"

1) Projecting length = 1 mm. To be considered for the last terminal in a row!
Printed on top on request

2) Please order cover and marking strips separately.

Multipole terminal blocks

MF 1/6...1/12




UL CE

see below

SLS 2/2



SLS 2/4



UL CE

see below

Max. technical data

Dimensions/approvals

Width/length/height (mm)

Insulation stripping length/clamping screw/screwdriver blade

Rated data according to IEC 60 947-7-1

Rated voltage²⁾/current/cross-section

Rated impulse voltage VDE 0110/1.89/pollution severity

Further technical data

Tightening torque range

Nm

Torque setting with electric screwdriver type DMS 2

Clampable conductor

Solid H07V-U

mm²

Stranded H07V-R

mm²

Flexible H07V-K

mm²

Flexible H07V-K and ferrule DIN 46 228/1

mm²

Flexible H07V-K and ferrule with plastic insul. collar

mm²

Max. clamping range in mm²/plug gauge acc. to IEC 60 947-1 Size

Rated data according to UL/CSA

Voltage/current/conductor size

UL

Voltage/current/conductor size

CSA

Ordering data

PA

300 V/10 A/24...12 AWG

300 V/10 A/22...10 AWG

Type Cat. No. Qty.

MF 1/6 KrG²⁾ **0479720000** 100

MF 1/6 KrG³⁾ **0480020000** 100

MF 1/8 KrG²⁾ **0479820000** 50

MF 1/8 KrG³⁾ **0480120000** 50

MF 1/12 KrG²⁾ **0479920000** 50

MF 1/12 KrG³⁾ **0480220000** 50

8 mm/M 3.5/4.0 x 0.8

400 V²⁾/16 A/4 mm²

6 kV/3

0.8...1.6

3

0.5...4

1.5...4

0.5...4

0.5...4

0.5...4

0.33...4.0 / A 3

300 V/10 A/22...10 AWG

300 V/10 A/22...10 AWG


Type Cat. No. Qty.

SLS 2/2 KrG **0213420000** 100

SLS 2/4 KrG **0240420000** 50



SLS 2/4 KrG **0480320000** 50

Slotted



Dimensions

Type	a	b	c	d
MF 1/6	52	34	9.5	6.5
MF 1/8	68	50	9.5	6.5
MF 1/12	113 ^{+0.5}	102	8	7.5



Expansion rivet/insulation sleeve

IH

IH 2.8 **0386060000** 100

IH 6.3 **0386260000** 100

SN **0200100000** 500

IH 2.8 **0386060000** 100

IH 6.3 **0386260000** 100

Cover/marking strips

BSTb 10/6 **0240900000** 50

BSTb 10/8 **0241100000** 50

BSTb 10/12 **0209500000** 50

BSTo 10/6 **0240800000** 50

BSTo 10/8 **0241000000** 50

BSTo 10/12 **0209400000** 100

Mounting rails, end brackets, further marking material see "Accessories"

²⁾ Insulation sleeves are to be used for tab connections to maintain the rated voltage.

²⁾ Single tab
³⁾ Double tab

Multipole terminal blocks





Screw, solder, tab connection

MKL 2/12

MF 2/12

MKL 3/12

MKL 4/16



Dimensions/approvals		MKL 2/12			MF 2/12			MKL 3/12			MKL 4/16				
Width/length/height (mm)		88/23/15			75/24/6			110/23/16			103/24/16.5				
Insulation stripping length/clamping screw/screwdriver blade		5 mm/M 2.5/3.5 x 0.6			5 mm			5mm/M 2.5/3.5 x 0.6			5mm/M 2.5/3.5 x 0.6				
Rated data															
Rated voltage*/current/cross-section		125 V/20 A/2.5/1.5/1 mm ²			63 V/17.5 A/1.5/1 mm ²			400 V*/20 A/2.5/1.5/1 mm ²			400 V/20 A/2.5/1.5/1 mm ²				
Rated impulse voltage VDE 0110/1.89/pollution severity		2.5 kV/3			1.5 kV/3			6 kV/3			6 kV/3				
Further technical data															
Tightening torque range		Nm 0.4...0.45						0.4...0.45			0.4...0.45				
Torque setting with electric screwdriver type DMS 2		1						1			1				
Clampable conductor															
Solid H07V-U		mm ² 0.5...2.5						0.5...4			0.5...4				
Stranded H07V-R		mm ² 1.5...2.5						1.5...2.5			1.5...2.5				
Flexible H07V-K		mm ² 0.5...2.5						0.5...2.5			0.5...2.5				
Flexible H07V-K and ferrule DIN 46 228/1		mm ² 0.5...2.5						0.5...1.5			0.5...1.5				
Flexible H07V-K and ferrule with plastic insul. collar		mm ² 0.5...2.5						0.5...1.5			0.5...1.5				
Max. clamping range in mm ² /plug gauge acc. to IEC 60 947-1 Size		0.2...2.5 / A 2						0.33...4.0 / A 2			0.33...4.0 / A 2				
Rated data according to UL/CSA															
Voltage/current/conductor size		UL						300 V/25 A/22...12 AWG			300 V/25 A/22...12 AWG				
Voltage/current/conductor size		CSA						300 V/25 A/22...12 AWG			150 V/15 A/22...12 AWG				
Ordering data		Versions		Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
Horizontal		2-pole								MKL 3/2 KrG	0274920000**	100			
Other number of poles on demand		4-pole								MKL 3/4 KrG	0275120000**	100			
		6-pole								MKL 3/6 KrG	0275320000**	50			
		12-pole		MKL 2/12 PA	0241360000	50				MKL 3/12 KrG	0243620000**	20			
		16-pole											MKL 4/16 KrG	0262020000	20
Vertical		2-pole								MKL 3/2 KrG	0276020000*	100			
Other number of poles on demand		4-pole													
		6-pole								MKL 3/6 KrG	0276420000*	50			
		12-pole								MKL 3/12 KrG	0249920000*	20			
		16-pole											MKL 4/16 KrG	0244320000	20
		double-sided 2.8 x 0.8					MF 2/12 PA	0241860000	50						
		single-sided 0.8 x 1.6/2.8 x 0.8					MF 2/12 PA	0241760000	50						

* For terminals directly mounted next to each other, the rated voltage is reduced to 250 V.

** Rated voltage 250 V. For terminals directly mounted next to each other, the rated voltage is reduced to 125 V.

Expansion rivet/insulation sleeve		MKL 2/12			MF 2/12			MKL 3/12			MKL 4/16		
IH		SN 0200100000 500			IH 2.8 0386060000 100								
Marking strips													
printed		BSTb 28/12 0245700000 50						BSTb 28/4 0289800000 50			BSTb 28/16 0262200000 50		
1 ...		bottom						BSTb 28/6 0290000000 50			bottom		
		top 0278500000 50						BSTb 28/12 0245900000 50			top		
unprinted		BSTo 28/12 0245600000 50						BSTo 28/4 0289300000 50			BSTo 28/16 0262100000 50		
								BSTo 28/6 0289500000 50					
								BSTo 28/12 0245800000 50					

Mounting rails, end brackets, further marking material see "Accessories"


* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

1) Rated voltage 250 V

Multipole terminal blocks

Screw, solder, tab
connection
Modular design

AKB 4



AKZ 2.5



ASK 1



Max. technical data

Dimensions/approvals	AKB 4	AKZ 2.5	ASK 1
Width/length/height (mm)	6/27/23	5/25.5/26.5	8/58/30.5
Insulation stripping length/clamping screw/screwdriver blade	9 mm/M 3/3.5 x 0.6	7 mm/M 2.5/3 x 0.5	9 mm/M 3/3.5 x 0.6
Rated data according to IEC 60 947-7-1			
Rated voltage/current/cross-section	400 V/32 A/4 mm ²	250 V/24 A/2.5 mm ²	500 V/6.3 A/4 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity	6 kV/3	4 kV/3	6 kV/3
Further technical data			
Tightening torque range Nm	0.5...1.0	0.4...0.6	0.5...1.0
Torque setting with electric screwdriver type DMS 2	2	1	2
Clampable conductor			
Solid H07V-U mm ²	0.5...6	0.5...4	0.5...4
Stranded H07V-R mm ²	1.5...4	1.5...2.5	1.5...4
Flexible H07V-K mm ²	0.5...4	0.5...2.5	0.5...4
Flexible H07V-K and ferrule DIN 46 228/1 mm ²	0.5...4	0.5...2.5	0.5...2.5
Flexible H07V-K and ferrule with plastic insul. collar mm ²	0.5...4	0.5...2.5	0.5...2.5
Max. clamping range in mm ² /plug gauge acc. to IEC 60 947-1 Size	0.33...4.0 / A3	0.13...4.0 / A3	0.13...4.0 / A3
Continuous current rating of cross-connection 2-pole A	32	24	(QB 2...4) 10
Continuous current rating of cross-connection multipole A	32	24	
Rated data according to UL/CSA			
Voltage/current/conductor size UL	300/250 V/27 A/22...12 AWG	300 V/10 A/22...12 AWG	300 V/10 A/22...12 AWG
Voltage/current/conductor size CSA	300 V/10 A/22...12 AWG	300 V/10 A/26...10 AWG	300 V/6.3 A/26...12 AWG
Ordering data			
	Type Cat. No. Qty.	Type Cat. No. Qty.	Type Cat. No. Qty.
PA	AKB 4 PA 0321560000 100	AKZ 2.5 0697160000 100	ASK 1 PA 0376960000 100
Blue PA	0321580000 100	AKZ 2.5 0697180000 100	
	Direct mounting with BB 1 please order separately	Direct mounting with BB 4 please order separately	(for G fuse inserts 5x 20 without indicator)
End plate/attachment bracket (thickness mm)			
AP	BB 1 (7) 0320560000 50	BB 4 (7.5) 0697560000 50	
PA	BS M 3 x 15 0359000000 100		
Blue PA		AP (2.5) 0697360000 50	AP (1.5) 0380360000 20
		AP (2.5) 0697380000 50	
Partition (thickness mm)			
	TW PA (0.5) 0348260000 50		
Small partition			
	TSch 4 0363360000 100		
Cross-connection			
Q 3 QB 4	Q 2 0336400000 50	Q 2 0368200000 50	QB 2 ¹⁾ 0461100000 50
	Q 3 0336500000 50	Q 3 0368300000 50	QB 3 ¹⁾ 0461200000 50
	Q 4 0336600000 50	Q 4 0368400000 50	QB 4 ¹⁾ 0461300000 50
	Q 10 0368600000 20	Q 10 0368500000 20	
Switchable cross-connection link			
VL BS VH	VL 2 0446700000 50		
	VH 10 0446600000 50		
	BS M 2.5x14 0266800000 100		
Test plug/socket			
PS StB	StB 8.5 0215700000 50	StB 8.5 0215700000 50	
	PS 2.3 0180400000 20	PS 2.3 0180400000 20	
Cover/contact sleeve			
K sleeve	AD 4 0303400000 50		
	BSKM2.5x18 0303300000 100		K sleeve 0553300000 100
Marking tags			
DEK Standard	DEK 6 see "Accessories"	DEK 5 see "Accessories"	DEK 6.5 see "Accessories"
Mounting rails, end brackets, further marking material see "Accessories"			

¹⁾ The conductor cross-section is reduced to max. 2.5 mm² when QB is used.

* With contact sleeve 19 A

Feed-through terminals

ADK 1 T



6/22/50.5
19.5...21.9
9 mm/M 3/3.5 x 0.6
400 V/8 A/4 mm ²
6 kV/3
0.5...1.0
2
0.5...4
1.5...4
0.5...4
0.5...2.5
0.5...2.5
0.13...4.0 / A3
10
300/250 V/10 A/26...12 AWG
300 V/15 A/26...12 AWG
1.5 Qty. 2.5 Qty.
0372260000 100
0366360000 100

Type	Cat. No.	Qty.
AP (3)	0476260000	50

TW (0.5)	0442300000	50
----------	-------------------	----

PS 2.3	0180400000	20
StB 8.5	0215700000	50

SST 1.2	0306600000	
---------	-------------------	--

DEK 6	see "Accessories"	
-------	-------------------	--

AKZ 2.5 K



5/26/45.5
22.4...23.6
7 mm/M 2.5/3.0 x 0.5
250 V/8 A/2.5 mm ²
4 kV/3
0.4...0.6
1
0.5...2.5
1.5...2.5
0.5...2.5
0.5...2.5
0.5...2.5
0.13...2.5 / A2
10
300/250 V/10 A/22...12 AWG
300 V/10 A/26...10 AWG
Cat. No. Qty.
0109160000 solder tag 100
0108960000 100

Type	Cat. No.	Qty.
AP (3)	0697260000	50

TW (1.5)	0318560000	20
----------	-------------------	----

PS 2.3	0180400000	20
StB 8.5	0215700000	50

IH 2.8	0386060000	100
--------	-------------------	-----

DEK 5	see "Accessories"	
-------	-------------------	--

ADK 1 FT



6/22/52
24
11 mm/M 2.5/3.5 x 0.6
250 V/10 A/2.5 mm ²
4 kV/3
0.4...0.6
1
0.5...2.5
1.5...2.5
0.5...2.5
0.5...1.5
0.5...1.5
0.33...2.5 / A2
10
300 V/3 A/22...14 AWG
Cat. No. 1.5 Qty.
0176960000 100


Type	Cat. No.	Qty.
AP (3)	0476260000	50

TW (0.5)	0442300000	50
----------	-------------------	----

SST 1.2	0306600000	
---------	-------------------	--

DEK 6	see "Accessories"	
-------	-------------------	--

MK 2/12



86/15/23
8
5
63 V/20 A/2.5/1.5 mm ²
1.5 kV/3
0.4...0.45
1
0.5...2.5
1.5...2.5
0.5...2.5
0.5...2.5
0.5...2.5
0.2...2.5 / A2
10
300 V/10 A/24...12 AWG
300 V/10 A/24...12 AWG
Cat. No. Qty.
0241460000 50

Type	Cat. No.	Qty.
AP (3)	0476260000	50

TW (0.5)	0442300000	50
----------	-------------------	----

SN	0200100000	500
----	-------------------	-----

BSTb 28/12	024570...	50
BSTo 28/12	024560...	50

SAK-series

Rack-mounted interface systems

TOP 1.5 F/32




SP 10 FF²⁾ SP 10 LF³⁾



SP 60 FF²⁾ SP 60 LF³⁾



SP 90 FF²⁾ SP 90 LF³⁾



Dimensions

Width/length/height (mm)		40.2/110.6/29.5	42/46.5/170/28	40/45.5/162.5/110	40/45.5/228.5/110
Hole spacing/mounting dimensions	mm	101.6/20.3	147	151/90	217/90
Insulation stripping length/clamping screw/screwdriver blade		10 mm/M 2.5/3.5 x 0.6			

Rated data

Rated voltage [*] /current/cross-section		250 [*] V/6 A/1.5/1 mm ²	1000 [*] V/16 A/2.5/1.5 mm ²	400 [*] V/16 A/2.5/1.5 mm ²	400 [*] V/16 A/2.5/1.5 mm ²
Rated impulse voltage VDE 0110/1.89/pollution severity		4 kV/3	6 kV/3	6 kV/3	6 kV/3

Further technical data

Tightening torque range	Nm	0.4...0.7			
Torque setting with electric screwdriver type DMS 2		1			

Clampable conductor

Solid H07V-U	mm ²	0.5...2.5			
Stranded H07V-R	mm ²	1.5			
Flexible H07V-K	mm ²	0.5...1.5			
Flexible H07V-K and ferrule DIN 46 228/1	mm ²	0.5...1.5			
Flexible H07V-K and ferrule with plastic insul. collar	mm ²	0.5...1.5			
Plug gauge acc. to IEC 60 947-1	Size	A1			

Ordering data

	Version	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
Pin 1.0 x 1.0	PA	TOP1.5F/32	0443160000 ¹⁾	5									
Pin 0.8 x 2.8 (push-on), unprinted	PA												
Pin 0.8 x 2.8 (push-on), printed, 1...32	PA												
Pin 0.8 x 2.8 (push-on), printed, 1...32, blue	PA												
6 x plug (6.3 x 0.8)	KrG				SP 10 FF	0456220000	10	SP 60 FF ⁴⁾	0340320000	1	SP 90 FF**	0248120000	1
6 x plug (6.3 x 0.8), blue	KrG							SP 60 FF ⁴⁾	0340370000	1			
6 x plug (6.3 x 0.8), bzw. 12 x 2.8 x 0.8 slotted	KrG										SP 90 FF**	0608920000	1
6 x plug (6.3 x 0.8), bzw. 12 x 2.8 x 0.8 slotted, blue	KrG												
3 x plug (6.3 x 0.8) / 1 x solder per pole	KrG							SP 60 LF ⁴⁾	0343720000	1	SP 90 LF**	0248220000	1
3 x plug (6.3 x 0.8) / 1 x solder per pole, blue	KrG							SP 60 LF ⁴⁾	0343770000	1			
3 x plug (6.3 x 0.8 bzw. 6 x 2.8 x 0.8) / 1 x solder	KrG							SP 60 LF ⁵⁾	0124520000	1			
3 x plug (6.3 x 0.8 bzw. 6 x 2.8 x 0.8) / 1 x solder, blue	KrG							SP 60 LF ⁵⁾	0124570000	1			
2 x direct connection, 1 x Pin 0.8 x 1.6	PA										printed:		

Insulation sleeves

Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
IH 2.8	0386060000	100	IH 2.8	0386060000	100	IH 2.8	0386060000	100	IH 2.8	0386060000	100
			IH 6.3	0386260000	100	IH 6.3	0386260000	100	IH 6.3	0386260000	100

Marking tags

	Print			
dekafix	for group markers		FW 5	see "Accessories"

Mounting rails, end brackets, further marking material see "Accessories"

* Insulation sleeves are to be used for tab connections to maintain the rated voltage.

¹⁾ Rated voltage 125 V

²⁾ FF = Tab-Tab
³⁾ LF = Solder-Tab

Rack-mounted interface systems


RV 8/8 long



RV 8/8 short



RV 8/9 long



RV 8/9 short



Technical data acc. to VDE

Pin versions (intern)

0.8 x 2.4/1 x 1

0.8 x 2.4/0.8 x 2.4

Plug adapter



1-pole

for connection of solid and flexible conductors from 0.75 to 1.5 mm² directly on to the pins of the interface system.


125 V/-/-			125 V/-/-		
Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
	0468860000	1		0467160000	1
	0468960000	1		0467260000	1
Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
DSA 1	0576060000	50	DSA 1	0576060000	50

105 V/-/-			125 V/-/-		
Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
	0498960000	1		0444060000	1
	0499060000	1		0545960000	1
with shield pins			with shield pins		
Type	Cat. No.	Qty.	Type	Cat. No.	Qty.
DSA 1	0576060000	50	DSA 1	0576060000	50

RV 8/20 short



RV 8/56 short



Technical data acc. to VDE

Pin versions (internal)


0.8 x 2.4/1 x 1

0.8 x 2.4/0.8 x 2.4

Additional versions on request

125 V/-/-		
Cat. No.	Qty.	
0544460000	1	

125 V/-/-		
Cat. No.	Qty.	
0462260000	1	
0533060000	4	



Type	Size A		Size B	
	in mm		in mm	
RV 8/8 K	81	40.64		
RV 8/9 K	89	40.64		
RV 8/8 L	93	40.64		
RV 8/9 L	100	40.64		
RV 8/20 K	187,62/31.5	63		
RV 8/56 K	460/31.5	63		

(K = short/L = long)

Cat. No.	RV	a	b	c
0468860000	8/8 L	26	20	200
0468960000	8/8 L	26	26	206
0467160000	8/8 K	26	20	84
0467260000	8/8 K	26	26	89
0119360000	8/20 K	26	20	84
0544460000	8/20 K	26	26	89
0462260000	8/56 K	26	20	84
0533060000	8/56 K	26	26	89

Mounting rails, end brackets, further marking material see "Accessories"

SAK-series