



THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC CM	DIST 00	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
	L4	REVISED PER ECO-11-004917	11MAR11	RK	HMR

1. PACKAGED IN HEAT SEALED 3 MIL POLYBAG.
2. MIL NO. MS3367-4.
3. OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI

UNIT OF MEASURE	A	B	C	D	E	L		MAX BUNDLE DIAMETER	MIN TENSILE STRENGTH
INCHES	.175	.169	.096	.151	.037	4.07		.75	18 LBS
MM	4.45	4.29	2.44	3.84	.94	103		19.1	8.165 KG



3 OBSOLETE	100	NATURAL HALAR	3-604771-0
	1000	NATURAL	2-604771-9
	1000	BLACK	2-604771-0
	100	NATURAL	1-604771-9
	100	BLACK	1-604771-0
	QTY/BAG	COLOR	PART NUMBER

METRIC

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS: mm [INCHES]	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± - 4 PLC ± - ANGLES ± -	DWN 07-NOV-03 K. WHITAKER	STE TE Connectivity	
	MATERIAL NYLON 6/6	CHK D. COLEY 07-NOV-03		
		NAME CABLE TIE, 4 INCH		RESTRICTED TO
		PRODUCT SPEC	SIZE A3	CAGE CODE 00779
		APPLICATION SPEC	DRAWING NO C-604771	REV L4
		WEIGHT	SCALE 1:1	
		CUSTOMER DRAWING		SHEET 1 OF 1