

## Specification Sheet

Part Number: TAG24T1-100B



Thermal Transfer Labels, Self-Laminating, 2.0" x .5" x 1.43", 1 Across, VL, White, 1000/roll

Article Number	596-00008
Type	TAG24T1
Color	White (WH)
Features & Benefits	<ul style="list-style-type: none"><li>• Clear laminate provides excellent abrasion protection and chemical resistance.</li><li>• Flexible material bends around small gauge wires and tight bends.</li><li>• Labels are UL recognized and include a strong acrylic adhesive for indoor and outdoor use.</li><li>• Standard 3" core can be used with HellermannTyton thermal transfer printers or most standard brands.</li></ul>
Quantity Per	roll

### Product Description

HellermannTyton self-laminating thermal transfer printer labels are made of a flexible vinyl film with a white printable surface that easily conforms to wires. These labels include a clear "tail" that laminates printed text when applied. Labels are UL recognized for indoor and outdoor use and feature a strong acrylic adhesive designed to bond to both large and small diameter wires.

<b>Short Description</b>	Thermal Transfer Labels, Self-Laminating, 2.0" x .5" x 1.43", 1 Across, VL, White, 1000/roll
<b>Global Part Name</b>	TAG24T1-100B-WH
<b>Width W (Imperial)</b>	2.0
<b>Width W (Metric)</b>	50.8
<b>Bundle Diameter Min (Imperial)</b>	0.137
<b>Bundle Diameter Min (Metric)</b>	3.5
<b>Bundle Diameter Max (Imperial)</b>	0.29
<b>Bundle Diameter Max (Metric)</b>	7.37
<b>Thickness T (Metric)</b>	25
<b>Width of Liner (Metric)</b>	55.9
<b>Width of Liner (imperial)</b>	2.20
<b>Material</b>	Type 100B
<b>Material Shortcut</b>	100B
<b>Adhesive</b>	Acrylic
<b>Halogen free</b>	No

<b>Adhesive Operating Temperature</b>	-51°F to +200°F (-46°C to +93°C)
<b>Operating Temperature (Metric)</b>	-40°F to +194°F (-40°C to +90°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Certification/Specification WEB</b>	UL-Recognized
<b>UL Recognized (US)</b>	Yes
<b>Package Quantity(Imperial)</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Customs Number</b>	3919102055
<b>Labels per Column</b>	1
<b>Labels per Row</b>	1
<b>Weight (Metric)</b>	1.176
<b>Weight (Imperial)</b>	2.57