


Material: UL94 V-2 Nylon 6/6
 Color: Natural

Part No.	A	
	mm	in
CBLS205A	3.2	.126
CBLS210A	4.8	0.187
CBLS215A	6.3	.248
CBLS220A	8	.315
CBLS225A	10	.394
CBLS230A	12	.472
CBLS235A	14	.551
CBLS240A	16	.630
CBLS245A	18	.709
CBLS250A	25	.984

TO SNAP LOCK IN A 3 (.118) Ø HOLE, IN A
 1.2 - 1.7 (.047 - .067) PANEL THICKNESS



TO SNAP LOCK IN A 4.8 (.187) Ø HOLE, IN
 A 0.8 - 2.2 (.031 - .086) PANEL THICKNESS

TOLERANCES
 UNLESS NOTED
 ≤ 5 mm ±0.2
 5 - 20 mm ±0.3
 20 - 40 mm ±0.4
 40 - 60 mm ±0.5
 60 - 100 mm ±0.8
 ≥ 100 mm ±1.0

TITLE: DUAL LOCKING CIRCUIT BOARD SUPPORT

FILE: CBLS2XX	DWN: CLC
SHEET: 1 OF 1	DT: 01/08/15
SHEET SIZE: A	
RE:	



DWG IN
MM (IN)

PART #

SEE TABLE

PRINT
TYPE

CA