

## Bus system cable - VS-OE-OE-94D-100,0 - 1416334

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



CAT5e-SF/UTP cable, 4 x 2 x 26 AWG, stranded (7-wire), shielded, outer sheath: PVC, outside diameter 6.4 mm, cable ring 100 m

### Key commercial data

Packing unit	0
Minimum order quantity	1
Catalog page	Page 296 (PC-2011)
GTIN	 4 046356 474559
Custom tariff number	85444290
Country of origin	GERMANY

### Technical data

#### Mechanical characteristics

Number of positions	8
Shielded	Yes
Cable diameter	6.40 mm
Cable structure	4x2xAWG26/7; SF-UTP
Smallest bending radius, fixed installation	60 mm (cable, fixed installation)
Smallest bending radius, movable installation	60 mm (for installation)
Length of cable	100 m
Ambient temperature (operation)	-40 °C ... 80 °C (cable, fixed installation)
Ambient temperature (operation)	-40 °C ... 80 °C (cable, flexible installation)

#### Material data

Outer sheath, material	PVC (reinforced) UV-resistant
External sheath, color	Deep black RAL 9005

#### Electrical characteristics

Transmission characteristics (category)	CAT5 (IEC 11801:2002), CAT5e (TIA 568B:2001)
---	--

## Bus system cable - VS-OE-OE-94D-100,0 - 1416334

### Classifications

#### eclass

eCl@ss 4.0	27060307
eCl@ss 4.1	27060307
eCl@ss 5.0	27060307
eCl@ss 5.1	27060307
eCl@ss 6.0	27060307
eCl@ss 7.0	27060307

#### etim

ETIM 3.0	EC000830
ETIM 4.0	EC000830

#### unspsc

UNSPSC 6.01	26121616
UNSPSC 7.0901	26121616
UNSPSC 11	26121604
UNSPSC 12.01	31261501
UNSPSC 13.2	26121616

### Accessories

#### Accessories

#### Tools

Tool - VS-CABLE-STRIP-VARIO - 1657407



Stripping tool, for the multi-level stripping of shielded cables